



**Report of Materials and
Equipment Acceptance Division**

NYC Department of Buildings
280 Broadway, New York, NY 10007
Patricia Lancaster, FAIA, Commissioner
(212) 566-5000, TTY: (212) 566-4769

Pursuant to Administrative Code Section 27-131, the following equipment or material has been found acceptable for use subject to the terms and conditions contained herein.

MEA 123-88-E Vol.8

Manufacturer: Alliance Laundry Systems LLC, Shepard Street,
P.O. Box 990, Ripon, Wisconsin 54971-0990

Trade Name(s): Unimac, Huebsch, Speed Queen

Product: Commercial Gas Clothes Dryer

Pertinent Code Section(s): 27-800, 27-807, RS 14-2 (ANSI Z223.1)

Prescribed Test(s): RS 14-6 (ANSI Z21.5)

Laboratory: CSA International

Test Report(s): CSA 1062900 dated, December 7, 2005

Description: - Commercial gas fired clothes dryer designed for commercial and coin operated usage. Unit consists of steel main burners, an intermittent ignition system comprising igniter with sensor and ignition control, combination gas pressure regulator, and temperature control. Units with model numbers, trade names and input ratings are as follows:

SINGLE UNITS		
Brand Name	Model Listing	Input Heat Rating (BTU/H)
Huebsch	HDG109*F, HDG909*F, HDGT09*F, HDGY09*F	25,000
Speed Queen	SDG009*F, SDG109*F, SDG109*F1124, SDG509*F, SDG909*F, SDG909*F1124, SDGA09*J, SDGB09*J, SDGF09*J, SDGM09*J, SDGT09*F, SDGX09*F, SDGY09*F, SFGB09*J, SFGF09*J, SFGT09*F, SFGX09*F, SFGY09*F	
Unimac	UDG009*F	

STACKED UNITS		
Brand Name	Model Listing	Input Heat Rating (BTU/H)
Huebsch	HSG119*F, HSG919*F, HSGT19*F, HSGY09*F, HSGY19*F	50,000 (25,000 per Pocket)
Speed Queen	SSG009*F, SSG109*F, SSG109*F1124, SSG119*F, SSG509*F, SSG909*F, SSG909*F1124, SSG919*F, SSGA19*J, SSGB09*J, SSGB19*J, SSGF09*J, SSGF19*J, SSGT09*F, SSGT19*F, SSGX09*F, SSGX19*F, SSGY09*F, SSGY19*F,	
Unimac	USG009*F	

- Notes:**
1. The model numbers SSG, HSG and USG series consist of two stacked units, each having an input of 25,000 BTU.
 2. Units may be installed on combustible flooring. Minimum installed clearances from combustible construction shall be as follows: Sides – 0 inches; rear – 2 inches (4 inches for stacked units); Ceiling – 12 inches (2 inches for stacked units); front – 2 inches.

Terms and Conditions: The above described commercial gas-fired clothes dryers, be accepted for use when fired by natural gas only. Provision for combustion air and ventilation air shall be made in accordance with Section 27-807 and other applicable code requirements. All shipments and deliveries of such equipment shall be provided with a metal tag, suitably placed, certifying that the equipment shipped and delivered is equivalent to those tested and accepted for use, as provided in Section 27-131 of the Building Code. Approval of all electrical equipment, apparatus, materials and devices shall be obtained from the Bureau of Electrical Control before installation.

Final Acceptance May 4, 2006

Examined By Simon Derkholm