

NYC Department of Buildings 280 Broadway, New York, NY 10007 Patricia Lancaster, FAIA, Commissioner (212) 566-5000, TTY: (212) 566-4769

Pursuant to Administrative Code Section 27-131, the following equipment or material has been found acceptable for use subject to the terms and conditions contained herein.

MEA 115-07-M

Manufacturer:	Maharam, 45 Rasons Court, Hauppauge, NY 11788	
Trade Name(s):	Inox Basic, Inox Basket, Inox Texture, Inox Structure	
Product:	Wallcovering, panel, upholstered wall fabric	
Pertinent Code Section(s):	27-348	
Prescribed Test(s):	RS 5-5 (ASTM E 84), UPITT Toxicity	
Laboratory:	Commercial Testing – ASTM E 84 Anderson Laboratories – UPITT Toxicity	
Test Report(s):	<u>UPITT</u> : Inox Basic – Test # 650 Inox Basket – Test # 648 Inox Structure & Inox Texture – Test # 649 <u>ASTM E 84</u> : Inox Basic – Test # 06-04010 Inox Basket – Test # 06-04012	
	Inox Structure – Test # 06-04011 Inox Texture – Test # 06-07485	

Description: Wallcovering, panel, upholstered wall textile which contains polyethylene/ polyolefin. Material has a stain-resistant finish with acrylic backing. Material is manufactured in 54" wide, 12.8 – 14.8 oz/linear yard.

Product Covered

	Flame Spread Rating	Smoke Density Rating
Inox Basic	15	10
Inox Basket	25	25
Inox Structure	15	30
Inox Texture	15	70

Terms and Conditions: The above-described wall-covering material is accepted with the following conditions.

- 1. Material is for interior-finish with Class 'A' flame spread rating, as indicated above.
- 2. Material with smoke density greater than 25 shall not be used in exits or corridors.
- 3. Material with smoke density greater than 50 shall not be used in occupancy group H-1 and H-2.
- 4. All shipments and deliveries of such materials shall be provided with a metal tag, suitably placed, certifying that the materials shipped or delivered are equivalent to those tested and acceptable for use, as provided in Section 27-131 of the New York City Building Code.

<u>NOTE</u>: In accordance with Section 27-131(d), all materials tested and accepted for use shall be subject to periodic retesting as determined by the Commissioner; and any material which upon retesting is found not to comply with Code requirements or the requirements set forth in the approval of the Commissioner shall cease to be acceptable for the use intended. During the period for such retesting, the Commissioner may require the use of such material to be restricted or discontinued if necessary to secure safety.

Final Acceptance May 10, 2007 Examined By Sum Destrudan