



Report of Materials and Equipment Acceptance Division

NYC Department of Buildings
280 Broadway, New York, NY 10007
Patricia Lancaster, FAIA, Commissioner
(212) 566-5000, TTY: (212) 566-4769

Pursuant to Administrative Code Section 27-131, the following equipment or material has been found acceptable for use subject to the terms and conditions contained herein.

MEA 429-06-E

Manufacturer: Selkirk Canada Corporation, 241 Arvin Avenue, Stoney Creek, Ontario L8E 2L9, Canada

Trade Name(s): Selkirk/Energy Vent ICA

Product: Factory-built chimney; building heating appliance type

Pertinent Code Section(s): 27-855

Prescribed Test(s): RS 15-8(A) ANSI/UL 103

Laboratory: Intertek Testing Services, Mississauga, Ontario

Test Report(s): File 297-0092-00, issued January 2001
File 297-0092-00, dated January 2001
File 276-345500-05, dated November 27, 2001

Description: Model ICA Industrial Chimney system is intended for use with certain process equipment and large oil- or gas-burning building heating appliances normally producing flue-gas temperatures of 1,400 degrees F, or less as applicable. This chimney system is comprised of numerous factory-made components which may be installed together in a modular fashion to achieve a variety of installation configurations.

Model ICA is available in sizes: 10", 12", 14", 16", 18", 20", 22", 24", 26", 28", 30", 32", 34" and 36" nominal inside diameters. Following is a list of components that make up this chimney system:

Part Number	Description
ICA*TC	Tee Cap
ICA*T	Tee
ICA*48	48" length chimney section
ICA*36	36" length chimney section
ICA*24	24" length chimney section
ICA*18	18" length chimney section
ICA*12	12" length chimney section
ICA*YT	Y Tee chimney section

ICA*IN	Increaser chimney section
ICA*PA	Pipe Adaptor chimney section
ICA*45	45 degree elbow chimney section
ICA*30	30 degree elbow chimney section
ICA*15	15 degree elbow chimney section
ICA*24ADJ	24" adjustable length chimney section
ICA*12ADJ	12" adjustable length chimney section
ICA*TS	Termination Section (rain cap adaptor)
ICA*SC	Storm Collar
ICA*WB	Wall Band
ICA*SB	Support Band (ceiling)
ICA*ARF	Adjustable Roof Flashing
ICA*FRS	Firestop Radiation Shield
ICA*FS	Firestop Spacer
ICA*GB	Guy Band
ICA*TCF	Tall Cone Flashing
ICA*RC	Rain Cap
ICA*WRS	Wall Radiation Shield
ICA*BS	Base Support
ICA*WSK	Wall Support Kit
ICA*RB	Roof Lateral Brace

Note: * Indicates chimney size (nominal inside diameter) in inches (e.g., ICA2045 is 20" diameter 45 degree elbow chimney section).

Terms and Conditions: The above-described factory-built chimney is accepted, where allowed, provided that:

1. All uses are intended for the venting of solid fuel, liquid or gas fuel exhaust gases, at a temperature not exceeding that recommended by the manufacturer under continuous operating conditions.
2. The chimney shall not be used with factory-built fireplaces unless specifically referenced in the laboratory listing of the fireplace units.
3. The chimney shall be installed in accordance with the New York City Building Code for listed factory-built chimneys.
4. All interior factory-built chimneys shall be enclosed in accordance with installation instructions provided by the manufacturer and in accordance with the Building Code.
5. All shipments and deliveries of such equipment shall be accompanied by a label or tag certifying that the material shipped or delivered is equivalent to that tested and acceptable for use, as provided for in Section 27-131 of the Building Code.

Final Acceptance

10/2/06

Examined By

Shyam S. [Signature]