



**NEW YORK CITY
ENVIRONMENTALLY PREFERABLE
PURCHASING (EPP)**

MINIMUM STANDARDS FOR GOODS



How To Use This Book

The *New York City Environmentally Preferable Purchasing (EPP) Minimum Standards for Goods* contains a complete list of goods covered by the environmentally preferable purchasing laws and incorporates all applicable standards specified or referenced in the laws and EPP rules. For a complete explanation of the EPP laws, please review the Mayor's Office of Contract Services (MOCS) Directive on *Environmentally Preferable Purchasing Laws: Coverage, Exemptions and Waivers*.

If you are purchasing any good, you must review the index to this book to determine whether an EPP standard exists for the product you are purchasing. If a standard does exist, include specifications in your procurement that meet or exceed the standards in the *New York City EPP Minimum Standards for Goods*. The standards in the book always include a definition and a standard. At your discretion, omit any EPP standards for which an EPP exemption or waiver applies

Your procurement must also include language, such as the following. You can make this language more explicit depending on the needs of your procurement:

This contract is subject to one or more of the following local laws and any rules enacted pursuant to such local laws: Local Law Number 118 of 2005, Local Law Number 119 of 2005, Local Law Number 120 of 2005 and Local Law Number 121 of 2005.

The vendor will be required to provide a report, for any period requested by an agency, on products specified by or for the City that appear in the *New York City EPP Minimum Standards for Goods*. The report must contain the following information: agency, item description, quantity ordered and dollar value of all items ordered over the period requested.

Please check the Mayor's Office of Contract Services (MOCS) website for revisions (<http://www.nyc.gov/html/moc/home.html>) and, if you have any questions, contact MOCS at (212) 788-0010.



New York City EPP Minimum Standards for Goods

Contents

Appliances - Commercial	11
1-1. Beverage Vending Machines	11
1-2. Bottled Water Coolers, Cold and/or Hot Water.....	12
1-3. Freezers	13
1-4. Fryers, Electric or Gas	14
1-5. Hot Food Holding Cabinets	15
1-6. Ice Cream Freezers	16
1-7. Refrigerators	17
1-8. Refrigerator-Freezers.....	18
1-9. Steam Cookers, Electric or Gas.....	19
Appliances - Residential.....	21
2-1. Clothes Washers	21
2-2. Dehumidifiers.....	22
2-3. Dishwashers, Standard-Sized.....	23
2-4. Freezers, Upright, Chest and Compact.....	24
2-5. Microwave Ovens.....	25
2-6. Refrigerators and Refrigerator-Freezers, Standard-Sized and Compact.....	26
Architectural Coatings	28
3-1. Clear Wood Coating - Clear-Brushing Lacquers	28
3-2. Clear Wood Coating - Conversion Varnishes	30
3-3. Clear Wood Coating - Lacquers (Including Lacquer Sanding Sealers).....	31
3-4. Clear Wood Coating - Sanding Sealers (Other Than Lacquers).....	32
3-5. Clear Wood Coating - Varnishes	34
3-6. Concrete Bond Breakers	36
3-7. Concrete Curing Compounds.....	37
3-8. Concrete Surface Retarders.....	38
3-9. Dry Fog Coatings	39
3-10. Faux Finishing Coatings	40
3-11. Fire-Resistive Coatings	41
3-12. Fire-Retardant Coatings - Clear.....	42
3-13. Fire-Retardant Coatings - Opaque	43



New York City EPP Minimum Standards for Goods

3-14. Flat Paint.....	44
3-15. Floor Coatings	45
3-16. Form Release Compounds	46
3-17. Graphic Arts Coatings (Sign Paints).....	47
3-18. High Temperature Coatings	48
3-19. Industrial Maintenance (IM) Coatings.....	49
3-20. Lacquers - Pigmented.....	51
3-21. Latex Paint – Consolidated	52
3-22. Latex Paint – Reprocessed White, Off-White and Pastel Colors.....	53
3-23. Latex Paint – Reprocessed Grey, Brown, Earthtones and Other Dark Colors	54
3-24. Low Solids Coatings	55
3-25. Magnesite Cement Coatings.....	56
3-26. Mastic Texture Coatings.....	57
3-27. Metallic Pigmented Coatings.....	58
3-28. Multi-Color Coatings	59
3-29. Nonflat High-Gloss Coatings.....	60
3-30. Nonflat Paint	61
3-31. Pre-Treatment Wash Primers	62
3-32. Primers for Flat Paint.....	63
3-33. Primers for Non-Flat Paint.....	64
3-34. Primers, Sealers, and Undercoaters	65
3-35. Quick-Dry Enamels.....	67
3-36. Quick-Dry Primers, Sealers, and Undercoaters	69
3-37. Recycled Coatings.....	71
3-38. Roof Coatings.....	72
3-39. Roof Coatings (Bituminous)	73
3-40. Roof Primers (Bituminous)	74
3-41. Rust Preventative / Anti-Corrosive Paint.....	75
3-42. Shellacs - Clear.....	76
3-43. Shellacs - Opaque.....	77
3-44. Specialty Primers, Sealers and Undercoaters.....	78
3-45. Stains	80



New York City EPP Minimum Standards for Goods

3-46. Swimming Pool Coatings and Swimming Pool Repair and Maintenance Coatings.....	81
3-47. Thermoplastic Rubber Coatings and Mastics.....	82
3-48. Waterproofing Concrete / Masonry Sealers.....	83
3-49. Waterproofing Sealers.....	84
3-50. Wood Preservatives.....	85
Electronics.....	87
4-1. Amplifiers/Pre-Amplifiers, Consumer.....	87
4-2. Answering Machines.....	88
4-3. Cassette Decks, Consumer.....	89
4-4. CD Players, Consumer.....	90
4-5. CD Recorders, Consumer.....	91
4-6. Clock Radios, Consumer.....	92
4-7. Combination TV with VCR, DVD, or VCR/DVD Units.....	93
4-8. Cordless Telephones.....	95
4-9. DVD Products.....	96
4-10. Equalizers, Consumer.....	97
4-11. Extended Power Adaptors.....	98
4-12. Laserdisc Players, Consumer.....	99
4-13. Mini- and Midi-Systems, Consumer.....	100
4-14. Minidisc Players, Consumer.....	101
4-15. Powered Speakers, Consumer.....	102
4-16. Receivers, Consumer.....	103
4-17. Table Radios, Consumer.....	104
4-18. Televisions.....	105
4-19. Tuners, Consumer.....	107
4-20. VCR.....	108
HVAC Equipment - Commercial.....	110
5-1. Air Conditioners, Air-Cooled.....	110
5-2. Air Conditioners, Gas/Electric Package Units.....	111
5-3. Chillers, Air-Cooled.....	112
5-4. Chillers, Water-Cooled.....	113
5-5. Heat Pumps, Air Source.....	114



New York City EPP Minimum Standards for Goods

HVAC Equipment - Residential	116
6-1. Air Conditioners, Central (<65,000 Btu/h).....	116
6-2. Air Conditioners, Central, Gas/Electric Package Units (<65,000 Btu/h).....	117
6-3. Air Source Heat Pumps (<65,000 Btu/h).....	118
6-4. Boilers and Boiler/Hot Water Heaters (<300,000 Btu/h).....	119
6-5. Ceiling Fans.....	120
6-6. Furnaces and Furnace/Hot Water Heaters (<340,000 Btu/h)	121
6-7. Ground Source Heat Pumps (Geothermal).....	122
6-8. In-Line Ventilating Fan.....	124
6-9. Programmable Thermostats.....	125
6-10. Range Hood and Bathroom /Utility Room Ventilating Fans	126
6-11. Room Air Cleaners.....	127
6-12. Room Air Conditioners.....	128
Lighting Products.....	130
7-1. Ballasts, Fluorescent, Linear T12 Lamps.....	130
7-2. Ballasts, Fluorescent, Linear T8 Lamps.....	131
7-3. Ballasts, Fluorescent, U-Bent T12 Lamps, 34-Watts.....	132
7-4. Ballasts, Fluorescent, U-Bent T8 Lamps, 32-Watts	133
7-5. Exit Signs.....	134
7-6. Lamps, Compact Fluorescent, Pin-Based	135
7-7. Lamps, Compact Fluorescent, Self-Ballasted, Screw Based	136
7-8. Lamps, Fluorescent Tube, Circline T9	137
7-9. Lamps, Fluorescent Tube, Linear T5, T8, T12	138
7-10. Lamps, Fluorescent Tube, U-Bent T8 & T12.....	140
7-11. Luminaires, Downlight, With Compact Fluorescent Lamps (13-32 Lamp Wattage).....	141
7-12. Luminaires, Downlight, With Metal Halide Lamps (<150 Watts).....	142
7-13. Luminaires, Fluorescent	143
7-14. Luminaires, Industrial HID, With High Pressure Sodium Lamps (<150 Lamp Wattage)	145
7-15. Luminaires, Industrial HID, With Metal Halide Lamps (<150 Lamp Wattage)	147
7-16. Luminaires, Residential	149
Landscape Products.....	151



New York City EPP Minimum Standards for Goods

8-1. Garden Hose	151
8-2. Hydraulic Mulch.....	152
8-3. Plastic Fencing	153
8-4. Soaker Hose	154
Miscellaneous Products - Construction	156
9-1. Building Insulation	156
9-2. Carpet Adhesives	157
9-3. Carpet Cushions.....	158
9-4. Carpet Cushion – Bonded Polyurethane.....	159
9-5. Carpet Cushion – Jute.....	160
9-6. Carpet Cushion – Rubber.....	161
9-7. Carpet Cushion – Synthetic Fibers.....	162
9-8. Carpets.....	163
9-9. Cement and Concrete.....	164
9-10. Channelizers.....	166
9-11. Delineators - Fixed.....	167
9-12. Delineators - Flexible	168
9-13. Electric Motors.....	169
9-14. Entry or Patio Doors, Residential.....	171
9-15. Floor Tiles	172
9-16. Flowable Fill.....	173
9-17. Insulation - Cellulose	174
9-18. Insulation - Foam-In-Place	175
9-19. Insulation - Glass Fiber Reinforced	176
9-20. Insulation - Laminated Paperboard	177
9-21. Insulation - Perlite Composition Board.....	178
9-22. Insulation - Phenolic Rigid Foam.....	179
9-23. Insulation - Plastic, Non-woven Batt.....	180
9-24. Insulation - Plastic Rigid Foam, Polyisocyanurate/Polyurethane: Rigid Foam	181
9-25. Insulation - Structural Fiberboard	182
9-26. Modular Threshold Ramps.....	183
9-27. Nonpressure Pipe	184



New York City EPP Minimum Standards for Goods

9-28. Playground Equipment	186
9-29. Residential Skylights.....	187
9-30. Residential Windows & Tubular Daylighting Devices	188
9-31. Restroom Dividers/Partitions, Steel.....	189
9-32. Roof Products.....	190
9-33. Roofing Materials	192
9-34. Shower Dividers/Partitions, Steel	193
9-35. Traffic Barricades	194
Miscellaneous Products - Non Construction	197
10-1. Mats, Rubber, Plastic or Rubber/Plastic Composite.....	197
10-2. Pallets, Wood, Plastic or Paperboard.....	198
10-3. Park Benches, Plastic.....	199
10-4. Signs, Plastic or Aluminum.....	200
10-5. Sign Posts/Supports, Plastic or Steel.....	201
10-6. Traffic Cones, Plastic or Crumb Rubber	202
10-7. Trash Bags, Plastic.....	203
10-8. Waste Receptacles / Recycling Containers, Office, Plastic,	204
Office Equipment	207
11-1. Combination Printer/Fax Machines	207
11-2. Computers	208
11-3. Computer Monitors (Min. 12 Inch Screen Size)	212
11-4. Computer Peripherals.....	213
11-5. Copiers.....	214
11-6. Fax Machines, Plain Paper	215
11-7. Mailing Machines	216
11-8. Multifunction Devices (Copier Plus)	217
11-9. Printers.....	219
11-10. Scanners.....	220
Paper Products	222
12-1. Bathroom Tissue, Commercial.....	222
12-2. Envelope Paper.....	224
12-3. Facial Tissue, Commercial.....	226



New York City EPP Minimum Standards for Goods

12-4. File Folders	228
12-5. General Purpose Industrial Wiper, Paper	230
12-6. Paper Napkins, Commercial	232
12-7. Paper Towels, Commercial	234
12-8. Reprographic Paper	236
12-9. Tablet Paper	238
Plumbing Fixtures	241
13-1. Lavatory Faucets.....	241
13-2. Showerheads, Residential and Commercial.....	242
13-3. Toilets, Residential and Commercial.....	243
13-4. Urinals, Residential and Commercial	244

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

Appliances - Commercial

1-1. Beverage Vending Machines

Covered Products:

This category shall cover beverage vending machines.

Definition:

Beverage Vending Machine: A self-contained system designed to accept consumer payments and dispense bottled, canned, and other sealed beverages at appropriate temperatures without on-site labor intervention.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

1-2. Bottled Water Coolers, Cold and/or Hot Water

Covered Products:

This category shall cover the following types of bottled water coolers, including compartment-type bottled water coolers: cold only bottled units; hot and cold bottled units; and cook and hold bottled units.

Definition:

Bottled Water Cooler: A freestanding device that consumes energy and dispenses water from removable 4 to 5-gallon plastic bottles commonly positioned on top of the unit.

Cold Only Bottled Units: These units dispense either cold water only, or both cold and room-temperature water.

Compartment-Type Bottled Water Cooler: A device used with an electric-discharge lamp to obtain the necessary circuit conditions (voltage, current, and waveform) for starting and operating.

Cook and Cold Bottled Units: A bottled water cooler which, in addition to the primary function of cooling and dispensing potable water, includes a refrigerated compartment with or without provisions for making ice.

Hot and Cold Bottled Units: These units dispense both hot and cold water. Some units may have a third room-temperature tap. Units have an electric resistance heater and a refrigeration cycle.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

1-3. Freezers

Covered Products:

This category shall cover the following types of commercial solid door freezers: reach-in cabinets; undercounter cabinets; and roll-in or roll-through cabinets.

Definition:

Commercial Solid-Door Freezer: A cabinet designed for storing food or other perishable items at temperatures of 0° Fahrenheit or below.

Reach-In Cabinet: An upright commercial, self-contained refrigeration cabinet with hinged, solid doors but excluding undercounter, roll-in, roll-through, or pass-through cabinets.

Roll-In or Roll-Through Cabinet: An upright, self-contained commercial refrigeration cabinet with hinged, solid doors that allows wheeled racks of product to be rolled into or through the refrigerator or freezer.

Self-Contained Refrigeration Cabinet: A refrigerator, freezer, or refrigerator-freezer which has the condensing unit built into the cabinet.

Undercounter Cabinet: An upright commercial, self-contained refrigeration cabinet without a worktop surface which has hinged, solid doors and which is intended for installation under a counter.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

1-4. Fryers, Electric or Gas

Covered Products:

This category shall cover commercial, open deep-fat fryers.

Definition:

Commercial, Open Deep-Fat Fryer: An appliance, including a cooking vessel, in which oil is placed to such a depth that the cooking food is essentially supported by displacement of the cooking fluid rather than by the bottom of the vessel. Heat is delivered to the cooking fluid by means of an immersed electric element or band-wrapped vessel (electric fryers), or by heat transfer from gas burners through either the walls of the fryer or through tubes passing through the cooking fluid (gas fryers).

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

1-5. Hot Food Holding Cabinets

Covered Products:

This category shall cover commercial hot food holding cabinets.

Definition:

Commercial Hot Food Holding Cabinet: An appliance that is designed to hold hot food at a specified temperature, which has been cooked using a separate appliance. This definition shall not apply to dual function equipment, such as cook-and-hold models.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

1-6. Ice Cream Freezers

Covered Products:

This category shall cover commercial ice cream freezers.

Definition:

Commercial Ice Cream Freezer: A cabinet designed for storing food or other perishable items at temperatures of -5° Fahrenheit (F) or below.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

1-7. Refrigerators

Covered Products:

This category shall cover commercial refrigerators.

Definition:

Commercial Refrigerator: A cabinet designed for storing food or other perishable items at temperatures above 32° Fahrenheit (F) but no greater than 40° F.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

1-8. Refrigerator-Freezers

Covered Products:

This category shall cover commercial refrigerator-freezers.

Definition:

Commercial Refrigerator-Freezer: A cabinet with two or more compartments, at least one of which is designed for storing food or other perishable items at temperatures above 32° Fahrenheit (F) but no greater than 40° F and at least one of which is designed for storing food or other perishable items at temperatures of 0° F or below.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

1-9. Steam Cookers, Electric or Gas

Covered Products:

This category shall cover 3, 4, 5 and 6-pan commercial steam cookers.

Definition:

Commercial Steam Cooker: A device (also referred to as a “compartment steamer”) with one or more food steaming compartments in which the energy in the steam is transferred to the food by direct contact. Models may include countertop models, wall-mounted models and floor-models mounted on a stand, pedestal or cabinet-style base.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

Appliances - Residential

2-1. Clothes Washers

Covered Products:

This specification shall cover standard-sized (>1.6ft³), front or top-loading clothes washers.

Definition:

Clothes Washer: An appliance designed to clean clothes, utilizing a water solution of soap or detergent and mechanical agitation or other movement.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

2-2. Dehumidifiers

Covered Products:

This specification shall cover dehumidifiers with daily water removal capabilities up to 57 liters (120.5 US pints).

Definition:

Dehumidifier: A self-contained, electrically operated, and mechanically refrigerated encased assembly consisting of (a) a refrigerated surface (evaporator) that condenses moisture from the atmosphere; (b) a refrigerating system, including an electric motor; (c) an air-circulating fan; and (d) means for collecting and/or disposing of the condensate.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

2-3. Dishwashers, Standard-Sized

Covered Products:

This specification shall cover standard-sized dishwashers.

Definition:

Dishwasher: A cabinet-like appliance which with the aid of water and detergent, washes, rinses, and dries (when a drying process is included) dishware, glassware, eating utensils, and most cooking utensils by chemical, mechanical and/or electrical means and discharges to the plumbing drainage system.

Standard-Sized: Having a capacity greater than or equal to eight place settings plus six serving pieces.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

2-4. Freezers, Upright, Chest and Compact

Covered Products:

This specification shall cover freezers.

Definition:

Freezer: A cabinet designed as a unit for the freezing and storage of food at temperatures of 0° Fahrenheit or below, and having a source of refrigeration requiring single phase, alternating current electric energy input only.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

2-5. Microwave Ovens

Covered Products:

This specification shall cover all microwave ovens.

Definition:

Microwave Oven: An appliance that electrically operated ovens using high-frequency electromagnetic waves that penetrate food, causing its molecules to vibrate and generate heat within the food to cook it very quickly.

Standby power: Refers to the electricity used by electrical products when they are switched off or not performing their primary purpose.

Standard:

Microwave Oven:

Recommended Standby Levels: 2 watts or less

Best Available Standby Level: 2 watts or less



New York City EPP Minimum Standards for Goods

2-6. Refrigerators and Refrigerator-Freezers, Standard-Sized and Compact

Covered Products:

This specification shall cover standard-sized and compact refrigerators and refrigerator-freezers.

Definition:

Refrigerator (Electric Refrigerator): A cabinet designed for the refrigerated storage of food at temperatures above 32° Fahrenheit (F) and below 39°F, configured for general refrigerated food storage, and having a source of refrigeration requiring single phase, alternating current electric energy input only. An electric refrigerator may include a compartment for the freezing and storage of food at temperatures below 32°F, but does not provide a separate low temperature compartment designed for the freezing and storage of food at temperatures below 8°F.

Refrigerator-Freezer (Electric Refrigerator-Freezer): A cabinet which consists of two or more compartments with at least one of the compartments designed for the refrigerated storage of food at temperatures above 32°F and with at least one of the compartments designed for the freezing and storage of food at temperatures below 8°F which may be adjusted by the user to a temperature of 0°F or below. The source of refrigeration requires single phase, alternating current electric energy input only.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

PAGE INTENTIONALLY LEFT BLANK



Architectural Coatings

3-1. Clear Wood Coating - Clear-Brushing Lacquers

Covered Products:

This category shall cover clear brushing lacquers to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Clear Wood Coating: Clear and semi-transparent coatings, including lacquers and varnishes applied to wood substrates to provide a transparent or translucent solid film.

Clear Brushing Lacquer: Any clear wood finish, excluding any clear lacquer sanding sealer, formulated with nitrocellulose or synthetic resins to dry by solvent evaporation without chemical reaction and to provide a solid, protective film, that is intended exclusively for application by brush and must comply with labeling requirements as defined in Title Six, Section 205.4 (e) of the New York Rules and Regulations.

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Sanding Sealer: Any clear or semi-transparent wood coating formulated for or applied to bare wood to seal the wood and to provide a coat that can be abraded to create a smooth surface for subsequent applications of coatings. A sanding sealer that also meets the definition of a lacquer is not included in this category, but it is included in the lacquer category.

Lacquer: A clear or opaque wood coating, including clear lacquer sanding sealers, formulated with cellulosic or synthetic resins to dry by evaporation without chemical reaction and to provide a solid, protective film.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.



New York City EPP Minimum Standards for Goods

Standard:

Clear Brushing Lacquers: Maximum Concentration of Volatile Organic Compounds in Grams per Liter : 275

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).



New York City EPP Minimum Standards for Goods

3-2. Clear Wood Coating - Conversion Varnishes

Covered Products:

This category shall cover conversion varnishes to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Clear Wood Coating: Clear and semi-transparent coatings, including lacquers and varnishes applied to wood substrates to provide a transparent or translucent solid film.

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Conversion Varnish: A clear acid curing coating with an alkyd or other resin blended with amino resins and supplied as a single component or two-component product. Conversion varnishes produce a hard, durable, clear finish designed for professional application to wood flooring. This film formation is the result of an acid-catalyzed condensation reaction, affecting a transesterification at the reactive ethers of the amino resins.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Conversion Varnishes: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 725

Any conversion varnish compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-3. Clear Wood Coating - Lacquers (Including Lacquer Sanding Sealers)

Covered Products:

This category shall cover lacquers (including sanding sealers) to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Clear Wood Coating: Clear and semi-transparent coatings, including lacquers and varnishes applied to wood substrates to provide a transparent or translucent solid film.

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Lacquer: A clear or opaque wood coating, including clear lacquer sanding sealers, formulated with cellulosic or synthetic resins to dry by evaporation without chemical reaction and to provide a solid, protective film.

Sanding Sealer: Any clear or semi-transparent wood coating formulated for or applied to bare wood to seal the wood and to provide a coat that can be abraded to create a smooth surface for subsequent applications of coatings. A sanding sealer that also meets the definition of a lacquer is not included in this category, but it is included in the lacquer category.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Lacquers (Including Lacquer Sanding Sealers): Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 550

Any lacquer compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-4. Clear Wood Coating - Sanding Sealers (Other Than Lacquers)

Covered Products:

This category shall cover sanding sealers (other than lacquers) to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Clear Wood Coating: Clear and semi-transparent coatings, including lacquers and varnishes applied to wood substrates to provide a transparent or translucent solid film.

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Lacquer: A clear or opaque wood coating, including clear lacquer sanding sealers, formulated with cellulosic or synthetic resins to dry by evaporation without chemical reaction and to provide a solid, protective film.

Sanding Sealer: Any clear or semi-transparent wood coating formulated for or applied to bare wood to seal the wood and to provide a coat that can be abraded to create a smooth surface for subsequent applications of coatings. A sanding sealer that also meets the definition of a lacquer is not included in this category, but it is included in the lacquer category.

Varnish: Any clear or semi-transparent wood coating, excluding lacquers and shellacs, formulated to dry by chemical reaction on exposure to air. Varnishes may contain small amounts of pigment to color a surface, or to control the final sheen or gloss of the finish.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.



New York City EPP Minimum Standards for Goods

Standard:

Sanding Sealers: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 275

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).



New York City EPP Minimum Standards for Goods

3-5. Clear Wood Coating - Varnishes

Covered Products:

This category shall cover varnishes to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Clear Wood Coating: Clear and semi-transparent coatings, including lacquers and varnishes applied to wood substrates to provide a transparent or translucent solid film.

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Lacquer: A clear or opaque wood coating, including clear lacquer sanding sealers, formulated with cellulosic or synthetic resins to dry by evaporation without chemical reaction and to provide a solid, protective film.

Shellac: A clear or opaque coating formulated solely with the resinous secretions of the lac beetle (*Lacifer lacca*), thinned with alcohol and formulated to dry by evaporation without a chemical reaction.

Varnish: Any clear or semi-transparent wood coating, excluding lacquers and shellacs, formulated to dry by chemical reaction on exposure to air. Varnishes may contain small amounts of pigment to color a surface, or to control the final sheen or gloss of the finish.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Varnishes: Maximum Concentration of Volatile Organic Compounds in Grams per Liter : 275

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale



New York City EPP Minimum Standards for Goods

Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).



3-6. Concrete Bond Breakers

Covered Products:

This category shall cover varnishes to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Bond Breaker: A coating labeled and formulated for application between layers of concrete to prevent a freshly poured top layer of concrete from bonding to the layer over which it is poured.

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Bond Breakers: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 350

Any bond breaker compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-7. Concrete Curing Compounds

Covered Products:

This category shall cover concrete curing compounds to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Concrete Curing Compound: A coating labeled and formulated for application to freshly poured concrete to retard the evaporation of water.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Concrete Curing Compounds: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 350

Any concrete curing compound compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-8. Concrete Surface Retarders

Covered Products:

This category shall cover concrete surface retarders to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Concrete Surface Retarder: A mixture of retarding ingredients such as extender pigments, primary pigments, resin, and solvent that interact chemically with the cement to prevent hardening on the surface where the retarder is applied, allowing the retarded mix of cement and sand at the surface to be washed away to create an exposed aggregate finish.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Concrete Surface Retarders: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 780

Any concrete surface retarder compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-9. Dry Fog Coatings

Covered Products:

This category shall cover dry fog coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Dry Fog Coating: A coating labeled and formulated only for spray application such that overspray droplets dry before subsequent contact with incidental surfaces in the vicinity of the surface coating activity.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Dry Fog Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter : 400

Any dry fog coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-10. Faux Finishing Coatings

Covered Products:

This category shall cover faux finishing coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Faux Finishing Coating: A coating labeled and formulated as a stain or a glaze to create artistic effects including, but not limited to, dirt, old age, smoke damage, and simulated marble and wood grain.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Faux Finishing Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 350

Any faux finishing coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-11. Fire-Resistive Coatings

Covered Products:

This category shall cover fire-resistive coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Fire-Resistive Coating: An opaque coating labeled and formulated to protect the structural integrity by increasing the fire endurance of interior or exterior steel and other structural materials, that has been fire tested and rated by a testing agency and approved by building code officials for use in bringing assemblies of structural materials into compliance with Federal, State, and local building code requirements. The fire-resistive coating and the testing agency must be approved by building code officials. The fire-resistive coating shall be tested in accordance with American Society for Testing and Materials (ASTM) Designation E 119-00a.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Fire-Resistive Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter : 350

Any fire resistive coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-12. Fire-Retardant Coatings - Clear

Covered Products:

This category shall cover clear fire-retardant coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Fire-Retardant Coating: A coating labeled and formulated to retard ignition and flame spread, that has been tested and rated by a testing agency approved by building code officials for use in bringing building and construction materials into compliance with Federal, State, and local building code requirements. The fire-retardant coating and the testing agency must be approved by building code officials. The fire-retardant coating shall be tested in accordance with ASTM Designation E 84-01.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Fire-Retardant Coatings: Clear: Maximum Concentration of Volatile Organic Compounds in Grams per Liter : 650

Any fire retardant coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-13. Fire-Retardant Coatings - Opaque

Covered Products:

This category shall cover opaque fire-retardant coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Fire-Retardant Coating: A coating labeled and formulated to retard ignition and flame spread, that has been tested and rated by a testing agency approved by building code officials for use in bringing building and construction materials into compliance with Federal, State, and local building code requirements. The fire-retardant coating and the testing agency must be approved by building code officials. The fire-retardant coating shall be tested in accordance with ASTM Designation E 84-01.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Fire-Retardant Coatings – Opaque: Maximum Concentration of Volatile Organic Compounds in Grams per Liter : 350

Any opaque fire retardant coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-14. Flat Paint

Covered Products:

This category shall cover flat paint to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Flat Paint: Any coating that registers a gloss of less than 15 on an 85-degree meter or less than 5 on a 60-degree meter.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Flat Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 100

Any form release compound compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-15. Floor Coatings

Covered Products:

This category shall cover floor coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Floor Coating: An opaque coating that is labeled and formulated for application to flooring, including, but not limited to, decks, porches, steps, and other horizontal surfaces which may be subjected to foot traffic.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Floor Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter : 100

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).



3-16. Form Release Compounds

Covered Products:

This category shall cover form release compounds to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Form-Release Compound: A coating labeled and formulated for application to a concrete form to prevent the freshly poured concrete from bonding to the form. The form may consist of wood, metal or some material other than concrete.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Form Release Compounds: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 250

Any form release compound compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-17. Graphic Arts Coatings (Sign Paints)

Covered Products:

This category shall cover graphic arts coatings (sign paints) to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Graphic Arts Coating or Sign Paint: A coating labeled and formulated for hand-application using brush or roller techniques to indoor and outdoor signs (excluding structural components) and murals including letter enamels, poster colors, copy blockers, and bulletin enamels.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Graphic Arts Coatings (Sign Paints): Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 500

Any graphic arts coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-18. High Temperature Coatings

Covered Products:

This category shall cover high temperature coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

High Temperature Coating: A high performance coating labeled and formulated for application to substrates exposed continuously or intermittently to temperatures above 204 Celsius (400 Fahrenheit).

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

High Temperature Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 420

Any high temperature coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-19. Industrial Maintenance (IM) Coatings

Covered Products:

This category shall cover industrial maintenance coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Industrial Maintenance Coating: A high performance architectural coating, including primers, sealers, undercoaters, intermediate coats, and topcoats, formulated for application to substrates exposed to one or more of the following extreme environmental conditions:

- (1) Immersion in water, wastewater, or chemical solutions (aqueous and non-aqueous solutions), or chronic exposures of interior surfaces to moisture condensation;
- (2) Acute or chronic exposure to corrosive, caustic or acidic agents, or to chemicals, chemical fumes, or chemical mixtures or solutions;
- (3) Repeated exposure to temperatures above 121°C (250°F);
- (4) Repeated (frequent) heavy abrasion, including mechanical wear and repeated (frequent) scrubbing with industrial solvents, cleansers, or scouring agents; or
- (5) Exterior exposure of metal structures and structural components.

In addition, any industrial maintenance coating shall display on the label or the lid of the container in which the coating is sold or distributed one or more of the descriptions listed below:

- (1) "For industrial use only."
- (2) "For professional use only."
- (3) "Not for residential use" or "Not intended for residential use."

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical



New York City EPP Minimum Standards for Goods

reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Industrial Maintenance Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 340

Any industrial maintenance coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-20. Lacquers - Pigmented

Covered Products:

This category shall cover industrial maintenance coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Pigmented Lacquer: An opaque wood coating, including clear lacquer sanding sealers, formulated with cellulosic or synthetic resins to dry by evaporation without chemical reaction and to provide a solid, protective film.

Sanding Sealer: Any clear or semi-transparent wood coating formulated for or applied to bare wood to seal the wood and to provide a coat that can be abraded to create a smooth surface for subsequent applications of coatings. A sanding sealer that also meets the definition of a lacquer is not included in this category, but it is included in the lacquer category.

Standard:

Pigmented Lacquers: Maximum Concentration of Volatile Organic Compounds in Grams per Liter : 275

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).



3-21. Latex Paint – Consolidated

Covered Products:

This specification shall cover consolidated latex paints used for covering graffiti, where color and consistency of performance are not primary concerns.

Definition:

Consolidated paint: Post-consumer latex paint with similar characteristics (such as type, color family, and finish) that is consolidated at the point of collection. The post-consumer paints are blended together and repackaged, usually with few or no new ingredients added to improve the performance of the resulting paint.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Latex Paint – Consolidated:

Material: Recovered Material

Recovered Post-consumer Content (%): 100

Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

3-22. Latex Paint – Reprocessed White, Off-White and Pastel Colors

Covered Products:

This specification shall cover reprocessed white, off-white and pastel colored latex paints used for interior and exterior architectural applications such as wallboard, ceilings, and trim; gutterboards; and concrete, stucco, masonry, wood, and metal surfaces.

Definition:

Reprocessed paint: Post-consumer latex paint that has been sorted by a variety of characteristics that are dictated by the recycler. In general, the paint is sorted by type (i.e., interior versus exterior), by light and dark colors, and by finish (i.e., high-gloss versus flat). The reprocessor adds raw materials to meet the performance and color requirements expected or required by the end user.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Latex Paint – Reprocessed White, Off-White and Pastel Colors:

Material: Recovered Material
Recovered Post-consumer Content (%): 20
Total Recovered Materials Content (%):20



New York City EPP Minimum Standards for Goods

3-23. Latex Paint – Reprocessed Grey, Brown, Earthtones and Other Dark Colors

Covered Products:

This specification shall cover reprocessed grey, brown, earthtone and other dark colored latex paints used for interior and exterior architectural applications such as wallboard, ceilings, and trim; gutterboards; and concrete, stucco, masonry, wood, and metal surfaces.

Definition:

Reprocessed paint: Post-consumer latex paint that has been sorted by a variety of characteristics that are dictated by the recycler. In general, the paint is sorted by type (i.e., interior versus exterior), by light and dark colors, and by finish (i.e., high-gloss versus flat). The reprocessor adds raw materials to meet the performance and color requirements expected or required by the end user.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Latex Paint – Reprocessed Grey, Brown, Earthtones and Other Dark Colors:

Material: Recovered Material
Recovered Post-consumer Content (%): 50-99
Total Recovered Materials Content (%):50-99



New York City EPP Minimum Standards for Goods

3-24. Low Solids Coatings

Covered Products:

This category shall cover low solids coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Low Solids Coating: A coating containing 0.12 kilogram or less of solids per liter (one pound or less of solids per gallon) of coating material.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Low Solids Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 120

Any low solids coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-25. Magnesite Cement Coatings

Covered Products:

This category shall cover magnesite cement coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Magnesite Cement Coating: A coating labeled and formulated for application to magnesite cement decking to protect the magnesite cement substrate from erosion by water.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Magnesite Cement Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 450

Any magnesite cement coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-26. Mastic Texture Coatings

Covered Products:

This category shall cover mastic texture coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Mastic Texture Coating: A coating labeled and formulated to cover holes and minor cracks and conceal surface irregularities, which is applied in a single coat of at least 10 mils (0.010 inch) dry film thickness.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Mastic Texture Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 300

Any mastic texture coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-27. Metallic Pigmented Coatings

Covered Products:

This category shall cover metallic pigmented coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Metallic Pigmented Coating: A coating containing at least 48 grams of elemental metallic pigment per liter of coating as applied (0.4 pounds per gallon), when tested in accordance with South Coast Air Quality Management District Method 318-95.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Metallic Pigmented Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 500

Any metallic pigmented coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-28. Multi-Color Coatings

Covered Products:

This category shall cover multi-color coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Multi-Color Coating: A coating that is packaged in a single container and exhibits more than one color when applied in a single coat.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Multi-Color Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 500

Any multi-color coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-29. Nonflat High-Gloss Coatings

Covered Products:

This category shall cover nonflat high-gloss coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Nonflat High-Gloss Coating: A non-flat coating that registers a gloss of 70 or above on a 60-degree meter according to ASTM Designation D 523-89 (1999) and must comply with labeling requirements as defined in part 205.4 (i) of Title Six of the New York Codes, Rules and Regulations.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Nonflat High-Gloss Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 250

Any nonflat high-gloss coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-30. Nonflat Paint

Covered Products:

This category shall cover nonflat paint to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Nonflat Paint: Any coating that a gloss of 5 or greater on a 60 degree meter and a gloss of 15 or greater on an 85 degree meter.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Nonflat Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 150

Any nonflat coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-31. Pre-Treatment Wash Primers

Covered Products:

This category shall cover pre-treatment wash primers to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Primer: A coating labeled and formulated for application to a substrate to provide a firm bond between the substrate and subsequent coats.

Pre-Treatment Wash Primer: A primer that contains a minimum of 0.5 acid, by weight, when tested in accordance with ASTM Designation D 1613-96 (1999), that is labeled and formulated for application directly to bare metal surfaces to provide corrosion resistance and to promote adhesion of subsequent topcoats.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Pre-Treatment Wash Primers: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 420

Any pre-treatment wash primer compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-32. Primers for Flat Paint

Covered Products:

This category shall cover primers for flat paint to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Flat Paint: Any coating that registers a gloss of less than 15 on an 85-degree meter or less than 5 on a 60-degree meter.

Primer: A coating labeled and formulated for application to a substrate to provide a firm bond between the substrate and subsequent coats.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Primer for Flat Paint: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 100

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).



3-33. Primers for Non-Flat Paint

Covered Products:

This category shall cover primers for non-flat paint to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Nonflat Paint: Any coating that a gloss of 5 or greater on a 60 degree meter and a gloss of 15 or greater on an 85 degree meter.

Primer: A coating labeled and formulated for application to a substrate to provide a firm bond between the substrate and subsequent coats.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Primer for Non-Flat Paint: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 150

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).



New York City EPP Minimum Standards for Goods

3-34. Primers, Sealers, and Undercoaters

Covered Products:

This category shall cover primers, sealers and undercoaters to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Flat Paint: Any coating that registers a gloss of less than 15 on an 85-degree meter or less than 5 on a 60-degree meter.

Nonflat Paint: Any coating that registers a gloss of 5 or greater on a 60 degree meter and a gloss of 15 or greater on an 85 degree meter.

Primer: A coating labeled and formulated for application to a substrate to provide a firm bond between the substrate and subsequent coats.

Rust Preventative / Anti-Corrosive Paint: Any coating formulated exclusively for non industrial use to prevent the corrosion of metal surfaces.

Undercoater: A coating labeled and formulated to provide a smooth surface for subsequent coatings.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Primers, Sealers and Undercoaters: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 200

Any primer, sealer and undercoater compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this



New York City EPP Minimum Standards for Goods

specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-35. Quick-Dry Enamels

Covered Products:

This category shall cover quick-dry enamels to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Quick-Dry Enamel: A non-flat coating that is formulated to have the following characteristics:

- (1) is capable of being applied directly from the container under normal conditions with ambient temperatures between 16°C and 27°Celsius (60° and 80° Fahrenheit);
- (2) when tested in accordance with ASTM Designation D 1640-95 (1999) (see Table 1, section 200.9 of this Title), sets to touch in two hours or less, is tack free in four hours or less, and dries hard in eight hours or less by the mechanical test method; and
- (3) has a dried film gloss of 70 or above on a 60-degree meter.

The labels of all quick-dry enamels prominently display the words "Quick dry" and the dry hard time.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Quick-Dry Enamels: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 250

Any quick-dry enamel compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this



New York City EPP Minimum Standards for Goods

specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-36. Quick-Dry Primers, Sealers, and Undercoaters

Covered Products:

This category shall cover quick-dry primers, sealers and undercoaters to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Primer: A coating labeled and formulated for application to a substrate to provide a firm bond between the substrate and subsequent coats.

Quick-Dry Primer, Sealer and Undercoater: A primer sealer or undercoater that is dry to the touch in 30 minutes and can be relocated in two hours when tested in accordance with ASTM Designation D 1640-95 (1999)

Sealer: A coating labeled and formulated for application to a substrate for one or more of the following purposes: to prevent subsequent coatings from being absorbed by the substrate, or to prevent harm to subsequent coatings by materials in the substrate.

Undercoater: A coating labeled and formulated to provide a smooth surface for subsequent coatings.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Quick-Dry Primers, Sealers and Undercoaters: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 200

Any quick-dry primer, sealer and undercoater compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required



New York City EPP Minimum Standards for Goods

under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-37. Recycled Coatings

Covered Products:

This category shall cover recycled coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Architectural Coating: Any coating to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This term shall not include the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Recycled Coating: An architectural coating formulated such that not less than 50 percent of the weight consists of secondary and post-consumer coating, with not less than 10 percent of the total weight consisting of post-consumer coating.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Recycled Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 250

Any recycled coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-38. Roof Coatings

Covered Products:

This category shall cover roof coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Metallic Pigmented Coating: A coating containing at least 48 grams of elemental metallic pigment per liter of coating as applied (0.4 pounds per gallon), when tested in accordance with South Coast Air Quality Management District Method 318-95.

Roof Coating: A non-bituminous coating labeled and formulated exclusively for application to roofs for the primary purpose of preventing penetration of the substrate by water or reflecting heat and ultraviolet radiation. Metallic pigmented roof coatings which qualify as metallic pigmented coatings shall not be considered in this category, but shall be considered to be in the metallic pigmented coatings category.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Roof Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 250

Any roof coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-39. Roof Coatings (Bituminous)

Covered Products:

This category shall cover bituminous roof coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Bitumen: Black or brown materials including, but not limited to, asphalt, tar, pitch, and asphaltite that are soluble in carbon disulfide, consist mainly of hydrocarbons, and are obtained from natural deposits or as residues from the distillation of crude petroleum or coal.

Bituminous Roof Coating: A coating which incorporates bitumens that is labeled and formulated exclusively for roofing.

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Bituminous Roof Coatings: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 300

Any bituminous roof coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-40. Roof Primers (Bituminous)

Covered Products:

This category shall cover bituminous roof primers to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Bitumen: Black or brown materials including, but not limited to, asphalt, tar, pitch, and asphaltite that are soluble in carbon disulfide, consist mainly of hydrocarbons, and are obtained from natural deposits or as residues from the distillation of crude petroleum or coal.

Bituminous Roof Coating: A coating which incorporates bitumens that is labeled and formulated exclusively for roofing.

Primer: A coating labeled and formulated for application to a substrate to provide a firm bond between the substrate and subsequent coats.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Bituminous Roof Primers: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 350

Any bituminous roof primer compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-41. Rust Preventative / Anti-Corrosive Paint

Covered Products:

This category shall cover rust-preventative / anti-corrosive paint to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Rust Preventative / Anti-Corrosive Paint: Any coating formulated exclusively for non industrial use to prevent the corrosion of metal surfaces.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Rust-Preventative / Anti-Corrosive Paint: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 250

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).



New York City EPP Minimum Standards for Goods

3-42. Shellacs - Clear

Covered Products:

This category shall cover clear shellacs to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Shellac: A clear or opaque coating formulated solely with the resinous secretions of the lac beetle (*Lacifer lacca*), thinned with alcohol and formulated to dry by evaporation without a chemical reaction.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Shellacs – Clear: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 730

Any clear shellac compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-43. Shellacs - Opaque

Covered Products:

This category shall cover opaque shellacs to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Shellac: A clear or opaque coating formulated solely with the resinous secretions of the lac beetle (*Lacifer lacca*), thinned with alcohol and formulated to dry by evaporation without a chemical reaction.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Shellacs – Opaque: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 550

Any opaque shellac compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-44. Specialty Primers, Sealers and Undercoaters

Covered Products:

This category shall cover specialty primers, sealers and undercoaters to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Primer: A coating labeled and formulated for application to a substrate to provide a firm bond between the substrate and subsequent coats.

Sealer: A coating labeled and formulated for application to a substrate for one or more of the following purposes: to prevent subsequent coatings from being absorbed by the substrate, or to prevent harm to subsequent coatings by materials in the substrate.

Specialty Primer, Sealer and Undercoater: A coating that is formulated for application to a substrate to seal fire, smoke or water damage, to condition excessively chalky surfaces, or to block stains. An excessively chalky surface is one that is defined as having a chalk rating of four or less as determined by ASTM Designation D 4214-98. Specialty Primers, Sealers and Undercoaters in this specification must comply with labeling requirements as defined in part 205.4 (f) of Title Six of the New York Codes, Rules and Regulations.

Undercoater: A coating labeled and formulated to provide a smooth surface for subsequent coatings.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.



New York City EPP Minimum Standards for Goods

Standard:

Specialty Primers, Sealers and Undercoaters: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 350

Any specialty primer, sealer and undercoater compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-45. Stains

Covered Products:

This category shall cover stains to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Stain: A clear semi-transparent or opaque coating labeled and formulated to change the color of a surface but not conceal the grain pattern or texture.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Stains: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 250

Any stain compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-46. Swimming Pool Coatings and Swimming Pool Repair and Maintenance Coatings

Covered Products:

This category shall cover swimming pool coatings and swimming pool repair and maintenance coatings to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Swimming Pool Coating: A coating labeled and formulated to coat the interior of swimming pools and to resist swimming pool chemicals.

Swimming Pool Repair and Maintenance Coating: A rubber based coating labeled and formulated to be used over existing rubber based coatings for the repair and maintenance of swimming pools.

Standard:

Swimming Pool Coatings and Swimming Pool Repair and Maintenance Coatings:
Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 340

Any swimming pool coating and swimming pool repair and maintenance coating compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-47. Thermoplastic Rubber Coatings and Mastics

Covered Products:

This category shall cover thermoplastic rubber coatings and mastics to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Thermoplastic Rubber Coating and Mastic: A coating or mastic formulated and recommended for application to roofing or other structural surfaces and that incorporates no less than 40 percent by weight of thermoplastic rubbers in the total resin solids and may also contain other ingredients including, but not limited to, fillers, pigments, and modifying resins.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Thermoplastic Rubber Coatings and Mastics: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 550

Any thermoplastic rubber coating and mastic compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-48. Waterproofing Concrete / Masonry Sealers

Covered Products:

This category shall cover waterproofing concrete/masonry sealers to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Pigmented Lacquer: An opaque wood coating, including clear lacquer sanding sealers, formulated with cellulosic or synthetic resins to dry by evaporation without chemical reaction and to provide a solid, protective film.

Standard:

Waterproofing Concrete/Masonry Sealers: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 400

Any waterproofing concrete/masonry sealer compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



New York City EPP Minimum Standards for Goods

3-49. Waterproofing Sealers

Covered Products:

This category shall cover waterproofing sealers to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Waterproofing Sealer: A coating labeled and formulated for application to a porous substrate for the primary purpose of preventing the penetration of water.

Standard:

Waterproofing Sealers: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 250

Any waterproofing sealer compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.



3-50. Wood Preservatives

Covered Products:

This category shall cover wood preservatives to be applied to stationary structures and their appurtenances at the site of installation, to portable buildings at the site of installation, to pavements, or to curbs. This category shall not apply to the following: marine-based paints and coatings; coatings or materials to be applied to metal structures, such as bridges; or coatings or materials labeled and formulated for application in roadway maintenance activities.

Definition:

Coating: A material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Wood Preservative: A coating labeled and formulated to protect exposed wood from decay or insect attack, that is registered under the Federal Insecticide, Fungicide, and Rodenticide Act (7 U.S.C. section 136, et. seq) and with Part 326 of the New York State Rules and Regulations.

Standard:

Wood Preservatives: Maximum Concentration of Volatile Organic Compounds in Grams per Liter: 350

Any wood preservative compliant with Part 205 of Title Six of the New York Codes, Rules and Regulations meets the standard required under this specification. The maximum content of VOCs shall be determined according to the test method required under part 205.6 of such part.

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

Electronics

4-1. Amplifiers/Pre-Amplifiers, Consumer

Covered Products:

This category shall cover all consumer amplifiers/pre-amplifiers that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-2. Answering Machines

Covered Products:

This category shall cover answering machines.

Definition:

Answering Machine: A commercially available electronic product—also known as a telephone answering device (TAD)—whose purpose is to provide analog or digital storage of outgoing and incoming telephone messages by connecting to the telephone line between the phone and the phone jack. Most of these devices require an external power supply for power and are plugged into an ac power outlet for 24 hours a day. The answering machine or its power supply must be designed to plug into a wall outlet.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-3. Cassette Decks, Consumer

Covered Products:

This category shall cover cassette decks that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-4. CD Players, Consumer

Covered Products:

This category shall cover CD Players that are also consumer audio products.

This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-5. CD Recorders, Consumer

Covered Products:

This category shall cover CD recorders that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-6. Clock Radios, Consumer

Covered Products:

This category shall cover all consumer clock radios that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-7. Combination TV with VCR, DVD, or VCR/DVD Units

Covered Products:

This category shall cover TV/DVD Combination Units, TV/VCR Combination Units, TV/VCR/DVD Combination Units, VCR/DVD Combination Units and Videocassette Recorders (VCR).

Definition:

TV/DVD Combination Unit: A system in which the TV and DVD are combined into a single unit and which meets all of the following criteria: the DVD is included in the television casing; it is not possible to measure the power requirements of the two components separately without removal of the television casing; and the system is connected to the wall outlet through a single power cable. To qualify, the TV/DVD must be capable of being powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital TV/DVDs.

TV/VCR Combination Unit: A system in which the TV and VCR are combined into a single unit and which meets all of the following criteria: the VCR is included in the television casing; it is not possible to measure the power requirements of the two components separately without removal of the television casing; and the system is connected to the wall outlet through a single power cable. To qualify, the TV/VCR must be capable of being powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital TV/VCRs.

TV/VCR/DVD Combination Unit: A system in which the TV, VCR, and DVD are combined into a single unit and which meets all of the following criteria: the VCR and DVD are included in the television casing; it is not possible to measure the power requirements of any of the components separately without removal of the television casing; and the system is connected to the wall outlet through a single power cable. To qualify, the TV/VCR/DVD must be capable of being powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital TV/VCR/DVDs.

VCR/DVD Combination Unit: A system in which the VCR and DVD are combined into a single unit and which meets all of the following criteria: it is not possible to measure the power requirements of the two components separately without removal of the casing; and the system is connected to the wall outlet through a single power cable. To qualify, the VCR/DVD must be capable of being powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital VCR/DVDs.

Videocassette Recorder/Videocassette Player (VCR): An electronic product designed to play and/or record video tape. The VCR must be capable of being



New York City EPP Minimum Standards for Goods

powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital videocassette recorders/videocassette players.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.



New York City EPP Minimum Standards for Goods

4-8. Cordless Telephones

Covered Products:

This category shall cover cordless telephones and combination cordless telephones/answering machines.

Definition:

Cordless Telephone: A commercially available electronic product with a base station and a handset whose purpose is to convert sound into electrical impulses for transmission. Most of these devices require a wall pack for power, are plugged into an AC power outlet for 24 hours a day, and do not have a power switch to turn them off. The base station of the cordless phone or its power supply must be designed to plug into a wall outlet and there must not be a physical connection between the portable handset and the phone jack.

Combination Cordless Telephone/Answering Machine: A commercially available electronic product in which the cordless telephone and answering machine are combined into a single unit and which meets all of the following criteria: the answering machine is included in the base station of the cordless telephone; it is not possible to measure the power requirements of the two components separately without removal of the telephone casing; and the unit is connected to the wall outlet through a single power cable. Most of these devices require an external power supply for power, are plugged into an ac power outlet for 24 hours a day, and do not have a power switch to turn them off. The combination unit or its power supply must be designed to plug into a wall outlet.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-9. DVD Products

Covered Products:

This category shall cover digital versatile disc (DVD) products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Digital Versatile Disc (DVD) Product: A commercially available electronic product encased in a single housing whose intended purpose is the production or recording of digitized video signals on a spinning reflective disc media. The product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. The products may have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-10. Equalizers, Consumer

Covered Products:

This category shall cover all consumer equalizers that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-11. Extended Power Adaptors

Definition:

External power adapters: Also known as power supplies, convert high voltage ac electricity from the wall outlet to the low voltage dc power used to power electronic products, like MP3 players, Personal Digital Assistants (PDAs), camcorders, digital cameras, laptops, and cordless and mobile phones.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-12. Laserdisc Players, Consumer

Definition:

Laserdisc Player: An electronic device that plays the first commercial optical disc storage medium, and is used primarily for the presentation of movies.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-13. Mini- and Midi-Systems, Consumer

Covered Products:

This category shall cover all consumer mini- and midi-systems that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-14. Minidisc Players, Consumer

Covered Products:

This category shall cover all consumer minidisc players that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-15. Powered Speakers, Consumer

Covered Products:

This category shall cover all consumer powered speakers that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-16. Receivers, Consumer

Covered Products:

This category shall cover all consumer receivers that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-17. Table Radios, Consumer

Covered Products:

This category shall cover all consumer mini- and midi-systems that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-18. Televisions

Covered Products:

This category shall cover Televisions, Television Monitors, Digital Cable-Ready Televisions and Component Televisions.

Definition:

Component Television Unit: A television system composed of two or more separate components (e.g., display device, tuner, and power supply or display device and tuner/power supply) marketed and sold as a television under one model or system designation. The system may have more than one power cord. For purposes of meeting the standby power criteria, the total standby power for the system is considered. The Component Television Unit must be capable of being powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital Component Television Units.

Component TV units with computer capability (e.g., computer input port) may qualify as ENERGY STAR under this definition as long as they are marketed and sold to consumers as televisions (i.e., focusing on television as the primary function). However, component units with a tuner/receiver and computer capability that are marketed and sold as 1) computer monitors or 2) dual function televisions and computer monitors are not included in this definition.

Digital Cable-Ready (DCR) TV with Point of Deployment (POD) Slot: A TV with at least one digital tuner (e.g., DSS, VSB or QAM) or at least one digital video input (e.g., IEEE 1394, DVI, iLink) which also incorporates a removable Point of Deployment (POD) slot. The removable POD separates a DCR TV from the cable operator's proprietary conditional access system, thereby enabling portability of the host to other cable networks.

Television (TV): A commercially available electronic product consisting of a tuner/receiver and a monitor encased in a single housing. The monitor usually relies upon a cathode-ray tube (CRT), liquid crystal display (LCD), plasma display, or other display device. The TV is designed to receive and display a television signal broadcast by antenna, satellite, or cable. To qualify, the TV must be capable of being powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital televisions in addition to televisions that require additional power to receive and process signals that contain information and/or data for electronic programming guides. Television products with a tuner/receiver and computer capability (e.g., computer input port) may qualify as ENERGY STAR under this definition as long as they are marketed and sold to consumers as televisions (i.e., focusing on television as the primary function). However, products with a tuner/receiver and computer capability that are marketed and sold as 1) computer monitors or 2) dual function televisions and computer monitors are not included.



New York City EPP Minimum Standards for Goods

Television Monitor: An electronic product intended to display a video signal from an external tuner or other video source such as a VCR or DVD Player on a CRT, LCD, plasma display, or other display device. To qualify, the television monitor must be capable of being powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital television monitors. Television monitors with computer capability (e.g., computer input port) may qualify as ENERGY STAR under this definition as long as they are marketed and sold to consumers as television monitors (i.e., focusing on television/video as the primary function). However, products with computer capability that are marketed and sold as 1) computer monitors or 2) dual function television and computer monitors are not included in this category.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.



New York City EPP Minimum Standards for Goods

4-19. Tuners, Consumer

Covered Products:

This category shall cover all consumer tuners that are also consumer audio products. This category does not cover professional, automotive, or solely battery-powered products.

Definition:

Consumer Audio Product: A commercially available electronic product encased in a single housing whose intended purpose, other than providing non-video status displays, is the production or recording of signals in the audio domain as reproduced by headphones, loudspeakers, or other transducers. This product must draw current from a building's AC power electrical outlet via a power cord or via an AC power adapter that is shipped with the product. Also eligible are those products that have a power switch to interrupt the current flow from the power line and perform no operating functions except in active mode. This definition does not cover professional, automotive, or solely battery-powered products.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

4-20. VCR

Covered Products:

Definition:

Videocassette Recorder/Videocassette Player (VCR): An electronic product designed to play and/or record video tape. The VCR must be capable of being powered from either a wall outlet or a battery unit that is sold with an AC adapter. This definition includes analog and digital videocassette recorders/videocassette players.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

PAGE INTENTIONALLY LEFT BLANK



HVAC Equipment - Commercial

5-1. Air Conditioners, Air-Cooled

Covered Products:

This specification shall cover air-cooled, light commercial central air conditioners that are either: (1) rated at 65,000 to 250,000 Btu/h; or (2) rated below 65,000 Btu/h and powered by three-phase current. This specification shall cover both single package and split system units.

Definition:

Central Air Conditioner: A central air-conditioner model consists of one or more factory-made assemblies that normally include an evaporator or cooling coil(s), compressor(s), and condenser(s). Central air conditioners provide the function of air-cooling, and may include the functions of air circulation, air cleaning, dehumidifying, or humidifying.

Single Package: A single package unit is a central air conditioner that combines both condenser and air handling capabilities in a single casing.

Split System: A split system is a central air conditioner with separate indoor (evaporator) and outdoor (condenser) units.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

5-2. Air Conditioners, Gas/Electric Package Units

Covered Products:

This specification shall cover light commercial gas/electric package units that are either: (1) rated at 65,000 to 250,000 Btu/h; or (2) rated below 65,000 Btu/h and powered by three-phase current.

Definition:

Gas/Electric Package Unit: A single package unit with gas heating and electric air conditioning that is often installed on a slab or roof.

Single Package: A single package unit is a central air conditioner that combines both condenser and air handling capabilities in a single casing.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

5-3. Chillers, Air-Cooled

Covered Products:

This specification shall cover part load optimized and full load optimized air-cooled chillers of the following types and cooling capacities: scroll, 30-60 tons; reciprocating, 30-180 tons; and screw 70-200 tons.

Definition:

Integrated Part-Load Value (IPLV): A weighted average of efficiency measurements at various part-load conditions, as described in ARI Standard 550/590-98.

Standard:

Chillers, Air-Cooled: Part Load Optimized Chillers IPLV (kW/ton) Required: Full Load Optimized Chillers IPLV (kW/ton) Required:

Compressor Type and Capacity: Scroll (30 - 60 tons)
Part Load Optimized Chillers IPLV (kW/ton) Required: 0.86 or less
Full Load Optimized Chillers IPLV (kW/ton) Required: 1.23 or less 1.1

Compressor Type and Capacity: Reciprocating (30 - 150 tons)
Part Load Optimized Chillers IPLV (kW/ton) Required: 0.90 or less
Full Load Optimized Chillers IPLV (kW/ton) Required: 1.23 or less 1

Compressor Type and Capacity: Screw (70 - 200 tons)
Part Load Optimized Chillers IPLV (kW/ton) Required: 0.98 or less
Full Load Optimized Chillers IPLV (kW/ton) Required: 1.23 or less 0.94



New York City EPP Minimum Standards for Goods

5-4. Chillers, Water-Cooled

Covered Products:

This specification shall cover part load optimized and full load optimized water-cooled chillers of the following types and cooling capacities: centrifugal, 150-2,000 tons; and rotary screw, greater than 150 tons.

Definition:

Integrated Part-Load Value (IPLV): A weighted average of efficiency measurements at various part-load conditions, as described in ARI Standard 550/590-98.

Standard:

Chillers, Water-Cooled:

Compressor Type and Capacity: Centrifugal (150 - 299 tons)
Part Load Optimized Chillers IPLV (kW/ton) Required: 0.52 or less
Full Load Optimized Chillers IPLV (kW/ton) Required: 0.59 or less

Compressor Type and Capacity: Centrifugal (300 - 2,000 tons)
Part Load Optimized Chillers IPLV (kW/ton) Required: 0.45 or less
Full Load Optimized Chillers IPLV (kW/ton) Required: 0.56 or less

Compressor Type and Capacity: Rotary Screw (>150 tons)
Part Load Optimized Chillers IPLV (kW/ton) Required: 0.49 or less
Full Load Optimized Chillers IPLV (kW/ton) Required: 0.64 or less



New York City EPP Minimum Standards for Goods

5-5. Heat Pumps, Air Source

Covered Products:

This specification shall cover air-source, light commercial heat pumps that are either: (1) rated at 65,000 to 250,000 Btu/h; or (2) rated below 65,000 Btu/h and powered by three-phase current. This specification shall cover both single package and split system units.

Definition:

Heat Pump: A heat pump model consists of one or more factory-made assemblies that normally include an indoor conditioning coil(s), compressor(s), and outdoor coil(s), including means to provide a heating function. Heat pumps shall provide the function of air heating with controlled temperature, and may include the functions of air-cooling, air circulation, air cleaning, dehumidifying, or humidifying.

Single Package: A single package unit is a central air conditioner that combines both condenser and air handling capabilities in a single casing.

Split System: A split system is a central air conditioner with separate indoor (evaporator) and outdoor (condenser) units.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

HVAC Equipment - Residential

6-1. Air Conditioners, Central (<65,000 Btu/h)

Covered Products:

This specification shall cover residential central air conditioners that are rated below 65,000 Btu/h, and powered by single-phase current. The central air conditioner may be a single packaged system, where there is only one assembly, or a split system where there are two.

Definition:

Central Air Conditioner: A central air-conditioner model consists of one or more factory-made assemblies that normally include an evaporator or cooling coil(s), compressor(s), and condenser(s). Central air conditioners provide the function of air-cooling, and may include the functions of air circulation, air cleaning, dehumidifying, or humidifying.

Single Package: A single package unit is a central air conditioner that combines both condenser and air handling capabilities in a single casing.

Split System: A split system is a central air conditioner with separate indoor (evaporator) and outdoor (condenser) units.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

6-2. Air Conditioners, Central, Gas/Electric Package Units (<65,000 Btu/h)

Covered Products:

This specification shall cover gas/electric package units that are rated below 65,000 Btu/h.

Definition:

Air-Source Heat Pump (ASHP): An air-source unitary heat pump model consists of one or more factory-made assemblies which normally include an indoor conditioning coil(s), compressor(s), and outdoor coil(s), including means to provide a heating function. ASHPs shall provide the function of air heating with controlled temperature, and may include the functions of air-cooling, air-circulation, air-cleaning, dehumidifying or humidifying.

Central Air Conditioner: A central air-conditioner model consists of one or more factory-made assemblies that normally include an evaporator or cooling coil(s), compressor(s), and condenser(s). Central air conditioners provide the function of air-cooling, and may include the functions of air circulation, air cleaning, dehumidifying, or humidifying.

Gas/Electric Package Unit: A single package unit with gas heating and electric air conditioning that is often installed on a slab or roof.

Single Package: A single package unit is a central air conditioner that combines both condenser and air handling capabilities in a single casing.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

6-3. Air Source Heat Pumps (<65,000 Btu/h)

Covered Products:

This specification shall cover air source heat pumps (ASPHs) that are rated below 65,000 Btu/h. The ASPH may be a single packaged system, where there is only one assembly, or a split system where there are two.

Definition:

Air-Source Heat Pump (ASHP): An air-source unitary heat pump model consists of one or more factory-made assemblies which normally include an indoor conditioning coil(s), compressor(s), and outdoor coil(s), including means to provide a heating function. ASHPs shall provide the function of air heating with controlled temperature, and may include the functions of air-cooling, air-circulation, air-cleaning, dehumidifying or humidifying.

Single Package: A single package unit is a central air conditioner that combines both condenser and air handling capabilities in a single casing.

Split System: A split system is a central air conditioner with separate indoor (evaporator) and outdoor (condenser) units.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

6-4. Boilers and Boiler/Hot Water Heaters (<300,000 Btu/h)

Covered Products:

This specification shall cover residential boilers and residential combination space-heating and water heating appliances.

Definition:

Boiler: A self-contained fuel burning appliance of less than 300,000 Btu per hour energy input, for supplying low pressure steam or hot water for space heating applications.

British Thermal Unit (Btu): A British standard unit of energy.

Combination Space-Heating and Water Heating Appliance: Appliance that provides both space conditioning (boiler) and hot water heating with one appliance or energy source. The combination appliance circulates hot water from the water heater through a heat exchanger in the air handler. A blower will move the heated air through a standard duct system. In the summer, an air conditioner is connected to the exchanger and the system functions similarly, with cool air being pushed through the ductwork.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

6-5. Ceiling Fans

Covered Products:

This specification shall cover residential ceiling fans but shall not cover hugger fans.

Definition:

Hugger Fan: A fan style where the motor mounts directly to the ceiling. Hugger fans are most commonly used in rooms with low ceilings. Hugger fans are manufactured and marketed as such and should not be confused with multi-mount (traditional) fans that can be hung without the down rod, giving the same effect as a hugger fan. Hugger fans are designed to allow installations on 7'6" – 8' height ceilings when using a fan light kit in a location where walking under the fan will occur.

Light Kit: A complete lighting unit consisting of a lamp or lamps, and ballasting (when applicable) together with the parts designed to distribute the light, position and protect the lamps, and connect the lamps to the power supply. Light kits can be:

- **Integral** – the light kit is attached to the ceiling fan housing at the time of purchase. This type of a light kit is integrated into the bottom cap of the fan and cannot be removed or replaced with another light kit.
- **Attachable** – the light kit is not, at the time of sale, physically attached to the fan. The light kit must be attached to the ceiling fan for the lights to work. Attachable light kits might be included inside the ceiling fan box at the time of sale or sold separately for subsequent attachment to the fan.

Residential Ceiling Fan: A non-portable device designed for home use that is suspended from the ceiling for circulating air via the rotation of fan blades. Some ceiling fans also have an integral or attachable light kit.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

6-6. Furnaces and Furnace/Hot Water Heaters (<340,000 Btu/h)

Covered Products:

This specification shall cover furnaces and combination furnace/hot water heaters with an output of less than 340,000 Btu/h.

Definition:

Furnace: A heating unit whose function is the combustion of fossil fuel for space heating with forced hot air. Unit must include burner(s), heat exchanger(s), blower(s) and connections to heating ducts. A heating unit that meets this definition and also provides hot water for domestic or other use may be considered a furnace.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



6-7. Ground Source Heat Pumps (Geothermal)

Covered Products:

This specification shall cover open loop, closed loop and direct expansion geothermal heat pumps. Geothermal heat pumps that include a water heating function in the refrigeration cycle (integrated demand water heating) are also covered.

Definition:

Closed Loop System: A ground heat exchanger in which the heat transfer fluid is permanently contained in a closed system.

Desuperheater: A partial heat recovery system that captures heat from the hot refrigerant as it leaves the heat pump compressor and transfers it to the domestic hot water. Desuperheaters provide hot water only while the heat pump is providing space conditioning.

Direct Expansion System: A geothermal heat pump system in which the refrigerant is circulated in pipes buried in the ground, rather than using a heat transfer fluid, such as water or antifreeze solution in a separate closed loop, and fluid to refrigerant heat exchanger.

Geothermal Heat Pump: A model which uses the thermal energy of the ground or groundwater as the heat source and heat sink for residential space heating and/or cooling. It may provide both space heating and cooling, cooling only or heating only functions. A geothermal heat pump model consists of one or more factory-made assemblies that normally include an indoor conditioning coil with air moving means, compressor(s) and refrigerant to fluid heat exchanger(s). In addition, for the purposes of this specification, some or all of the domestic water heating shall be provided through the use of a desuperheater, integrated demand water heater or a separately installed compressor that provides demand water heating. The geothermal heat pump includes all the equipment and connections from the point at which the ground heat exchanger enters the house, except for indoor equipment that was installed by someone not representing the manufacturer or manufacturer's representative, such as the ground heat exchanger installer.

Ground Heat Exchanger: The method by which heat is exchanged with the ground, groundwater or surface water. Geothermal heat pumps may use any form of ground heat exchanger, which may include horizontal or vertical closed loops, open loop vertical wells, or surface water. For the purposes of this specification, the ground heat exchanger comprises all the equipment (piping, connections, grouting, etc.) that is installed outside the house, and up to the point



New York City EPP Minimum Standards for Goods

it enters the house and any equipment or connections that the ground heat exchanger contractor installs inside the house.

Integrated Demand Water Heating: For purposes of this specification, this term is used to describe geothermal heat pumps that include a water heating function in the refrigeration cycle. Integrated demand water heating differs from desuperheater in that the integrated demand water heating model provides all or nearly all of the domestic hot water needs and provides hot water even when space conditioning is not required. This includes systems that employ the use of a separate water heating compressor unit or that use the same compressor for space conditioning and water heating. Also sometimes referred to as full-demand or demand water heating.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



6-8. In-Line Ventilating Fan

Covered Products:

This specification shall cover in-line residential ventilating fans (single and multi-port), both ducted and direct-discharge models. Ventilating fans with sensors and timers may qualify under this specification. Residential ventilating fans under this specification can also be used in small commercial applications (e.g., bathroom of a restaurant).

Definition:

In-Line Ventilating Fan: A fan designed to be located within the building structure and requires ductwork on both intake and exhaust. Those in-line fans with only one intake are referred to as “single port” in-line fans, while those with multiple intake ports are referred to as “multi-port” in-line fans in this specification.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

6-9. Programmable Thermostats

Covered Products:

This specification shall cover programmable thermostats with at least two different programming periods (for weekday and weekend programming) and at least four possible temperature settings (i.e., wake, day, evening, and sleep settings).

Definition:

Comfort Setpoint Temperature: The temperature setting in degrees Fahrenheit or degrees Celsius for the time period during which the building is expected to be occupied, e.g., the early morning and evening hours.

Energy-Saving Setpoint Temperature: The setpoint temperature for the energy-saving periods, usually specified for both the heating and cooling seasons.

1) Set-Back Temperature. The setpoint temperature for the energy-saving periods during the heating season, generally at night and during unoccupied hours. temperature than the comfort setpoint temperature.

2) Set-Up Temperature. The setpoint temperature for the energy-saving periods during the cooling season, generally at night and during unoccupied hours. temperature than the comfort setpoint temperature.

Programmable Thermostat: A device that enables the user to set one or more time periods each day when a comfort setpoint temperature is maintained and one or more time periods each day when an energy-saving setpoint temperature is maintained. This device enables the user to save energy because the heating and cooling equipment is not running needlessly at a comfort temperature setpoint 24 hours per day. A programmable thermostat may be capable of controlling one or more zones of a conditioned space.

Setpoint Temperature: The temperature setting in degrees Fahrenheit or degrees Celsius for any given time period.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



6-10. Range Hood and Bathroom /Utility Room Ventilating Fans

Covered Products:

This specification shall cover range hoods and bathroom and utility room residential ventilating fans, both ducted and direct-discharge models, with airflow that does not exceed 500 cfm. Ventilating fans with sensors and timers may qualify under this specification. Residential ventilating fans under this specification can also be used in small commercial applications (e.g., bathroom of a restaurant).

Definition:

Residential Ventilating Fan: A ceiling, wall-mounted, or remotely mounted in-line fan designed to be used in a bathroom or utility room whose purpose is to move objectionable air from inside the building to the outdoors. Residential ventilating fans used for cooling (e.g., whole-house fans) or air circulation are excluded from this definition.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

6-11. Room Air Cleaners

Covered Products:

This specification shall cover room air cleaners.

Definition:

Fan with Filter and Electrostatic Plates: Air cleaner which operates with a fan and filter(s) that incorporates electrically charged plates or wires to electrostatically collect particulate matter.

Ion Generator: Air cleaner that incorporates an ion generator only.

Ozone Generator: A device intended to reduce or eliminate microorganisms within a chamber by means of introducing ozone into the room environment.

Room Air Cleaner: An electric cord-connected, portable appliance with the primary function of removing particulate matter from the air and which can be moved from room to room, including any electrostatic filter, ion generator, ozone generator or other type of air cleaner.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

6-12. Room Air Conditioners

Covered Products:

This specification shall cover room air conditioners.

Definition:

Casement-only: A room air conditioner designed for mounting in a casement window with an encased assembly with a width of 14.8 inches or less and a height of 11.2 inches or less.

Casement-slider: A room air conditioner with an encased assembly designed for mounting in a sliding or casement window with a width of 15.5 inches or less.

Reverse Cycle: The heating function found in certain room air conditioner models.

Room Air Conditioner (RAC): A device that is used to control temperature and humidity in an enclosed space. This definition applies to window RACs, through-the-wall RACs, casement and casement slider RACs, and reverse cycle RACs (or heat pump RACs.) This definition does not apply to a packaged terminal air conditioner (PTAC).

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

Lighting Products

7-1. Ballasts, Fluorescent, Linear T12 Lamps

Covered Products:

This specification shall cover ballasts for linear T12 lamps of the lengths and wattages listed in the table below.

Definition:

Ballast Efficacy Factor (BEF): The ratio of the ballast factor (BF) to input watts; it measures the efficiency of the lamp/ballast system relative to others using the same type and number of lamps. Ballast factor (BF), also called relative light output (RLO), is the ratio of the light output of a lamp(s) operated by a ballast, to the light output of the same lamp(s) operated by a reference ballast at rated current and voltage.

Fluorescent Ballast: The fluorescent ballast is designed to provide the necessary burst of energy to start a fluorescent lamp and then limits the electricity flow to provide an even discharge of current to sustain an even generation of light.

Standard:

Ballasts, Fluorescent, Linear T12 Lamps:

Product Type: Ballast, Fluorescent, Four-Foot, T12, 34-Watts

Number of Lamps: 1

Required BEF: 2.64 or higher

Product Type: Ballast, Fluorescent, Four-Foot, T12, 34-Watts

Number of Lamps: 2

Required BEF: 1.41 or higher

Product Type: Ballast, Fluorescent, Four-Foot, T12, 34-Watts

Number of Lamps: 3

Required BEF: 0.93 or higher

Product Type: Ballast, Fluorescent, Eight-Foot, T12, 60-Watts

Number of Lamps: 2

Required BEF: 0.80 or higher



New York City EPP Minimum Standards for Goods

7-2. Ballasts, Fluorescent, Linear T8 Lamps

Covered Products:

This specification shall cover ballasts for linear T8 lamps of the lengths and wattages listed in the table below.

Definition:

Ballast Efficacy Factor (BEF): The ratio of the ballast factor (BF) to input watts; it measures the efficiency of the lamp/ballast system relative to others using the same type and number of lamps. Ballast factor (BF), also called relative light output (RLO), is the ratio of the light output of a lamp(s) operated by a ballast, to the light output of the same lamp(s) operated by a reference ballast at rated current and voltage.

Fluorescent Ballast: The fluorescent ballast is designed to provide the necessary burst of energy to start a fluorescent lamp and then limits the electricity flow to provide an even discharge of current to sustain an even generation of light.

Standard:

Ballasts, Fluorescent, Linear T8 Lamps:

Product Type: Ballast, Fluorescent, Four-Foot, T8, 32-Watts
Number of Lamps: 1
Required BEF: 2.54 or higher

Product Type: Ballast, Fluorescent, Four-Foot, T8, 32-Watts
Number of Lamps: 2
Required BEF: 1.44 or higher

Product Type: Ballast, Fluorescent, Four-Foot, T8, 32-Watts
Number of Lamps: 3
Required BEF: 0.93 or higher

Product Type: Ballast, Fluorescent, Four-Foot, T8, 32-Watts
Number of Lamps: 4
Required BEF: 0.73 or higher

Product Type: Ballast, Fluorescent, Eight-Foot, T8, 59-Watts
Number of Lamps: 2
Required BEF: 0.80 or higher



New York City EPP Minimum Standards for Goods

7-3. Ballasts, Fluorescent, U-Bent T12 Lamps, 34-Watts

Covered Products:

This specification shall cover ballasts for 34-watt, U-bent T12 lamps with 1-3 lamps.

Definition:

Ballast Efficacy Factor (BEF): The ratio of the ballast factor (BF) to input watts; it measures the efficiency of the lamp/ballast system relative to others using the same type and number of lamps. Ballast factor (BF), also called relative light output (RLO), is the ratio of the light output of a lamp(s) operated by a ballast, to the light output of the same lamp(s) operated by a reference ballast at rated current and voltage.

Fluorescent Ballast: The fluorescent ballast is designed to provide the necessary burst of energy to start a fluorescent lamp and then limits the electricity flow to provide an even discharge of current to sustain an even generation of light.

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Standard:

Ballasts, Fluorescent, U-Bent T12 Lamps, 34-Watts:

Product Type: Ballast, Fluorescent, Four-Foot, T12, 34-Watts
Number of Lamps: 1
Required BEF: 2.64 or higher

Product Type: Ballast, Fluorescent, Four-Foot, T12, 34-Watts
Number of Lamps: 2
Required BEF: 1.41 or higher

Product Type: Ballast, Fluorescent, Four-Foot, T12, 34-Watts
Number of Lamps: 3
Required BEF: 0.93 or higher



New York City EPP Minimum Standards for Goods

7-4. Ballasts, Fluorescent, U-Bent T8 Lamps, 32-Watts

Covered Products:

This specification shall cover ballasts for 32-watt, U-bent T8 lamps with 1-4 lamps.

Definition:

Ballast Efficacy Factor (BEF): The ratio of the ballast factor (BF) to input watts; it measures the efficiency of the lamp/ballast system relative to others using the same type and number of lamps. Ballast factor (BF), also called relative light output (RLO), is the ratio of the light output of a lamp(s) operated by a ballast, to the light output of the same lamp(s) operated by a reference ballast at rated current and voltage.

Fluorescent Ballast: The fluorescent ballast is designed to provide the necessary burst of energy to start a fluorescent lamp and then limits the electricity flow to provide an even discharge of current to sustain an even generation of light.

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Standard:

Ballasts, Fluorescent, U-Bent T8 Lamps, 32-Watts:

Product Type: Ballast, Fluorescent, U-Tube, T8, 32-Watts
Number of Lamps: 1
Required BEF: 2.54 or higher

Product Type: Ballast, Fluorescent, U-Tube, T8, 32-Watts
Number of Lamps: 2
Required BEF: 1.44 or higher

Product Type: Ballast, Fluorescent, U-Tube, T8, 32-Watts
Number of Lamps: 3
Required BEF: 0.93 or higher

Product Type: Ballast, Fluorescent, U-Tube, T8, 32-Watts
Number of Lamps: 4
Required BEF: 0.73 or higher



New York City EPP Minimum Standards for Goods

7-5. Exit Signs

Covered Products:

This specification shall cover all signs that operate on 5 watts or less per sign.

Definition:

Exit Sign: A sign that is permanently fixed in place and used to identify a means of egress. For the purposes of ENERGY STAR, an exit sign must have an illuminated, legally-required legend. Exit signs that are required by section 7.10.4 of the Life Safety Code to remain illuminated via an emergency power source upon failure of the normal power supply must be designed to comply with this requirement.

Legally Required Legend: The words "EXIT", "TO EXIT", "STAIR", "TO STAIR", "STAIRS", "TO STAIRS", "FIRE ESCAPE", "TO FIRE ESCAPE", "FIRE EXIT", and "TO FIRE EXIT". This definition will also encompass other combinations of letters and symbols if and when these signs may be listed in accordance with UL 924.

Exit Sign Model: For the purposes of ENERGY STAR, an exit sign model is an exit sign in the configuration that is actually packaged and sold to end users under a unique model number or name. For exit sign models with an individual rechargeable battery, the battery charger shall be included as part of the exit sign model and shall be tested and qualified as a single product.

Input Power Demand: The amount of active power required to continuously illuminate an exit sign model, measured in watts (W). For exit sign models with rechargeable batteries, input power demand shall be measured with batteries at full charge.

Power Factor: A measurement that determines how effectively power drawn by the equipment is converted into actual usable power by an electric component. Power Factor is the ratio between active (useful) power, measured in watts, and apparent power, measured in volt-amperes.

Lagging Power Factor: With an inductive load, the current lags the applied voltage in a clockwise direction represented on a vector diagram, and is said to be a lagging power factor.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

7-6. Lamps, Compact Fluorescent, Pin-Based

Covered Products:

This category shall cover 2-pin and 4-pin compact fluorescent lamps.

Definition:

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Lamp Life: The rated hours of output for a fluorescent tube lamp measured using instant-start ballasts at three hours per start, except for T5 lamps, which shall be measured using program start ballasts.

Maximum Mercury: The total weight of mercury in a lamp.

Standard:

Lamp Type: 4-Pin
Maximum Lamp Life (Rated Hours): 12,000
Maximum Mercury (mg.): 5

Lamp Type: 2-Pin
Maximum Lamp Life (Rated Hours): 10,000
Maximum Mercury (mg.): 5



New York City EPP Minimum Standards for Goods

7-7. Lamps, Compact Fluorescent, Self-Ballasted, Screw Based

Covered Products:

This category shall cover self-ballasted compact fluorescent lamps.

Definition:

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Lamp Life: The rated hours of output for a fluorescent tube lamp measured using instant-start ballasts at three hours per start, except for T5 lamps, which shall be measured using program start ballasts.

Maximum Mercury: The total weight of mercury in a lamp.

Standard:

Lamp Type: Twist/Spiral or Loop (Self-Ballasted)

Minimum Lamp Life (Rated Hours): 8,000

Maximum Mercury (mg.): 5

Lamp Type: Other Self-Ballasted

Minimum Lamp Life (Rated Hours): 6,000

Maximum Mercury (mg.): 5

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

7-8. Lamps, Fluorescent Tube, Circline T9

Covered Products:

This category shall cover circline T9 fluorescent tube lamps of the lengths and wattages listed in the table below.

Definitions:

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Lamp Life: The rated hours of output for a fluorescent tube lamp measured using instant-start ballasts at three hours per start, except for T5 lamps, which shall be measured using program start ballasts.

Maximum Mercury: The total weight of mercury in a lamp.

Standard:

Lamp Characteristics			Standard		
Lamp Type	Length (Inches)	Watts	Minimum Mean Lumens	Minimum Lamp Life (Rated Hours)	Maximum Mercury (mg.)
T9 Circline	Any	22	675	12,000	20
T9 Circline	Any	32	1,300	12,000	20
T9 Circline	Any	40	1,975	12,000	20



New York City EPP Minimum Standards for Goods

7-9. Lamps, Fluorescent Tube, Linear T5, T8, T12

Covered Products:

This category shall cover linear T5, T8 and T12 fluorescent tube lamps of the lengths and wattages listed in the table below.

Definitions:

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Lamp Life: The rated hours of output for a fluorescent tube lamp measured using instant-start ballasts at three hours per start, except for T5 lamps, which shall be measured using program start ballasts.

Maximum Mercury: The total weight of mercury in a lamp.

Standard:

Lamp Characteristics			Standard		
Lamp Type	Length (Inches)	Watts	Minimum Mean Lumens	Minimum Lamp Life (Rated Hours)	Maximum Mercury (mg.)
T5	46-48	28	2,700	20,000	5
T5 High Output	45-46	54	4,600	20,000	5
T8	24	17	1,300	24,000	5
T8	36	25	2,000	24,000	5
T8	48	32	2,800	24,000	5
T8 Instant Start	96	59	5,400	18,000	10
T8 High Output	96	86	7,300	18,000	10
T8 Rapid Start	60	40	3,200	18,000	5
T8 Preheat	18	15	740	7,500	6
T8 Preheat	36	30	1,800	7,500	6
T12	24	30	1,870	18,000	10
T12	48	34	2,520	20,000	10
T12	48	40	2,660	20,000	10



New York City EPP Minimum Standards for Goods

Lamp Characteristics			Standard		
Lamp Type	Length (Inches)	Watts	Minimum Mean Lumens	Minimum Lamp Life (Rated Hours)	Maximum Mercury (mg.)
T12 Instant Start	48	39	2,400	9,000	10
T12 Instant Start	72	56	3,900	12,000	10
T12 Instant Start	96	60	4,950	12,000	10
T12 Instant Start	96	75	5,900	12,000	10
T12 High Output	48	60	3,200	15,000	15
T12 High Output	72	85	5,500	12,000	25
T12 High Output	96	95	6,900	12,000	15
T12 High Output	96	110	8,100	12,000	15
T12 Preheat	18	15	650	9,000	16
T12 Preheat	24	20	1,040	9,000	9.5



New York City EPP Minimum Standards for Goods

7-10. Lamps, Fluorescent Tube, U-Bent T8 & T12

Covered Products:

This category shall cover U-bent T8 and T12 fluorescent tube lamps of the lengths and wattages listed in the table below.

Definitions:

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Lamp Life: The rated hours of output for a fluorescent tube lamp measured using instant-start ballasts at three hours per start, except for T5 lamps, which shall be measured using program start ballasts.

Maximum Mercury: The total weight of mercury in a lamp.

Standard:

Lamp Characteristics			Standard		
Lamp Type	Length (Inches)	Watts	Minimum Mean Lumens	Minimum Lamp Life (Rated Hours)	Maximum Mercury (mg.)
T8 U-Bent, 6" Spacing	Any	32	2,325	18,000	8
T12 U-Bent, 6" Spacing	Any	31-32/34	2,000	18,000	8
T12 U-Bent, 6" Spacing	Any	40	2,700	18,000	8



New York City EPP Minimum Standards for Goods

7-11. Luminaires, Downlight, With Compact Fluorescent Lamps (13-32 Lamp Wattage)

Covered Products:

This specification shall cover downlight luminaires for 13-32 watt compact fluorescent lamps.

Definition:

Baffle: A light-absorbing element within the luminaire.

Downlight Luminaire: Luminaire is a complete lighting unit consisting of a fixture along with one or more ballasts and lamps. Downlight is a small, ceiling-mounted direct lighting unit that casts its light downward.

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Luminaire Efficacy Rating (LER): Describes the efficiency of a luminaire in terms of rated light output (in lumens) per watt of electricity use. Lumen is a measure of light output.

NEMA: National Electrical Manufacturers Association

Standard:

Luminaires, Downlight, With Compact Fluorescent Lamps (13-32 Lamp Wattage):

Luminaire Type (NEMA Designation): Open Optics
Required LER: 29 or higher

Luminaire Type (NEMA Designation): Baffled Optics
Required LER: 21 or higher

Luminaire Type (NEMA Designation): Lensed Optics
Required LER: 24 or higher



New York City EPP Minimum Standards for Goods

7-12. Luminaires, Downlight, With Metal Halide Lamps (<150 Watts)

Covered Products:

This specification shall cover downlight luminaires for metal halide lamps under 150 watts.

Definition:

Downlight Luminaire: Luminaire is a complete lighting unit consisting of a fixture along with one or more ballasts and lamps. Downlight is a small, ceiling-mounted direct lighting unit that casts its light downward.

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Luminaire Efficacy Rating (LER): Describes the efficiency of a luminaire in terms of rated light output (in lumens) per watt of electricity use. Lumen is a measure of light output.

NEMA: National Electrical Manufacturers Association

Standard:

Luminaires, Downlight, With Metal Halide Lamps (<150 Watts):

Luminaire Type (NEMA Designation): Open Optics
Required LER: 35 or higher

Luminaire Type (NEMA Designation): Lensed Optics
Required LER: 30 or higher



New York City EPP Minimum Standards for Goods

7-13. Luminaires, Fluorescent

Covered Products:

This specification shall cover fluorescent luminaires, including 2' x 2' Recessed, For U-Tube Lamps, 2' x 4' For Recessed Lamps, Plastic Wraparound, Strip Lights and Industrial Luminaires.

Definition:

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Luminaire: A complete lighting unit consisting of a fixture along with one or more ballasts and lamps.

Luminaire Efficacy Rating (LER): Describes the efficiency of a luminaire in terms of rated light output (in lumens) per watt of electricity use. Lumen is a measure of light output.

NEMA: National Electrical Manufacturers Association

Video Display Terminal (VDT): Computer monitor.

VDT-Preferred: A type of luminaire that meet Illuminating Engineering Society of North America (IESNA) recommendations for glare reduction, based on maximum allowable average luminance at 55° and higher angles from vertical.

Standard:

Luminaires, Fluorescent:

Luminaire Type (NEMA Designation): Lensed (FL)

Number of Lamps: 2; Required LER: 62 or higher

Number of Lamps: 3; Required LER: 61 or higher

Number of Lamps: 4; Required LER: 61 or higher

Luminaire Type (NEMA Designation): VDT-Preferred Louvered (FP)

Number of Lamps: 2; Required LER: 50 or higher

Number of Lamps: 3; Required LER: 51 or higher

Number of Lamps: 4; Required LER: 54 or higher

Luminaire Type (NEMA Designation): Four-Foot (FW)

Number of Lamps: 2; Required LER: 63 or higher

Number of Lamps: 4; Required LER: 62 or higher



New York City EPP Minimum Standards for Goods

Luminaire Type (NEMA Designation): Four-Foot (FS)
Number of Lamps: 1; Required LER: 70 or higher
Number of Lamps: 2; Required LER: 70 or higher

Luminaire Type (NEMA Designation): Four-Foot (FI)
Number of Lamps: 1; Required LER: 67 or higher

Luminaire Type (NEMA Designation): Eight-Foot (FI)
Number of Lamps: 2; Required LER: 68 or higher



New York City EPP Minimum Standards for Goods

7-14. Luminaires, Industrial HID, With High Pressure Sodium Lamps (<150 Lamp Wattage)

Covered Products:

This specification shall cover industrial HID luminaires with high pressure sodium lamps less than 150 watts,

Definition:

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Luminaire: A complete lighting unit consisting of a fixture along with one or more ballasts and lamps.

Luminaire Efficacy Rating (LER): Describes the efficiency of a luminaire in terms of rated light output (in lumens) per watt of electricity use. Lumen is a measure of light output.

Upward Efficiency: The portion of light directed up. Both high-bay and low-bay luminaires are available with opaque reflectors, which direct all or most of the light downward, and with transparent refractors, which direct some light up.

Standard:

Luminaires, Industrial HID, With High Pressure Sodium Lamps (<150 Lamp Wattage):

Upward Efficiency: 0%; Lamp Wattage: 150-399
Closed Fixture (HC) LER Required: 58 or higher
Open Fixture (HC) LER Required: 68 or higher

Upward Efficiency: 0%; Lamp Wattage: 400-999
Closed Fixture (HC) LER Required: 63 or higher
Open Fixture (HC) LER Required: 84 or higher

Upward Efficiency: 0%; Lamp Wattage: >1000
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required: N/A

Upward Efficiency: 1%-10%; Lamp Wattage: 150-399
Closed Fixture (HC) LER Required: 64 or higher
Open Fixture (HC) LER Required: 63 or higher



New York City EPP Minimum Standards for Goods

Upward Efficiency: 1%-10%; Lamp Wattage: 400-999
Closed Fixture (HC) LER Required: 82 or higher
Open Fixture (HC) LER Required: 89 or higher

Upward Efficiency: 1%-10%; Lamp Wattage: >1000
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required: 109 or higher

Upward Efficiency: 11%-20%; Lamp Wattage: 150-399
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required: 78 or higher

Upward Efficiency: 11%-20%; Lamp Wattage: 400-999
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required: 94 or higher

Upward Efficiency: 11%-20%; Lamp Wattage: >1000
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required: N/A

Upward Efficiency: >20%; Lamp Wattage: 150-399
Closed Fixture (HC) LER Required: 75 or higher
Open Fixture (HC) LER Required: 77 or higher

Upward Efficiency: >20%; Lamp Wattage: 400-999
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required: N/A

Upward Efficiency: >20%; Lamp Wattage: >1000
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required: N/A



New York City EPP Minimum Standards for Goods

7-15. Luminaires, Industrial HID, With Metal Halide Lamps (<150 Lamp Wattage)

Covered Products:

This specification shall cover Industrial HID luminaires with metal halide lamps that are less than 150 watts.

Definition:

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Luminaire: A complete lighting unit consisting of a fixture along with one or more ballasts and lamps.

Luminaire Efficacy Rating (LER): Describes the efficiency of a luminaire in terms of rated light output (in lumens) per watt of electricity use. Lumen is a measure of light output.

Upward Efficiency: The portion of light directed up. Both high-bay and low-bay luminaires are available with opaque reflectors, which direct all or most of the light downward, and with transparent refractors, which direct some light up.

Standard:

Luminaires, Industrial HID, With Metal Halide Lamps (<150 Lamp Wattage):

Upward Efficiency: 0%; Lamp Wattage: 150-399
Closed Fixture (HC) LER Required: 41 or higher
Open Fixture (HC) LER Required:N/A

Upward Efficiency: 0%; Lamp Wattage: 400-999
Closed Fixture (HC) LER Required: 53 or higher
Open Fixture (HC) LER Required:59 or higher

Upward Efficiency: 0%; Lamp Wattage: >1000
Closed Fixture (HC) LER Required: 77 or higher
Open Fixture (HC) LER Required:N/A

Upward Efficiency: 1%-10%; Lamp Wattage: 150-399
Closed Fixture (HC) LER Required: 56 or higher
Open Fixture (HC) LER Required:N/A



New York City EPP Minimum Standards for Goods

Upward Efficiency: 1%-10%; Lamp Wattage: 400-999
Closed Fixture (HC) LER Required: 62 or higher
Open Fixture (HC) LER Required:64 or higher

Upward Efficiency: 1%-10%; Lamp Wattage: >1000
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required:88 or higher

Upward Efficiency: >20%; Lamp Wattage: 150-399
Closed Fixture (HC) LER Required: 62 or higher
Open Fixture (HC) LER Required:77 or higher

Upward Efficiency: >20%; Lamp Wattage: 400-999
Closed Fixture (HC) LER Required: 65 or higher
Open Fixture (HC) LER Required:N/A

Upward Efficiency: >20%; Lamp Wattage: >1000
Closed Fixture (HC) LER Required: N/A
Open Fixture (HC) LER Required:N/A



New York City EPP Minimum Standards for Goods

7-16. Luminaires, Residential

Covered Products:

This specification shall cover indoor and outdoor light fixtures and recessed downlight retrofit kits intended primarily for residential type applications.

Definition:

Ballast: A device used with an electric-discharge lamp to obtain the necessary circuit conditions (voltage, current, and waveform) for starting and operating.

Lamp: Any glass envelope with a gas, coating, or filament that produces visible light when electricity is applied, but such term shall not include automotive light bulbs.

Light Fixture (Luminaire): A complete lighting unit consisting of a lamp or lamps and ballasting (when applicable) together with the parts designed to distribute the light, position and protect the lamps, and connect the lamps to the power supply.

Luminaire: A complete lighting unit consisting of a fixture along with one or more ballasts and lamps.

Optics: Include reflectors, baffles, lenses and/or diffusers, all which control the light distribution and the appearance of the lighted fixture.

Recessed Downlight Retrofit Kit: A non-linear lighting unit consisting of lamp(s), ballasting, optics, trim, and power supply connection designed to convert an incandescent or halogen type Insulated Ceiling (IC) or non-IC recessed downlight into an air-tight fixture that uses an energy-efficient light source.

Standard:

All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

Landscape Products

8-1. Garden Hose

Covered Products:

This category shall cover garden hoses composed of rubber and/or plastic. This category does not cover garden hoses manufactured from another material.

Definition:

Garden Hose: Conducts water through its tubing to a specific location using a nozzle.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Garden Hose:

Material Recovered: Rubber and/or Plastic

Postconsumer Recovered Material Content (%):60-65



New York City EPP Minimum Standards for Goods

8-2. Hydraulic Mulch

Covered Products:

This category shall cover paper-based and wood-based hydraulic mulch.

Definition:

Hydraulic Mulch: Material comprised of small pieces of cellulose fibers that is intended to stabilize soil, prevent wind and water erosion, and/or provide protection and warmth for seeds.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Hydraulic Mulch:

Product: Paper-Based Hydraulic Mulch

Material Recovered: Paper

Total Recovered Material Content (%): 100

Postconsumer Recovered Material Content (%):100

Product: Wood-Based Hydraulic Mulch

Material Recovered: Wood and Paper

Total Recovered Material Content (%): 100

Postconsumer Recovered Material Content (%):--

The recovered materials content levels refer to the dry weight of the fiber, exclusive of any dyes, wetting agents, seeds, fertilizer, or other non-cellulose additives.



New York City EPP Minimum Standards for Goods

8-3. Plastic Fencing

Covered Products:

This category shall cover plastic fencing. This category does not cover fencing manufactured from another material, such as wood.

Definition:

Plastic Fencing: Fencing composed of plastic that is typically used to control drifting snow and sand and as a warning or safety barrier at construction sites. Fencing used in these applications goes by many names, including snow fencing, temporary fencing, beach or dune fencing, warning barrier, and safety barrier.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Plastic Fencing:

Material Recovered: Plastic

Postconsumer Recovered Material Content (%): 60-100

Total Recovered Material Content (%): 90-100



New York City EPP Minimum Standards for Goods

8-4. Soaker Hose

Covered Products:

This category shall cover soaker hoses composed of rubber and/or plastic. This category does not cover soaker hoses manufactured from another material

Definition:

Soaker Hose: Perforated tubing that gently irrigates gardens or planted areas.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Soaker Hose:

Material Recovered: Rubber and/or Plastic

Postconsumer Recovered Material Content (%):60-70

PAGE INTENTIONALLY LEFT BLANK



Miscellaneous Products - Construction

9-1. Building Insulation

Covered Products:

This category shall cover building insulation made from rock wool or fiberglass. This category does not cover building insulation manufactured from another material.

Definitions:

Fiberglass: A material made from small fibers of glass twisted together, which is used for keeping buildings warm, or a plastic strengthened by these fibers and used for making structures such as the outsides of cars and boats.

Recovered Materials: Waste materials and byproducts that have been recovered or diverted from solid waste, but does not include materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Rock Wool: A composition of fibers manufactured from slag or natural rock.

Standard:

Product: Rock Wool
Material: Slag
Postconsumer Content (%): --
Total Recovered Materials (%): 75

Product: Fiberglass
Material: Glass Cullet
Postconsumer Content (%): --
Total Recovered Materials (%): 20-25

The recovered materials content levels are based on the weight (not volume) of materials in the insulating core only.



New York City EPP Minimum Standards for Goods

9-2. Carpet Adhesives

Covered Products:

This specification shall cover carpet adhesives.

Definition:

Carpet Adhesive: Any substance used to adhere carpet to a floor by surface attachment, including any latex multi-purpose floor adhesive, pressure-sensitive floor adhesive, vinyl-backed floor adhesive, latex seam adhesive, vinyl-backed seam sealer, cove base adhesive, tackless cushion adhesive and contact adhesive.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Carpet Adhesives: This product may not contain any volatile organic compound in any concentration exceeding that specified below:

Volatile Organic Compound : Formaldehyde
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 50
14-Day Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 31

Volatile Organic Compound : 2-ethyl-1-hexanol
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 300
14-Day Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 300

Volatile Organic Compound : Total Volatile Organic Compounds
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 8000
14-Day Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): -

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).

Products that are compliant with the Green Label Plus program of the Carpet and Rug Institute are also compliant with this standard.



New York City EPP Minimum Standards for Goods

9-3. Carpet Cushions

Covered Products:

This specification shall cover carpet cushions.

Definition:

Carpet cushion: Any kind of material placed under carpet to provide softness when it is walked upon.

Standard:

Carpet Cushions: This product may not contain any volatile organic compound in any concentration exceeding that specified below:

Volatile Organic Compound : Butylated Hydroxytoluene
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 300

Volatile Organic Compound : Formaldehyde
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 50

Volatile Organic Compound : 4-Phenylcyclohexene (4PCH)
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 50

Volatile Organic Compound : Total Volatile Organic Compounds
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 1000

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).

Products that are compliant with the Green Label Plus program of the Carpet and Rug Institute are also compliant with this standard.



New York City EPP Minimum Standards for Goods

9-4. Carpet Cushion – Bonded Polyurethane

Covered Products:

This specification shall cover bonded polyurethane carpet cushions.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Carpet Cushion- Bonded Polyurethane:

Material Recovered: Old Carpet Cushion
Post-consumer Content (%): 15-50
Total Recovered Materials Content (%):15-50



New York City EPP Minimum Standards for Goods

9-5. Carpet Cushion – Jute

Covered Products:

This specification shall cover jute carpet cushions.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Carpet Cushion – Jute:

Material Recovered: Burlap

Post-consumer Content (%): 40

Total Recovered Materials Content (%):40



New York City EPP Minimum Standards for Goods

9-6. Carpet Cushion – Rubber

Covered Products:

This specification shall cover rubber carpet cushions.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Carpet Cushion – Rubber:

Material Recovered: Tire Rubber

Post-consumer Content (%): 60-90

Total Recovered Materials Content (%):60-90



New York City EPP Minimum Standards for Goods

9-7. Carpet Cushion – Synthetic Fibers

Covered Products:

This specification shall cover synthetic fiber carpet cushions.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Carpet Cushion – Synthetic Fibers:

Material Recovered: Carpet Fabrication Scrap
Post-consumer Content (%): No Range Recommended
Total Recovered Materials Content (%):100



New York City EPP Minimum Standards for Goods

9-8. Carpets

Covered Products:

This specification shall cover carpets.

Definition:

Carpet: Any fabric used as a floor covering, but such term shall not include artificial turf.

Volatile Organic Compound (VOC): Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, as specified in part 51.00 of chapter 40 of the United States code of federal regulations.

Standard:

Carpets:

This product may not contain any volatile organic compound in any concentration exceeding that specified below:

Volatile Organic Compound: Formaldehyde
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 50
14-Day Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 30

Volatile Organic Compound: 4-Phenylcyclohexene
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 50
14-Day Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 17

Volatile Organic Compound: Styrene
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 410
14-Day Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 410

Volatile Organic Compound: Total Volatile Organic Compounds
24-Hour Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): 500
14-Day Testing Maximum Emission Factor ($\mu\text{g}/\text{m}^2\cdot\text{hr}$): -

The maximum content of VOCs shall be determined according to the American Society for Testing and Materials test method D 5116 (Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products).

Products that are compliant with the Green Label Plus program of the Carpet and Rug Institute are also compliant with this VOC standard.



New York City EPP Minimum Standards for Goods

9-9. Cement and Concrete

Covered Products:

This specification shall cover cement and concrete.

Definition:

Cenospheres: Additives similar to coal fly ash and ground granulated blast furnace (GGBF) slag. Cenospheres occur naturally in fly ash, the largest byproduct of coal-fired power plants. They are microscopic spheres made of silica and alumina and are filled with air or other gases.

Coal fly ash: A byproduct of coal burning at electric utility plants. It is called “fly” ash because it is transported from the combustion chamber by exhaust gases.

GGBF slag: A byproduct of iron blast furnaces. The slag is ground into granules finer than portland cement and can be used as an ingredient in concrete.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Cement and Concrete:

Material Recovered: Cenospheres

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%): Minimum 10% (by volume)

Material Recovered: Coal fly Ash

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%): No Range Recommended

Material Recovered: GGBF Slag

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%): No Range Recommended



New York City EPP Minimum Standards for Goods

Material Recovered: Silica Fume

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%):5-10% of cementitious material (dry weight basis)



New York City EPP Minimum Standards for Goods

9-10. Channelizers

Covered Products:

This specification shall cover channelizers.

Definition:

Channelizers: Barrels or drums that direct traffic around areas of road repair and construction.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Channelizers:

Material Recovered: Plastic

Post-consumer Content (%): 25-90

Total Recovered Materials Content (%):No Range Recommended

Material Recovered: Rubber (base only)

Post-consumer Content (%): 100

Total Recovered Materials Content (%):No Range Recommended



New York City EPP Minimum Standards for Goods

9-11. Delineators - Fixed

Covered Products:

This specification shall cover fixed delineators with surface mount or rubber bases.

Definition:

Delineators: Temporary pavement markers that come in many shapes, sizes, and compositions.

Basic Oxygen Furnace (BOF): Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

Electric Arc Furnace (EAF): Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Delineators - Fixed:

Material Recovered: Plastic

Post-consumer Content (%): 25-90

Total Recovered Materials Content (%): No Range Recommended

Material Recovered: Rubber (base only)

Post-consumer Content (%): 100

Total Recovered Materials Content (%): No Range Recommended

Material Recovered: Steel (BOF, base only)

Post-consumer Content (%): 16

Total Recovered Materials Content (%): 25-30

Material Recovered: Steel (EAF, base only)

Post-consumer Content (%): 67

Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

9-12. Delineators - Flexible

Covered Products:

This specification shall cover flexible delineators.

Definition:

Flexible Delineators: Stakes driven into the ground flexible enough so that vehicles can strike them without causing damage to the vehicle or the delineator.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Delineators - Flexible:

Material Recovered: Plastic PET

Post-consumer Content (%): 25-85

Total Recovered Materials Content (%): No Range Recommended



New York City EPP Minimum Standards for Goods

9-13. Electric Motors

Covered Products:

This specification shall cover induction motors rated 600 volts or less (random wound) or induction motors rated medium voltage of 5 kV or less (form wound).

Definition:

Electric Motors: a motor that converts electricity to mechanical work.

Open drip proof motor: has interior components that are cooled by a fan moving cool air through intake and exhaust vents.

Totally enclosed fan cooled motor: has an externally-mounted fan that blows air across the motor casing.

Standard:

Electric Motors:

Motor Size (HP)	Open Drip-Proof (ODP)			Totally Enclosed Fan-Cooled (TEFC)		
	6-pole (1200 rpm)	4-pole (1800 rpm)	2-pole (3600 rpm)	6-pole (1200 rpm)	4-pole (1800 rpm)	2-pole (3600 rpm)
1	82.5	85.5	77.0	82.5	85.5	77.0
1.5	86.5	86.5	84.0	87.5	86.5	84.0
2	87.5	86.5	85.5	88.5	86.5	85.5
3	88.5	89.5	85.5	89.5	89.5	86.5
5	89.5	89.5	86.5	89.5	89.5	88.5
7.5	90.2	91.0	88.5	91.0	91.7	89.5
10	91.7	91.7	89.5	91.0	91.7	90.2
15	91.7	93.0	90.2	91.7	92.4	91.0
20	92.4	93.0	91.0	91.7	93.0	91.0
25	93.0	93.6	91.7	93.0	93.6	91.7



New York City EPP Minimum Standards for Goods

Motor Size (HP)	Open Drip-Proof (ODP)	Totally Enclosed Fan-Cooled (TEFC)	Motor Size (HP)	Open Drip-Proof (ODP)	Totally Enclosed Fan-Cooled (TEFC)	Motor Size (HP)
	6-pole (1200 rpm)	4-pole (1800 rpm)		6-pole (1200 rpm)	4-pole (1800 rpm)	
30	93.6	94.1	91.7	93.0	93.6	91.7
40	94.1	94.1	92.4	94.1	94.1	92.4
50	94.1	94.5	93.0	94.1	94.5	93.0
60	94.5	95.0	93.6	94.5	95.0	93.6
75	94.5	95.0	93.6	94.5	95.4	93.6
100	95.0	95.4	93.6	95.0	95.4	94.1
125	95.0	95.4	94.1	95.0	95.4	95.0
150	95.4	95.8	94.1	95.8	95.8	95.0
200	95.4	95.8	95.0	95.8	96.2	95.4
250	95.4	95.8	95.0	95.8	96.2	95.8
300	95.4	95.8	95.4	95.8	96.2	95.8
350	95.4	95.8	95.4	95.8	96.2	95.8
400	95.8	95.8	95.8	95.8	96.2	95.8
450	96.2	96.2	95.8	95.8	96.2	95.8
500	96.2	96.2	95.8	95.8	96.2	95.8
Nominal Efficiencies for Induction Motors Rated Medium Voltage - 5 kV or less (Form Wound)						
250 - 500	95.0	95.0	94.5	95.0	95.0	95.0



New York City EPP Minimum Standards for Goods

9-14. Entry or Patio Doors, Residential

Covered Products:

This specification shall cover residential entry or patio doors.

Definition:

Door: A residential entry or patio door system including door leaf, frame, and lites, where applicable.

Entry door: An exterior door other than glass doors.

Patio door: A hinged or sliding glass door.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

9-15. Floor Tiles

Covered Products:

This specification shall cover floor tiles (heavy duty, commercial use).

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Floor Tiles:

Material Recovered: Rubber

Post-consumer Content (%): 90-100

Total Recovered Materials Content (%):No Range Recommended

Material Recovered: Plastic

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%):90-100



New York City EPP Minimum Standards for Goods

9-16. Flowable Fill

Covered Products:

This category shall cover flowable fill.

Definitions:

Coal Fly Ash: A byproduct of coal burning at electric utility plants. It is called “fly” ash because it is transported from the combustion chamber by exhaust gases.

Flowable Fill: A wet, flowable slurry made of coal fly ash, water, a coarse aggregate (such as foundry sand) and a portland cement that is used as an economical fill or backfill material. It can take the place of concrete, compacted soils, or sand commonly used to fill around pipes or void areas.

Foundry Sand: Clean, high-quality silica sand or lake sand from both ferrous and nonferrous metal castings.

Standard:

Flowable fill shall contain coal fly ash and/or ferrous foundry sands in a proportion deemed appropriate for the intended application by the procuring agency.



New York City EPP Minimum Standards for Goods

9-17. Insulation - Cellulose

Covered Products:

This specification shall cover cellulose insulation (loose fill and spray on).

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Cellulose:

Material Recovered: Post-consumer Paper

Post-consumer Content (%): 75

Total Recovered Materials Content (%):75



New York City EPP Minimum Standards for Goods

9-18. Insulation - Foam-In-Place

Covered Products:

This specification shall cover foam-in-place insulation.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Foam-In-Place:

Material Recovered: Recovered Material

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%):5



New York City EPP Minimum Standards for Goods

9-19. Insulation - Glass Fiber Reinforced

Covered Products:

This specification shall cover glass fiber reinforced insulation.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Glass Fiber Reinforced:

Material Recovered: Recovered Material

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%):6



New York City EPP Minimum Standards for Goods

9-20. Insulation - Laminated Paperboard

Covered Products:

This specification shall cover laminated paperboard used for insulation.

Definition:

Laminated paperboard: Boards made from one or more plies of kraft paper bonded together and used for decorative, structural, or insulating purpose.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Laminated Paperboard:

Material Recovered: Post-consumer Paper

Post-consumer Content (%): 100

Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

9-21. Insulation - Perlite Composition Board

Covered Products:

This specification shall cover perlite composition board insulation.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Perlite Composition Board:

Material Recovered: Post-consumer Paper
Post-consumer Content (%): 23
Total Recovered Materials Content (%): 23



New York City EPP Minimum Standards for Goods

9-22. Insulation - Phenolic Rigid Foam

Covered Products:

This specification shall cover phenolic rigid foam insulation.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Phenolic Rigid Foam:

Material Recovered: Recovered Material

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%): 5



New York City EPP Minimum Standards for Goods

9-23. Insulation - Plastic, Non-woven Batt

Covered Products:

This specification shall cover plastic, non-woven batt insulation.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Plastic, Non-woven Batt:

Material Recovered: Recovered and/or Post-consumer Plastic

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

9-24. Insulation - Plastic Rigid Foam, Polyisocyanurate/Polyurethane: Rigid Foam

Covered Products:

This specification shall cover plastic rigid foam, polyisocyanurate/polyurethane: rigid foam insulation.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Plastic Rigid Foam, Polyisocyanurate/Polyurethane: Rigid Foam:

Material Recovered: Recovered Material
Post-consumer Content (%): No Range Recommended
Total Recovered Materials Content (%): 9



New York City EPP Minimum Standards for Goods

9-25. Insulation - Structural Fiberboard

Covered Products:

This specification shall cover structural fiberboard used for insulation.

Definition:

Structural fiberboard: Panel made from wood, cane, or paper fibers matted together and used for sheathing, structural, and insulating purposes.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Insulation - Structural Fiberboard:

Material Recovered: Recovered Material

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%): 80-100



New York City EPP Minimum Standards for Goods

9-26. Modular Threshold Ramps

Covered Products:

This specification shall cover modular threshold ramps.

Definition:

Modular Threshold Ramps: Devices used to modify door thresholds and other small rises, particularly to improve access for people with disabilities.

Basic Oxygen Furnace (BOF): Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

Electric Arc Furnace (EAF): Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Modular Threshold Ramps:

Material Recovered: Steel (BOF)
Post-consumer Content (%): 16
Total Recovered Materials Content (%): 25-30

Material Recovered: Steel (EAF)
Post-consumer Content (%): 67
Total Recovered Materials Content (%): 100

Material Recovered: Aluminum
Post-consumer Content (%): No Range Recommended
Total Recovered Materials Content (%): 10

Material Recovered: Rubber
Post-consumer Content (%): 100
Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

9-27. Nonpressure Pipe

Covered Products:

This specification shall cover non-pressure pipes.

Definition:

Nonpressure Pipe: Pipe used for drainage and as conduit in construction, communications, municipal, industrial, agricultural, and mining applications. Most nonpressure pipe is made with polyvinyl chloride (PVC) and high-density polyethylene (HDPE).

Basic Oxygen Furnace (BOF): Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

Electric Arc Furnace (EAF): Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.

Nonpressure pipe: Pipe used for drainage and as conduit in construction, communications, municipal, industrial, agricultural, and mining applications. Most nonpressure pipe is made with polyvinyl chloride (PVC) and high-density polyethylene (HDPE).

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Nonpressure Pipe:

Material Recovered: Steel (BOF)
Post-consumer Content (%): 16
Total Recovered Materials Content (%):25-30

Material Recovered: Steel (EAF)
Post-consumer Content (%): 67
Total Recovered Materials Content (%):100



New York City EPP Minimum Standards for Goods

Material Recovered: Plastic (HDPE)
Post-consumer Content (%): 100
Total Recovered Materials Content (%):100

Material Recovered: Plastic (PVC)
Post-consumer Content (%): 5-15
Total Recovered Materials Content (%):25-100

Material Recovered: Cement
Post-consumer Content (%): No Range Recommended
Total Recovered Materials Content (%):No Range Recommended



New York City EPP Minimum Standards for Goods

9-28. Playground Equipment

Covered Products:

This specification shall cover playground equipment such as swings, swing sets, play structures, modular play structures, slides, bridges, platforms, canopies or roofs, crawl tunnels, and any hardware for these components.

Definition:

Basic Oxygen Furnace (BOF): Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

Electric Arc Furnace (EAF): Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.

Plastic: Includes both single and mixed plastic resins.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Playground Equipment:

Material Recovered: Plastic
Post-consumer Content (%): 90-100
Total Recovered Materials Content (%): 100

Material Recovered: Plastic Composite
Post-consumer Content (%): 50-75
Total Recovered Materials Content (%): 95-100

Material Recovered: Steel (BOF)
Post-consumer Content (%): 16
Total Recovered Materials Content (%): 95

Material Recovered: Steel (EAF)
Post-consumer Content (%): 50-100
Total Recovered Materials Content (%): 95-100



9-29. Residential Skylights

Covered Products:

This specification shall cover residential skylights.

Definition:

Skylight: An entire glazed unit designed for a sloped or horizontal application in the roof of a residential building to allow for natural daylighting. May be fixed or operable.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

9-30. Residential Windows & Tubular Daylighting Devices

Covered Products:

This specification shall cover residential exterior windows and tubular daylighting devices.

Definition:

Tubular Daylighting Device (Tubular Skylight): A device consisting of a glazed entrance aperture, a reflective cylindrical light pipe, and a glazed exit aperture installed in the roof of a residential building to allow for natural daylighting.

Window: An entire glazed unit designed for a vertical installation in an external wall of a residential building to allow for views and natural daylighting. May be fixed or operable.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

9-31. Restroom Dividers/Partitions, Steel

Covered Products:

This specification shall cover steel restroom dividers/partitions.

Definition:

Basic Oxygen Furnace (BOF): Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

Electric Arc Furnace (EAF): Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Restroom Divider/Partition: A barrier used to provide privacy in public restroom facilities.

Standard:

Restroom Dividers/Partitions, Steel:

Material Recovered: Steel (from BOF)
Post-consumer Content (%): 16
Total Recovered Materials Content (%): 25-30

Material Recovered: Steel (from EAF)
Post-consumer Content (%): 67
Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

9-32. Roof Products

Covered Products:

This specification shall cover all low-slope or steep slope roof products, such as roof coatings and single-ply membranes.

Definition:

Built-Up-Roof (BUR): Traditional hot asphalt or coal tar built-up roofing membrane assembly consists of alternating layers of felts, fabrics, or mats saturated with bitumen during manufacture, assembled in place, and adhered with applied layers of hot bitumen. Surfacing for the hot BUR can be aggregate embedded in hot asphalt; mineral-surface cap sheets; modified bitumen cap sheets; or smooth-surface applications or coatings.

Composite Shingle: Composed of a base material, either organic felt or glass fiber mat; asphalt; and surfacing material, generally in the form of mineral granules.

Low-Slope Roofs: Surfaces with a slope of 2:12 inches or less.

Low-Slope Roof Products: Products that are typically installed on low-slope surfaces such as single-ply membranes, built-up-roofs (BUR), modified bitumen, spray polyurethane foam, roof coatings, and standing-seam profiled metal. Some products that are typically installed on low slope roofs may also be installed on steep-slope roofs (e.g., single-ply membranes and roof coatings). For the purposes of this definition, the roof product will constitute the uppermost surface of the building structure.

Metal Roof Component: Metal roof product designed to resemble a traditional steep-slope residential product such as shingle, tile, shake, or slate.

Metal Roof Panel: Metal roofing systems are divided into two categories, architectural and structural. Architectural metal roofs usually require a slope of at least 3:12. Structural metal roofs can be used on roofs with slopes as low as 1/4:12. Steel and aluminum sheets are commonly used to fabricate metal roof panels. Steel requires a corrosion resistant metal coating such as zinc, aluminum, alloys of zinc-aluminum, or tin. Metallic coated steel includes galvanized steel, aluminized steel, zinc-aluminum-coated steel and terne-coated steel. Metallic coated steels are also painted to provide additional corrosion protection, as well as color.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy



New York City EPP Minimum Standards for Goods

have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

9-33. Roofing Materials

Covered Products:

This specification shall cover roofing materials.

Definition:

Basic Oxygen Furnace (BOF): Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

Electric Arc Furnace (EAF): Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Roofing Materials: Material Recovered Post-consumer Content (%) Total Recovered Materials Content (%)

Steel (BOF) 16 25-30

Steel (EAF) 67 100

Aluminum 20-95 20-95

Fiber (felt) or Fiber Composite 50-100 50-100

Rubber 12-100 100

Plastic or Plastic/Rubber Composite 100 100

Wood/Plastic Composite No Range Recommended 100

Cement No Range Recommended No Range Recommended



New York City EPP Minimum Standards for Goods

9-34. Shower Dividers/Partitions, Steel

Covered Products:

This specification shall cover steel shower dividers/partitions.

Definition:

Basic Oxygen Furnace (BOF): Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

Electric Arc Furnace (EAF): Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Shower Divider/Partition: A barrier used to provide privacy in public restroom facilities.

Standard:

Shower Dividers/Partitions, Steel:

Material Recovered: Steel (from BOF)
Post-consumer Content (%): 16
Total Recovered Materials Content (%): 25-30

Material Recovered: Steel (from EAF)
Post-consumer Content (%): 67
Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

9-35. Traffic Barricades

Covered Products:

This specification shall cover traffic barricades of all kinds including 'A' frame types, 'I' beam types, as well as free standing vertical and folding breakaway types.

Definition:

Traffic Barricades: Used to redirect or restrict traffic in areas of highway construction or repair.

Basic Oxygen Furnace (BOF): Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

Electric Arc Furnace (EAF): Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Traffic Barricades:

Material Recovered: Plastic (High Density Polyethylene [HDPE], Low-Density Polyethylene [LDPE], Polyethylene terephthalate [PET])

Post-consumer Content (%): 80-100

Total Recovered Materials Content (%): 100

Material Recovered: Steel (BOF)

Post-consumer Content (%): 16

Total Recovered Materials Content (%): 25-30

Material Recovered: Steel (EAF)

Post-consumer Content (%): 67

Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

Material Recovered: Fiberglass

Post-consumer Content (%): No Range Recommended

Total Recovered Materials Content (%): No Range Recommended

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

Miscellaneous Products - Non Construction

10-1. Mats, Rubber, Plastic or Rubber/Plastic Composite

Covered Products:

This category shall cover mats made from rubber, plastic or rubber/plastic composite. This category does not cover mats manufactured from another material.

Definition:

Mat: Temporary or semi-permanent protective floor covering used for numerous applications, including home and office carpet protection, car and truck floor board protection, traction on slippery surfaces, cushion from floor hardness, and reduction of injury risk during athletic events.

Standard:

Mat:

Material Recovered: Rubber
Postconsumer Content (%): 75-100
Total Recovered Materials Content (%):85-100

Material Recovered: Plastic
Postconsumer Content (%): 10-100
Total Recovered Materials Content (%):100

Material Recovered: Rubber/Plastic Composite
Postconsumer Content (%): 100
Total Recovered Materials Content (%):100

The recommended recovered materials content levels are based on the dry weight of the raw materials, exclusive of any additives such as adhesives, binders, or coloring agents.



New York City EPP Minimum Standards for Goods

10-2. Pallets, Wood, Plastic or Paperboard

Covered Products:

This category shall cover all pallets made from wood, plastic (plastic lumber or thermoformed) or paperboard. This category does not cover pallets manufactured from another material.

Definition:

Pallet: A portable platform for storing or moving cargo or freight.

Standard:

Pallets, Wood, Plastic or Paperboard:

Product: Wooden pallets
Material Recovered: Wood
Postconsumer Content (%): 95-100

Product: Plastic lumber
Material Recovered: Plastic
Postconsumer Content (%): 100

Product: Thermoformed
Material Recovered: Plastic
Postconsumer Content (%): 25-50

Product: Paperboard pallets
Material Recovered: Paperboard
Postconsumer Content (%): 50



New York City EPP Minimum Standards for Goods

10-3. Park Benches, Plastic

Covered Products:

This category shall cover park benches made from plastic or plastic composite. This category does not cover park benches manufactured from another material.

Definition:

Park Bench: Recreational furniture found in parks, outdoor recreational facilities, and the grounds of office buildings and other facilities.

Plastics: Includes both single and mixed plastic resins.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Park Benches, Plastic:

Material Recovered: Plastics
Postconsumer Content (%): 90-100
Total Recovered Materials Content (%):100

Material Recovered: Plastic Composites
Postconsumer Content (%): 50-100
Total Recovered Materials Content (%):100

The recommended recovered materials content levels are based on the dry weight of the raw materials, exclusive of any additives such as adhesives, binders, or coloring agents.

Park benches made with recovered plastics may also contain other recovered materials such as sawdust, wood, or fiberglass. The percentage of these materials contained in the product would also count toward the recovered materials content level of the item.



New York City EPP Minimum Standards for Goods

10-4. Signs, Plastic or Aluminum

Covered Products:

This category shall apply to signs made from plastic or aluminum. This category does not cover signs manufactured from another material.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Sign: Used for identification and directional purposes for public roads and highways, and inside and outside office buildings, museums, parks, and other public places.

Standard:

Signs, Plastic or Aluminum:

Item/Material Recovered: Plastic Signs
Postconsumer Content (%): 80-100
Total Recovered Materials Content (%):80-100

Item/Material Recovered: Aluminum Signs
Postconsumer Content (%): 25
Total Recovered Materials Content (%):25



New York City EPP Minimum Standards for Goods

10-5. Sign Posts/Supports, Plastic or Steel

Covered Products:

This category shall cover sign posts/supports made from plastic or steel.

This category does not cover sign posts/supports manufactured from another material.

Definition:

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Standard:

Sign Posts/Supports, Plastic or Steel:

Item/Material Recovered: Plastic Sign Posts/Supports
Postconsumer Content (%): 80-100
Total Recovered Materials Content (%):80-100

Item/Material Recovered: Steel Sign Posts/Supports
Postconsumer Content (%): 16/67
Total Recovered Materials Content (%):25-30/100

The range in required recovered materials content levels for steel in this table reflect the fact that the designated items can be made from steel manufactured in either a Basic Oxygen Furnace (BOF) or an Electric Arc Furnace (EAF). Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel. Steel from the EAF process contains a total of 100% recovered steel, of which 67% is post-consumer.



New York City EPP Minimum Standards for Goods

10-6. Traffic Cones, Plastic or Crumb Rubber

Covered Products:

This category shall apply to traffic cones made from plastic (PVC or LDPE) or crumb rubber. This category does not cover traffic cones manufactured from another material.

Definition:

Low Density Polyethylene (LDPE): A plastic resin used for both rigid containers and plastic film applications such as plastic bags and film wrap.

Polyvinyl Chloride (PVC): A family of plastic copolymers, also known as vinyl. PVC is used to make products such as pipes, bottles, upholstery, and automotive parts.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Standard:

Traffic Cones, Plastic or Crumb Rubber:

Material Recovered: Plastic (PVC and LDPE)
Postconsumer Content (%): --
Total Recovered Materials Content (%): 50-100

Material Recovered: Crumb Rubber
Postconsumer Content (%): --
Total Recovered Materials Content (%): 50-100

The recommended recovered materials content levels are based on the dry weight of the raw materials, exclusive of any additives such as adhesives, binders, or coloring agents.



New York City EPP Minimum Standards for Goods

10-7. Trash Bags, Plastic

Covered Products:

This category shall cover plastic trash bags. This category does not cover trash bags manufactured from another material.

Definition:

Plastic Trash Bags: Plastic Trash Bags

Standard:

Plastic Trash Bags:

Product: Plastic Trash Bags

Material Recovered: Plastic

Postconsumer Content (%): 10-100



New York City EPP Minimum Standards for Goods

10-8. Waste Receptacles / Recycling Containers, Office, Plastic,

Covered Products:

This category shall cover all office waste receptacles and recycling containers composed of plastic, steel or paper (corrugated, solid fiber boxes or industrial paperboard). This category does not cover waste receptacles/recycling containers manufactured from another material.

Definition:

Recovered Material: Waste materials and byproducts which have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process.

Postconsumer Recovered Material: A material or finished product that has served its intended use and has been diverted or recovered from waste destined for disposal, having completed its life as a consumer item. Postconsumer material is a part of the broader category of recovered materials.

Waste Receptacle / Recycling Container: Used to collect and transport waste materials in offices, either in desk side or larger, more centralized containers.

Standard:

Waste Receptacles / Recycling Containers, Office, Plastic, Steel or Paper:

Material Recovered: Plastic
Postconsumer Content (%): 20 - 100
Total Recovered Materials Content (%): --

Material Recovered: Steel
Postconsumer Content (%): 16
Total Recovered Materials Content (%): 25-30

Material Recovered: Paper (Corrugated)
Postconsumer Content (%): 25-50
Total Recovered Materials Content (%): 25-50

Material Recovered: Paper (Solid Fiber Boxes)
Postconsumer Content (%): 40
Total Recovered Materials Content (%): --

Material Recovered: Paper (Industrial Paperboard)
Postconsumer Content (%): 40-80
Total Recovered Materials Content (%): 100



New York City EPP Minimum Standards for Goods

The recommended recovered materials content levels are based on the dry weight of the raw materials, exclusive of any additives such as adhesives, binders, or coloring agents.

The recommended recovered materials content levels for steel in this table reflect the fact that the designated items are made from steel manufactured in a Basic Oxygen Furnace (BOF). Steel from the BOF process contains 25-30% total recovered materials, of which 16% is post-consumer steel.

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

Office Equipment

11-1. Combination Printer/Fax Machines

Covered Products:

This category shall apply to all combination printer/fax machines.

Definition:

Combination Printer/Fax Machine: Imaging equipment manufactured as a standard model that serves as both a fully-functional printer and fax machine.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.



New York City EPP Minimum Standards for Goods

11-2. Computers

Covered Products:

This category shall cover all computers.

Definition:

Computer: A device which performs logical operations and processes data. Computers are composed of, at a minimum: (1) a central processing unit (CPU) to perform operations; (2) user input devices such as a keyboard, mouse, digitizer or game controller; and (3) a display screen to output information. For the purposes of this category, computers include both stationary and portable units, including desktop computers, gaming consoles, integrated computers, notebook computers, tablet PCs, desktop-derived servers and workstations. Although computers must be capable of using input devices and displays, as noted in numbers 2 and 3 above, computer systems do not need to include these devices on shipment to meet this definition.

Desktop Computer: A computer where the main unit is intended to be located in a permanent location, often on a desk or on the floor. Desktops are not designed for portability and utilize an external monitor, keyboard, and mouse. Desktops are designed for a broad range of home and office applications including, email, web browsing, word processing, standard graphics applications, gaming, etc.

Desktop-Derived Server: A desktop-derived server is a computer that typically uses desktop components in a tower form factor, but is designed explicitly to be a host for other computers or applications. For the purposes of this category, a computer must be marketed as a server and have the following characteristics to be considered a desktop-derived server:

- Designed and placed on the market as a Class B product per EuroNorm EN55022:1998 under the EMC Directive 89/336/EEC and has no more than single processor capability (1 socket on board);
- Designed in a pedestal, tower, or other form factor similar to those of desktop computers such that all data processing, storage, and network interfacing is contained within one box/product;
- Designed to operate in a high-reliability, high-availability application environment where the computer must be operational 24 hours/day and 7 days/week, and unscheduled downtime is extremely low (on the order of hours/year);
- Capable of operating in a simultaneous multi-user environment serving several users through networked client units; and
- Shipped with an industry accepted operating system for standard server applications (e.g., Windows NT, Windows 2003 Server, Mac OS X Server, OS/400, OS/390, Linux, Unix and Solaris).



New York City EPP Minimum Standards for Goods

Desktop-derived servers are designed to perform functions such as processing information for other systems, providing network infrastructure services (e.g., archiving), data hosting and running web servers.

This definition does not cover mid-range or large servers, defined as:

- Designed and placed on the market as a Class A product per EuroNorm EN55022:1998 under the EMC Directive 89/336/EEC and designed and capable of having a single or dual processor capability (1 or greater sockets on board);
- Placed on the market as a Class B product, but hardware upgraded from a Class A product, per EuroNorm EN55022:1998 under the EMC Directive 89/336/EEC and designed capable of having a single or dual processor capability (1 or greater sockets on board); and
- Designed and placed on the market as a Class B product per EuroNorm EN55022:1998 under the EMC Directive 89/336/EEC and designed and capable of having a minimum dual processor capability (2 sockets on board)

Display: A commercially-available, electronic product with a display screen and its associated electronics encased in a single housing, or within the computer housing (e.g., notebook or integrated computer), that is capable of displaying output information from a computer via one or more inputs, such as a VGA, DVI, and/or IEEE 1394. Examples of display technologies are the cathode-ray tube (CRT) and liquid crystal display (LCD).

Game Consoles: Stand alone computers whose primary use is to play video games. For the purposes of this category, game consoles must use a hardware architecture based on typical computer components (e.g., processors, system memory, video architecture, optical and/or hard drives, etc.). The primary input for game consoles are special hand held controllers rather than the mouse and keyboard used by more conventional computer types. Game consoles are also equipped with audio visual outputs for use with televisions as the primary display, rather than an external monitor or integrated display. These devices do not typically use a conventional operating system, but often perform a variety of multimedia functions such as: DVD/CD playback, digital picture viewing, and digital music playback.

Integrated Computer: A desktop system in which the computer and display function as a single unit which receives its ac power through a single cable. Integrated computers come in one of two possible forms: (1) a system where the display and computer are physically combined into a single unit; or (2) a system packaged as a single system where the display is separate but is connected to the main chassis by a dc power cord and both the computer and display are powered from a single power supply. As a subset of desktop computers, integrated computers are typically designed to provide similar functionality as desktop systems.



New York City EPP Minimum Standards for Goods

Notebook and Tablet Computers: A computer designed specifically for portability and to be operated for extended periods of time without a direct connection to an ac power source. Notebooks and tablets must utilize an integrated monitor and be capable of operation off an integrated battery or other portable power source. In addition, most notebooks and tablets use an external power supply and have an integrated keyboard and pointing device, though tablets use touch-sensitive screens. Notebook and tablet computers are typically designed to provide similar functionality to desktops except within a portable device. For the purposes of this category, docking stations are considered accessories and therefore, the performance levels associated with notebooks presented in Table 1 of Section 3, below, do not include them.

Workstation: For the purposes of this category, to qualify as a workstation, a computer must:

- Be marketed as a workstation;
- Have a mean time between failures (MTBF) of at least 15,000 hours based on either Bellcore TR-NWT-000332, issue 6, 12/97 or field collected data; and
- Support error-correcting code (ECC) and/or buffered memory.
- In addition, a workstation must meet three of the following six optional characteristics:
 - Have supplemental power support for high-end graphics (i.e., PCI-E 6-pin 12V supplemental power feed);
 - System is wired for greater than x4 PCI-E on the motherboard in addition to the graphics slot(s) and/or PCI-X support;
 - Does not support Uniform Memory Access (UMA) graphics;
 - Includes 5 or more PCI, PCIe or PCI-X slots;
 - Capable of multi-processor support for two or more processors (must support physically separate processor packages/sockets, i.e., not met with support for a single multi core processor); and/or
 - Be qualified by at least 2 Independent Software Vendor (ISV) product certifications; these certifications can be in process, but must be completed within 3 months of qualification.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous



New York City EPP Minimum Standards for Goods

Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.



New York City EPP Minimum Standards for Goods

11-3. Computer Monitors (Min. 12 Inch Screen Size)

Covered Products:

This category shall cover all computer monitors with a viewable diagonal screen size greater than 12 inches and capable of being powered by a separate AC wall outlet or a battery unit that is sold with an AC adapter.

Definition:

Computer Monitor: A commercially-available, electronic product with a display screen and its associated electronics encased in a single housing that is capable of displaying output information from a computer via one or more inputs, such as VGA, DVI, and/or IEEE 1394. The monitor usually relies upon a cathode-ray tube (CRT), liquid crystal display (LCD), or other display device. This definition is intended primarily to cover standard monitors designed for use with computers. Computer monitors with a tuner/receiver are included under this definition if they are marketed and sold to consumers as computer monitors (i.e., focusing on computer monitor as the primary function) or as dual function computer monitors and televisions. However, products with a tuner/receiver and computer capability that are marketed and sold as televisions are not included in this definition.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.



New York City EPP Minimum Standards for Goods

11-4. Computer Peripherals

Covered Products:

This category shall cover any computer keyboards, computer mice and card readers.

Standard:

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.



New York City EPP Minimum Standards for Goods

11-5. Copiers

Covered Products:

The Energy Star and RoHS Directive provisions of this minimum standard shall apply to all standard-sized copiers designed to handle A4 or 8.5" x 11" paper and large format copiers designed to handle A2 or 17" x 22" paper or larger. The Double-Siding and Recycled Performance provisions of this minimum standard shall apply to copiers that can print at a rate of twenty pages or faster per minute.

Definition:

Copier: A commercial reprographic imaging unit whose sole function is the production of duplicates from a graphic hard copy original. A copier must include a marking system, an imaging system, and a paper handling module.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.

Double-Siding: Any copier that can print at a rate of twenty pages or faster per minute shall have the capacity to print double-sided.

Recycled Performance: This product shall perform equally well with paper containing postconsumer recycled material as with paper containing no postconsumer recycled material.



New York City EPP Minimum Standards for Goods

11-6. Fax Machines, Plain Paper

Covered Products:

This category shall cover fax machines.

Definition:

Fax Machine: Imaging equipment, manufactured as a standard model, that serves as a hard copy output device whose primary function is sending and receiving information. Plain paper fax machines are covered in this definition (e.g., ink jet/bubble jet, laser/LED, and thermal transfer). The unit must be capable of being powered from a wall outlet.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.



New York City EPP Minimum Standards for Goods

11-7. Mailing Machines

Covered Products:

This category shall apply to all mailing machines.

Definition:

Mailing Machine: Imaging equipment that serves to print postage onto mail pieces. The unit must be capable of being powered from a wall outlet.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.



New York City EPP Minimum Standards for Goods

11-8. Multifunction Devices (Copier Plus)

Covered Products:

This Energy Star and RoHS Directive provisions of this minimum standard shall cover multifunction devices that perform the function of a copier as well as the functions of at least one of the following devices: printer, facsimile machine or scanner. The Double-Siding and Recycled Performance provisions of this minimum standard shall apply to multifunction devices that can print at a rate of twenty pages or faster per minute.

Definition:

Base Unit: The most basic version of a multifunction device that is actually sold as a fully operational model. The base unit can be designed and shipped as a single piece or as a combination of functionally integrated components. The base unit must allow copying and one or both of the additional core functions of printing or faxing. The base unit does not include any external power-consuming accessories that may be sold separately.

Multifunction Device (MFD): A physically integrated device or a combination of functionally integrated components (the "base unit") that produces hard copy duplicates from graphical hard copy originals (distinct from single sheet convenience copying, see next paragraph) as well as performing one or both of the following core functions: printing of documents (from digital information received from direct connect computers, networked computers, file servers and fax transmissions) or faxing (send and receive). A MFD may also include scanning to computer file or any other capabilities not listed in this definition. The device may be connected to a network, and may output black & white, gray scale, or color images. This definition covers products that are marketed and sold as multifunction equipment whose primary function is copying, but that are able to perform one or both of the additional core functions of printing or faxing. Devices whose primary function is faxing and offer limited sheet copying capabilities (so-called single sheet "convenience copying") are not covered under this definition.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules



New York City EPP Minimum Standards for Goods

of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.

Double-Siding: Any copier that can print at a rate of twenty pages or faster per minute shall have the capacity to print double-sided.

Recycled Performance: This product shall perform equally well with paper containing postconsumer recycled material as with paper containing no postconsumer recycled material.



New York City EPP Minimum Standards for Goods

11-9. Printers

Covered Products:

This category shall cover all printers, including printers that can be upgraded to a multifunctional device.

Definition:

Local Area Network: Any two or more computers and associated devices that share a common communications line or wireless link and typically share the resources of a single processor or server within a small geographic area.

Printer: Imaging equipment, manufactured as a standard model that serves as a hard copy output device, and is capable of receiving information from single-user or networked computers. In addition, the unit must be capable of being powered from a wall outlet.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.

Double-Siding: Any copier that can print at a rate of twenty pages or faster per minute shall have the capacity to print double-sided.



New York City EPP Minimum Standards for Goods

11-10. Scanners

Covered Products:

This category covers scanners.

Definition:

Scanner: An electro-optical device for converting color or black-and-white information into electronic images that can be stored, edited, converted, or transmitted primarily in a personal computing environment. Scanners defined as such are typically used for digitizing hard-copy images. This definition covers widely-used desktop scanners (e.g., flatbed, sheet-fed, and film scanners) and does not cover high-end office document management scanners. This definition is for stand-alone scanners; it does not cover multifunction products with scanning capabilities, network scanners (i.e., scanners that connect exclusively to a network and are capable of managing the scanned information for transmissions to multiple locations on the network), or scanners that are not powered directly by the building power supply.

Standard:

Energy Star: All energy-using products for which the United States Environmental Protection Agency and the United States Department of Energy have developed energy efficiency standards for compliance with the Energy Star program shall be ENERGY STAR labeled.

RoHS Directive: This product may not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in any quantity exceeding that permitted under Section 11-10 of the Rules of the City of New York. Products that are compliant with European Union Directive 2002/95/EC on the Restriction of the use of Certain Hazardous Substances in Electrical and Electronic Equipment are also compliant with Section 11-10.

PAGE INTENTIONALLY LEFT BLANK



Paper Products

12-1. Bathroom Tissue, Commercial

Covered Products:

This category shall cover bathroom tissue used in rolls or sheets.

Definition:

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;



New York City EPP Minimum Standards for Goods

(iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;

(iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and

(v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

Bathroom Tissue:

Item: Bathroom Tissue

Postconsumer Recovered Fiber (%): 20-60

Recovered Fiber (%):20-100



New York City EPP Minimum Standards for Goods

12-2. Envelope Paper

Covered Products:

This category shall cover wove and kraft envelopes.

Definition:

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;

(iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;



New York City EPP Minimum Standards for Goods

(iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and

(v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

Envelope Paper:

Item: Wove

Postconsumer Recovered Fiber (%): 30

Recovered Fiber (%):30

Item: Kraft (White and colored including manila)

Postconsumer Recovered Fiber (%): 10-20

Recovered Fiber (%):10-20

Item: Kraft (Unbleached)

Postconsumer Recovered Fiber (%): 10

Recovered Fiber (%):10



New York City EPP Minimum Standards for Goods

12-3. Facial Tissue, Commercial

Covered Products:

This category shall cover facial tissue used for personal care.

Definition:

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;

(iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;



New York City EPP Minimum Standards for Goods

(iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and

(v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

Facial Tissue:

Item: Facial Tissue

Postconsumer Recovered Fiber (%): 10-15

Recovered Fiber (%):10-100



New York City EPP Minimum Standards for Goods

12-4. File Folders

Covered Products:

This category shall cover manila or colored file folder.

Definition:

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;

(iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;



New York City EPP Minimum Standards for Goods

(iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and

(v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

File Folders (manila and colored):

Item: File Folders (manila and colored)
Postconsumer Recovered Fiber (%): 30
Recovered Fiber (%):30



New York City EPP Minimum Standards for Goods

12-5. General Purpose Industrial Wiper, Paper

Covered Products:

This category shall cover general-purpose industrial wipers used in cleaning and wiping applications.

Definition:

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;



New York City EPP Minimum Standards for Goods

- (iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;
- (iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and
- (v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

General Purpose Industrial Wipers:

Item: General Purpose Industrial Wipers
Postconsumer Recovered Fiber (%): 40
Recovered Fiber (%):40-100



New York City EPP Minimum Standards for Goods

12-6. Paper Napkins, Commercial

Covered Products:

This category shall cover paper napkin used in food service applications, facial tissue used for personal care.

Definition:

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;



New York City EPP Minimum Standards for Goods

(iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;

(iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and

(v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

Paper Napkins:

Item: Paper Napkins

Postconsumer Recovered Fiber (%): 30-60

Recovered Fiber (%):30-100



New York City EPP Minimum Standards for Goods

12-7. Paper Towels, Commercial

Covered Products:

This category shall cover paper towels used in rolls or sheets.

Definition:

Tablet paper: Loose leaf paper, notebooks, note pads, adding machine rolls and cash register rolls.

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;



New York City EPP Minimum Standards for Goods

(iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;

(iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and

(v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

Paper Towels:

Item: Paper Towels

Postconsumer Recovered Fiber (%): 40-60

Recovered Fiber (%):40-100



New York City EPP Minimum Standards for Goods

12-8. Reprographic Paper

Covered Products:

This category shall cover business papers typically used for copying, duplicating or printing.

Definition:

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;



New York City EPP Minimum Standards for Goods

(iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;

(iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and

(v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

Reprographic Paper (e.g., mimeo and duplicator paper, high-speed copier paper, and bond paper):

Item: Reprographic Paper (e.g., mimeo and duplicator paper, high-speed copier paper, and bond paper)

Postconsumer Recovered Fiber (%): 30

Recovered Fiber (%):30



New York City EPP Minimum Standards for Goods

12-9. Tablet Paper

Covered Products:

This category shall cover loose leaf paper, notebooks, note pads, adding machine rolls and cash register rolls.

Definition:

Postconsumer Recovered Fiber: This term means: (1) Paper, paperboard and fibrous wastes from retail stores, office buildings, homes and so forth, after they have passed through their end-usage as a consumer item including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards and used cordage; and (2) All paper, paperboard and fibrous wastes that enter and are collected from municipal solid waste;

Recovered Fiber: Waste material and byproducts that have been recovered or diverted from solid waste, but such term does not include those materials and byproducts generated from, and commonly reused within, an original manufacturing process. This definition includes:

(1) Postconsumer materials such as—

(i) Paper, paperboard, and fibrous wastes from retail stores, office buildings, homes, and so forth, after they have passed through their end-usage as a consumer item, including: Used corrugated boxes; old newspapers; old magazines; mixed waste paper; tabulating cards; and used cordage; and

(ii) All paper, paperboard, and fibrous wastes that enter and are collected from municipal solid waste, and

(2) Manufacturing, forest residues, and other wastes such as—

(i) Dry paper and paperboard waste generated after completion of the papermaking process (that is, those manufacturing operations up to and including the cutting and trimming of the paper machine reel in smaller rolls of rough sheets) including: Envelope cuttings, bindery trimmings, and other paper and paperboard waste, resulting from printing, cutting, forming, and other converting operations; bag, box, and carton manufacturing wastes; and butt rolls, mill wrappers, and rejected unused stock; and

(ii) Finished paper and paperboard from obsolete inventories of paper and paperboard manufacturers, merchants, wholesalers, dealers, printers, converters, or others;



New York City EPP Minimum Standards for Goods

(iii) Fibrous byproducts of harvesting, manufacturing, extractive, or wood-cutting processes, flax, straw, linters, bagasse, slash, and other forest residues;

(iv) Wastes generated by the conversion of goods made from fibrous material (that is, waste rope from cordage manufacture, textile mill waste, and cuttings); and

(v) Fibers recovered from waste water which otherwise would enter the waste stream.

Standard:

Tablet Paper (e.g., offset paper such as note pads, stationery, and other writing papers):

Item: Tablet Paper (e.g., offset paper such as note pads, stationery, and other writing papers)

Postconsumer Recovered Fiber (%): 30

Recovered Fiber (%):30

PAGE INTENTIONALLY LEFT BLANK



New York City EPP Minimum Standards for Goods

Plumbing Fixtures

13-1. Lavatory Faucets

Covered Products:

This specification shall cover lavatory faucets.

Definition:

Lavatory Faucet: A device which controls the flow of liquid from a pipe or the like by opening or closing an orifice.

Standard:

Lavatory Faucets:

Product: Faucet

Water Efficiency Requirement: < 2.0 gallons per minute



New York City EPP Minimum Standards for Goods

13-2. Showerheads, Residential and Commercial

Covered Products:

This specification shall cover showerheads.

Definition:

Showerhead: A perforated nozzle that showers water. This definition includes hand-held showerheads.

Standard:

Showerheads, Residential and Commercial:

Product: Showerhead

Water Efficiency Requirement: < 2.2 gallons per minute



New York City EPP Minimum Standards for Goods

13-3. Toilets, Residential and Commercial

Covered Products:

This specification shall cover residential and commercial toilets.

Definition:

Toilet: A bathroom fixture consisting of a bowl, usually with a detachable, hinged seat and lid, and a device for flushing with water. There are three common varieties of toilets: gravity flow, (siphon-jet) flush valve, and pressurized tank systems.

Standard:

Toilets, Residential and Commercial:

Product: Toilet

Water Efficiency Requirement: < 1.6 gallons per flush



New York City EPP Minimum Standards for Goods

13-4. Urinals, Residential and Commercial

Covered Products:

This specification shall cover residential and commercial urinals.

Definition:

Urinal: A plumbing fixture which receives only liquid body waste and, on demand, conveys the waste through a trap seal into a gravity drainage system, except such term does not include fixtures designed for installations in prisons.

Standard:

Urinals, Residential and Commercial:

Product: Urinal

Water Efficiency Requirement: < 1.0 gallons per flush



New York City EPP Minimum Standards for Goods

Air Conditioners, Air-Cooled	110	Combination Printer/Fax Machines	207
Air Conditioners, Central (<65,000 Btu/h)116		Combination TV with VCR, DVD, or VCR/DVD Units	93
Air Conditioners, Central, Gas/Electric Package Units (<65,000 Btu/h).....	117	Computer Monitors (Min. 12 Inch Screen Size)	212
Air Conditioners, Gas/Electric Package Units	111	Computer Peripherals	213
Air Source Heat Pumps (<65,000 Btu/h) .	118	Computers	208
Amplifiers/Pre-Amplifiers, Consumer	87	Concrete Bond Breakers	36
Answering Machines	88	Concrete Curing Compounds.....	37
Ballasts, Fluorescent, Linear T12 Lamps	130	Concrete Surface Retarders.....	38
Ballasts, Fluorescent, Linear T8 Lamps ..	131	Copiers	214
Ballasts, Fluorescent, U-Bent T12 Lamps, 34-Watts	132	Cordless Telephones	95
Ballasts, Fluorescent, U-Bent T8 Lamps, 32-Watts	133	Dehumidifiers.....	22
Bathroom Tissue, Commercial	222	Delineators - Fixed.....	167
Beverage Vending Machines.....	11	Delineators - Flexible	168
Boilers and Boiler/Hot Water Heaters (<300,000 Btu/h)	119	Dishwashers, Standard-Sized.....	23
Bottled Water Coolers, Cold and/or Hot Water.....	12	Dry Fog Coatings	39
Carpet Adhesives	157	DVD Products.....	96
Carpet Cushion – Bonded Polyurethane .	159	Electric Motors	169
Carpet Cushion – Jute.....	160	Entry or Patio Doors, Residential.....	171
Carpet Cushion – Rubber	161	Envelope Paper	224
Carpet Cushion – Synthetic Fibers	162	Equalizers, Consumer	97
Carpet Cushions	158	Exit Signs.....	134
Carpets	163	Extended Power Adaptors.....	98
Cassette Decks, Consumer	89	Facial Tissue, Commercial	226
CD Players, Consumer.....	90	Faux Finishing Coatings	40
CD Recorders, Consumer.....	91	Fax Machines, Plain Paper	215
Ceiling Fans	120	File Folders	228
Cement and Concrete	164	Fire-Resistive Coatings.....	41
Channelizers	166	Fire-Retardant Coatings - Clear.....	42
Chillers, Air-Cooled.....	112	Fire-Retardant Coatings - Opaque	43
Chillers, Water-Cooled	113	Flat Paint.....	44
Clear Wood Coating - Clear-Brushing Lacquers	28	Floor Coatings	45
Clear Wood Coating - Conversion Varnishes.....	30	Floor Tiles	172
Clear Wood Coating - Lacquers (Including Lacquer Sanding Sealers).....	31	Form Release Compounds	46
Clear Wood Coating - Sanding Sealers (Other Than Lacquers)	32	Freezers	13
Clear Wood Coating - Varnishes.....	34	Freezers, Upright, Chest and Compact....	24
Clock Radios, Consumer	92	Fryers, Electric or Gas	14
Clothes Washers	21	Furnaces and Furnace/Hot Water Heaters (<340,000 Btu/h).....	121
		Garden Hose	151
		General Purpose Industrial Wiper, Paper	230
		Graphic Arts Coatings (Sign Paints).....	47
		Ground Source Heat Pumps (Geothermal)	122
		Heat Pumps, Air Source	114



New York City EPP Minimum Standards for Goods

High Temperature Coatings.....	48	Multi-Color Coatings	59
Hot Food Holding Cabinets.....	15	Multifunction Devices (Copier Plus).....	217
Hydraulic Mulch	152	Nonflat High-Gloss Coatings.....	60
Ice Cream Freezers.....	16	Nonflat Paint	61
Industrial Maintenance (IM) Coatings	49	Nonpressure Pipe	184
In-Line Ventilating Fan	124	Pallets, Wood, Plastic or Paperboard.....	198
Insulation - Cellulose	174	Paper Napkins, Commercial.....	232
Insulation - Foam-In-Place.....	175	Paper Towels, Commercial	234
Insulation - Glass Fiber Reinforced	176	Park Benches, Plastic.....	199
Insulation - Laminated Paperboard	177	Plastic Fencing	153
Insulation - Perlite Composition Board	178	Playground Equipment	186
Insulation - Phenolic Rigid Foam.....	179	Powered Speakers, Consumer	102
Insulation - Plastic Rigid Foam, Polyisocyanurate/Polyurethane Rigid Foam	181	Pre-Treatment Wash Primers	62
Insulation - Plastic, Non-woven Batt	180	Primers for Flat Paint	63
Insulation - Structural Fiberboard	182	Primers for Non-Flat Paint.....	64
Lacquers - Pigmented	51	Primers, Sealers, and Undercoaters	65
Laserdisc Players, Consumer.....	99	Printers.....	219
Latex Paint – Consolidated.....	52	Programmable Thermostats.....	125
Latex Paint – Reprocessed Grey, Brown, Earhtones and Other Dark Colors	54	Quick-Dry Enamels	67
Latex Paint – Reprocessed White, Off-White and Pastel Colors.....	53	Quick-Dry Primers, Sealers, and Undercoaters	69
Lavatory Faucets	241	Range Hood and Bathroom /Utility Room Ventilating Fans.....	126
Low Solids Coatings	55	Receivers, Consumer	103
Luminaires, Downlight, With Compact Fluorescent Lamps (13-32 Lamp Wattage)	141	Recycled Coatings	71
Luminaires, Downlight, With Metal Halide Lamps (<150 Watts)	142	Refrigerator-Freezers.....	18
Luminaires, Fluorescent.....	143	Refrigerators	17
Luminaires, Industrial HID, With High Pressure Sodium Lamps (<150 Lamp Wattage)	145	Refrigerators and Refrigerator-Freezers, Standard-Sized and Compact.....	26
Luminaires, Industrial HID, With Metal Halide Lamps (<150 Lamp Wattage) ...	147	Reprographic Paper	236
Luminaires, Residential.....	149	Residential Skylights.....	187
Magnesite Cement Coatings	56	Residential Windows & Tubular Daylighting Devices.....	188
Mailing Machines	216	Restroom Dividers/Partitions, Steel	189
Mastic Texture Coatings	57	Roof Coatings.....	72
Mats, Rubber, Plastic or Rubber/Plastic Composite	197	Roof Coatings (Bituminous)	73
Metallic Pigmented Coatings	58	Roof Primers (Bituminous)	74
Microwave Ovens	25	Roof Products.....	190
Mini- and Midi-Systems, Consumer	100	Roofing Materials	192
Minidisc Players, Consumer	101	Room Air Cleaners.....	127
Modular Threshold Ramps.....	183	Room Air Conditioners.....	128
		Rust Preventative / Anti-Corrosive Paint...	75
		Scanners	220
		Shellacs - Clear	76
		Shellacs - Opaque.....	77
		Shower Dividers/Partitions, Steel	193
		Showerheads, Residential and Commercial	242



New York City EPP Minimum Standards for Goods

Sign Posts/Supports, Plastic or Steel	201	Toilets, Residential and Commercial	243
Signs, Plastic or Aluminum	200	Traffic Barricades	194
Soaker Hose	154	Traffic Cones, Plastic or Crumb Rubber .	202
Specialty Primers, Sealers and Undercoaters	78	Trash Bags, Plastic	203
Stains	80	Tuners, Consumer	107
Steam Cookers, Electric or Gas	19	Urinals, Residential and Commercial	244
Swimming Pool Coatings and Swimming Pool Repair and Maintenance Coatings	81	VCR	108
Table Radios, Consumer	104	Waste Receptacles / Recycling Containers, Office, Plastic,	204
Tablet Paper	238	Waterproofing Concrete / Masonry Sealers	83
Televisions	105	Waterproofing Sealers	84
Thermoplastic Rubber Coatings and Mastics	82	Wood Preservatives	85