

A. INTRODUCTION

This chapter of the EIS describes the traffic and parking characteristics and potential impacts associated with the proposed project. As described in Chapter 1, “Project Description,” the proposed project would include 900 dwelling units (DUs), 8,800 gsf of local retail space, 330,000 gsf of auto showroom and maintenance, a 20,000 gsf public health club, 36,000 gsf NYPD stables, and 225 accessory parking spaces. Vehicle access to the site would be via curb cuts along W. 53rd Street and W. 54th Street (see Figure 1-6, in Chapter 1).

The project site is presently vacant and undergoing as-of-right foundation work and is conservatively assumed to be vacant under No-Build conditions. The primary vehicle routes to and from the site are expected to be Twelfth Avenue/Miller Highway (Route 9A), Eleventh Avenue, and Tenth Avenue, with local access via W. 53rd and W. 54th Streets. Public transit in the vicinity of the site consists of three local bus routes, the north-south running M11, and cross-town service provided by the M31, which travels southbound/northbound south of W. 57th Street via Eleventh and Tenth Avenues, respectively, with a terminus on W. 54th Street adjacent to the project site, and M57. Subway service on both IRT and IND lines is available at the W. 59th Street-Columbus Circle subway station, located approximately one-half mile to the east of the site with an entrance at W. 57th Street and Eighth Avenue. Other nearby subway stations are at W. 50th/ 51st Streets at Seventh and Eighth Avenues and W. 53rd Street at Broadway. Pedestrian activity is relatively light on sidewalks immediately adjacent to the site. Sidewalks on blocks to the east experience progressively higher volumes. Refer to Chapter 14, “Transit and Pedestrians,” for more details.

B. METHODOLOGY

The study area selected for the traffic analysis is shown in Figure 13-1. The area was selected to encompass those roadways and other facilities most likely to be used by the majority of persons and vehicles traveling to and from the site. The study area is bounded on the north by W. 57th Street, on the south by W. 51st Street, on the east by Tenth Avenue, and on the west by Twelfth Avenue. Sixteen intersections within the study area are analyzed for vehicular traffic during the weekday AM (8-9 AM), weekday midday (12-1 PM), weekday PM (5-6 PM), and Saturday midday (1-2 PM) peak hours. All sixteen of these are signal-controlled intersections. As the proposed project’s 225 parking space accessory garage would not fully accommodate projected demand, the analysis also includes an evaluation off-street public parking facilities in the area.

This chapter describes in detail the 2008 existing conditions for traffic and parking in the study area. The 2011 future conditions without the project (the No-Build condition) are then determined, including additional transportation-system demand and any changes in the roadways and parking systems expected by 2011. The increase in travel demand resulting from the proposed project is then projected and added to future No-Build conditions to develop the 2011 Build condition for detailed analysis. Significant impacts from project generated demands are then identified. Chapter 19 of this

EIS presents proposed measures to mitigate any transportation or other impacts associated with the proposed project.

B. EXISTING CONDITIONS

The existing 2008 traffic and parking conditions in the study area were developed from data collected from different sources. The traffic network was based on on-going traffic studies in the study area. Additional manual turning movement and automatic traffic recorder (ATR) counts conducted in May and June 2008 were then used to complement this network. Data on existing parking capacity and utilization were collected during field surveys in October and November 2007. Figures 13-2, 13-3, 13-4, and 13-5 show the resultant traffic volumes for existing conditions during the weekday AM, midday, PM, and Saturday midday peak hours, respectively.

Vehicular Traffic

The study area is typical of the Manhattan grid, composed of major north-south avenues and principal and minor east-west cross-streets. To the east, Broadway traverses the grid diagonally, intercepting the pattern at W. 65th Street/Columbus Avenue and W. 59th Street/Columbus Circle. On the western edge of the grid is Twelfth Avenue/Route 9A, which extends from the Henry Hudson and George Washington bridges in the north to South Ferry at the southern tip of Manhattan. Twelfth Avenue, which is two-way, generally has six to eight lanes. There are protected left-turn bays at most cross-streets. Twelfth Avenue serves as a distribution roadway for highway traffic, as well as serving as the western-most express arterial in Manhattan. Twelfth Avenue two-way peak hour traffic volumes vary from approximately 5,800 vph to 7,200 vph near W. 55th Street. The avenue does not host any NYCT bus routes along its length.

The Manhattan Cruise Terminal (formerly the New York Passenger Ship Terminal) is located on the west side of Twelfth Avenue between W. 54th and W. 46th Streets. The terminal generates substantial traffic when one or more vessels are in port.

East of Twelfth Avenue is Eleventh Avenue, a two-way arterial with two lanes in each direction plus parking. Parking is typically restricted, especially southbound in AM peak hour. The avenue, which is 70 feet wide, provides left-turn lanes at most intersections. Southbound volumes range from 1,000 to 1,100 vph in the AM peak period and from 150 to 400 vph northbound in the PM peak period. Because Eleventh Avenue commences northbound traffic flow just south of the study area at W. 44th Street, the northbound volume is substantially lower than southbound volumes in most peak periods. Eleventh Avenue south of W. 54th Street does not have a regular NYCT bus route however, M31 route travels southbound on the avenue between W. 57th to a terminus on W. 54th streets (see discussion in Chapter 14).

Tenth Avenue and Ninth Avenue are adjacent one-way arterials forming a main north-south arterial couplet and truck routes on the West Side. Tenth Avenue is northbound, has five traffic lanes plus parking, and has its heaviest peak traffic flow in the PM period with peak hour volumes ranging from 1,900 to 2,100 vph in the study area. Ninth Avenue just east of the study area is southbound and

contains four traffic lanes plus parking in the study area. Traffic on Ninth Avenue peaks in the AM with peak hour volumes ranging between 1,700 and 2,200 vph.

The principal cross-street in the study area is W. 57th Street. W. 57th Street, which is the northern boundary of the study area, has a 60-foot-travelway that provides two travel lanes in each direction plus parking. It commences at Twelfth Avenue and is therefore an attractive cross-street for through traffic flows. In the PM peak period, two-way peak hour volumes on West 57th Street range from 900 vph to 1,000 vph in the study area. This major cross-street also hosts the M57 and M31 bus routes in the study area.

Adjacent to the project site are W. 53rd Street and W. 54th Street, both local streets on the Manhattan grid. Each roadway is 30 to 32 feet in width between Eleventh and Tenth Avenues, with W. 53rd Street one-way westbound and W. 54th Street one-way eastbound. However, W. 54th Street is two-way for the one block segment between Eleventh and Twelfth Avenues. W. 53rd Street ends directly west of the project site in a T-intersection at Eleventh Avenue, as De Witt Clinton Park occupies a two-square block area bounded by W. 54th Street, Eleventh Avenue, W. 52nd Street, and Twelfth Avenue. Both of these cross-streets have low traffic volumes with peak hour volumes generally ranging between 200 and 350 vehicles per hour.

Capacity Analysis

The capacity analyses at study area intersections are based on the methodology presented in the *Highway Capacity Software Version HCS 5.3*. Traffic data required for these analyses includes volumes on each approach, as well as various other physical and operational characteristics. Signal timing plans for each intersection were obtained from NYCDOT. Field inventories were also conducted to document curbside parking regulations, vehicle classifications, and other relevant characteristics.

The HCM methodology expresses quality of flow in terms of level of service (LOS), which is based on the amount of delay that a driver typically experiences at an intersection. Levels of service range from A, with minimal delay, to F, which represents long delays and congestion. Generally, congestion and poor service are characterized by both LOS E and F. The following defines the LOS/delay relationship for the HCM methodology for signalized intersection.

Intersection Level of Service Criteria

Level of Service (LOS)	Average Delay per Vehicle (seconds)	
	Signalized Intersections	Unsignalized Intersections
A	less than 10.1	less than 10.1
B	10.1 to 20.0	10.1 to 15.0
C	20.1 to 35.0	15.1 to 25.0
D	35.1 to 55.0	25.1 to 35.0
E	55.1 to 80.0	35.1 to 50.0
F	greater than 80.0	greater than 50.0

Source: 2000 Highway Capacity Manual.

The methodology also provides a volume-to-capacity (v/c) ratio for intersection traffic movements. A ratio of under 0.85 is generally considered to represent non-congested conditions in Manhattan, whereas above this value, congestion increases. At a v/c ratio of between 0.95 and 1.0, near-capacity conditions are reached and delays can become substantial. Ratios of greater than 1.05 indicate saturated conditions with queuing.

There is also one stop-controlled, unsignalized intersection approach analyzed in the study area.

For unsignalized intersections, the HCM methodology generally assumes that major street traffic is not affected by minor street flows. Left turns from the major street are assumed to be affected by minor street flows. Left turns from the major street are assumed to be affected by the opposing, or oncoming, major street flow. Minor street traffic is obviously affected by all conflicting movements. Similar to signalized intersections, the HCM methodology expresses the quality of flow at unsignalized intersections in terms of LOS based on the amount of delay that a driver experiences. This relationship differs somewhat from the criteria used for signalized intersections, primarily because drivers expect different levels of performance from the two different kinds of transportation facilities. For unsignalized intersections, levels of service range from A, with minimal delay (10 seconds or less per vehicle), to F, which represents long delays (over 50 seconds per vehicle.)

Table 13-1 shows the results of the capacity analysis at sixteen study area intersections analyzed in the four peak hours. The table highlights (with an asterisk *) those intersection movements that operate at LOS E or F and/or have a high v/c ratio (generally 0.90 and above), and are therefore considered to be congested. Table 13-1 shows that 9 of the 16 study area intersections have one or more congested movements in one or more of the analyzed peak hours. There are 6 intersections with one or more congested movements in the weekday AM peak hour, 7 in the weekday midday, 5 in the weekday PM, and 6 in the Saturday peak hours. These are discussed in more detail below.

Tenth Avenue Corridor

Along the Tenth Avenue corridor, in the weekday AM, midday, and PM peak hours there are no intersections that have a congested movement.

In the Saturday midday peak hour, there is one congested movement. The westbound movement at the intersection of Tenth Avenue and W. 55th Street operates at LOS E, with 79.6 seconds of delay and a v/c ratio of 1.05.

Eleventh Avenue Corridor

On the Eleventh Avenue corridor, all congested movements are on eastbound or westbound cross-street approaches. There are two or more congested movements in each of the four analyzed peak hours.

Signalized Intersection	Lane Group	2008 Existing AM Peak Hour			2008 Existing MD Peak Hour			2008 Existing PM Peak Hour			2008 Existing SMD Peak Hour		
		V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS
10th Avenue (NB) @ West 52nd Street (EB)	EB-LT	0.86	42.8	D	0.66	31.5	C	0.62	30.2	C	0.53	27.6	C
	NB-TR	0.60	9.8	A	0.71	11.5	B	0.50	8.6	A	0.68	10.9	B
10th Avenue (NB) @ West 53rd Street (WB)	WB-TR	0.75	37.5	D	0.65	32.4	C	0.81	42.0	D	0.67	33.0	C
	NB-LT	0.59	9.7	A	0.69	11.1	B	0.47	8.4	A	0.64	10.4	B
10th Avenue (NB) @ West 54th Street (EB)	EB-LT	0.71	34.6	C	0.48	27.1	C	0.47	26.9	C	0.27	23.4	C
	NB-TR	0.59	9.7	A	0.70	11.3	B	0.49	8.6	A	0.66	10.6	B
10th Avenue (NB) @ West 55th Street (WB)	WB-TR	0.88	48.8	D	0.73	35.6	D	0.86	45.4	D	1.05	79.6	E *
	NB-LT	0.58	9.6	A	0.66	10.7	B	0.49	8.5	A	0.62	10.1	B
10th Avenue (NB) @ West 57th Street (E-W)	EB-LT	0.73	26.8	C	0.56	24.3	C	0.43	21.7	C	0.44	22.2	C
	WB-TR	0.55	21.5	C	0.80	30.9	C	0.64	25.6	C	0.68	26.7	C
	NB-LT	0.68	16.7	B	0.56	12.9	B	0.56	12.6	B	0.53	12.5	B
	NB-R				0.38	16.1	B	0.24	13.9	B	0.28	14.3	B
11th Avenue (N-S) @ West 51st Street (WB)	WB-L	0.21	19.3	B	0.39	32.5	C	0.36	31.9	C	0.42	33.3	C
	WB-TR	0.27	19.9	B	0.65	39.7	D	0.76	45.4	D	0.69	41.5	D
	NB-L	0.16	14.7	B	0.08	6.6	A	0.08	3.3	A	0.07	6.4	A
	NB-T	0.47	15.8	B	0.15	6.5	A	0.08	2.8	A	0.11	6.2	A
	SB-TR	0.84	21.3	C	0.56	10.3	B	0.54	10.0	A	0.52	9.7	A
11th Avenue (N-S) @ West 52nd Street (EB)	EB-LTR	0.64	26.8	C	0.98	72.3	E *	0.70	40.4	D	0.71	40.8	D
	NB-TR	0.51	16.5	B	0.21	6.8	A	0.13	3.0	A	0.17	6.6	A
	SB-L	0.45	17.1	B	0.13	6.8	A	0.18	7.2	A	0.13	6.8	A
	SB-T	0.80	19.2	B	0.51	9.6	A	0.50	9.4	A	0.47	9.0	A
11th Avenue (N-S) @ West 53rd Street (WB)	WB-LR	0.59	29.5	C	0.94	69.2	E *	0.83	53.5	D	1.02	90.1	F *
	NB-T	0.46	13.5	B	0.21	6.9	A	0.12	2.9	A	0.15	6.5	A
	SB-T	0.70	13.2	B	0.45	8.8	A	0.50	9.4	A	0.44	8.8	A
11th Avenue (N-S) @ West 54th Street (EB)	EB-LTR	0.66	31.7	C	0.57	36.6	D	0.52	34.9	C	0.30	29.9	C
	NB-L	0.40	17.7	B	0.13	7.0	A	0.37	7.1	A	0.34	10.3	B
	NB-TR	0.52	14.4	B	0.27	7.3	A	0.16	3.1	A	0.22	6.9	A
	SB-L	0.31	11.0	B	0.14	6.9	A	0.13	6.7	A	0.07	6.2	A
	SB-T	0.62	11.5	B									
	SB-R	0.04	9.6	A									
	SB-TR				0.45	8.9	A	0.51	9.5	A	0.46	9.0	A
11th Avenue (N-S) @ West 55th Street (WB)	WB-LTR	0.90	49.9	D *	1.05	91.9	F *	0.57	32.5	C	1.05	80.0	E *
	NB-L	0.73	34.7	C	0.23	8.2	A	0.15	3.8	A	0.19	7.7	A
	NB-T	0.40	12.7	B	0.20	6.8	A	0.11	2.9	A	0.17	6.6	A
	SB-TR	0.45	9.2	A									
	SB-T				0.37	8.1	A	0.41	8.4	A	0.33	7.6	A
SB-R				0.15	6.7	A	0.14	6.6	A	0.16	6.7	A	
11th Avenue (N-S) @ West 57th Street (E-W)	EB-L	0.97	80.5	F *	0.51	25.6	C	0.58	30.4	C	0.37	21.4	C
	EB-TR	1.05	86.9	F *	0.72	39.5	D	0.91	60.6	E *	0.62	34.5	C
	WB-L	0.83	49.0	D	0.92	63.0	E *	0.62	26.6	C	0.89	54.1	D
	WB-TR	0.99	73.5	E *	0.96	65.6	E *	1.05	86.8	F *	0.94	61.3	E *
	NB-L	0.09	15.5	B	0.15	16.2	B	0.22	15.2	B	0.28	18.6	B
	NB-TR	0.57	20.5	C	0.38	17.7	B	0.33	14.5	B	0.37	17.6	B
	SB-L	0.64	29.7	C	0.29	18.4	B	0.44	21.5	C	0.27	17.9	B
	SB-TR	0.70	20.3	C	0.48	19.1	B	0.55	20.2	C	0.47	19.0	B
12th Avenue (N-S) @ West 52nd Street (EB)	EB-LTR	--	--	--	--	--	--	--	--	--	--	--	
	NB-TR	0.93	34.9	C *	1.05	58.7	E *	1.05	46.9	D *	0.90	29.4	C *
	SB-L	1.05	131.1	F *	1.05	132.9	F *	1.05	142.2	F *	1.05	138.4	F *
	SB-T	1.01	21.4	C *	0.66	12.8	B	0.74	12.0	B	0.79	15.8	B
12th Avenue (N-S) @ West 54th Street (E-W)	WB-R	0.48	60.0	E *	0.26	39.1	D	0.62	67.4	E *	0.48	44.7	D
	NB-TR	0.80	15.1	B	0.82	17.0	B	0.93	8.4	A *	0.69	13.4	B
	SB-L	0.51	59.4	E *	0.37	40.8	D	0.42	57.6	E *	0.20	37.4	D
	SB-T	1.05	37.2	D *	0.63	12.3	B	0.72	12.4	B	0.77	15.1	B
	(Service Rd) SB-T	0.54	3.7	A	0.30	9.0	A	0.28	7.3	A	0.27	8.7	A
12th Avenue (N-S) @ West 55th Street (WB)	WB-L	1.05	119.9	F *	0.62	48.1	D	0.60	61.7	E *	0.99	87.1	F *
	WB-R	0.39	56.6	E *	0.59	46.7	D	0.55	61.4	E *	0.72	52.7	D
	NB-L	1.05	169.1	F *	1.05	141.8	F *	0.72	104.7	F *	1.02	141.3	F *
	NB-T	0.69	12.2	B	0.68	13.8	B	0.84	5.1	A	0.63	12.8	B
	SB-T	1.05	40.6	D *	0.78	24.4	C	0.85	24.8	C	0.88	28.6	C
	(Service Rd) NB-T	0.37	8.5	A	0.31	9.5	A	0.32	8.0	A	0.23	8.8	A
(Service Rd) SB-T	0.32	12.7	B	0.28	15.8	B	0.15	11.7	B	0.24	15.3	B	
12th Avenue (N-S) @ West 56th Street (EB)	NB-T	0.98	52.9	D *	0.69	11.3	B	0.95	14.1	B *	0.65	10.8	B
	SB-L	0.82	34.4	C	0.97	77.6	E *	0.89	70.5	E *	0.61	47.4	D
	(Service Rd) NB-TR	0.50	30.9	C	0.21	6.6	A	0.24	3.4	A	0.14	6.1	A
12th Avenue (N-S) @ West 57th Street (E-W)	NB-T Main	0.69	26.9	C	0.75	16.4	B	0.89	10.1	B	0.71	15.3	B
	NB-T Service	0.41	22.1	C	0.20	9.3	A	0.14	3.1	A	0.13	8.6	A
	WB-R	0.25	30.3	C	0.43	37.2	D	0.53	50.6	D	0.49	38.1	D
	unsignalized (Service Rd) NB-R	0.77	21.4	C	0.54	15.9	C	0.59	17.0	C	0.50	15.1	C

This table has updated since the DEIS

NOTES:
 EB-Eastbound, WB-Westbound, NB-Northbound, SB-Southbound
 L-Left, T-Through, R-Right, DfL-Analysis considers a Defacto Left Lane on this approach.
 V/C Ratio - Volume to Capacity Ratio, SEC/VEH - Seconds per vehicle
 LOS - Level of service
 * -Denotes Congested Location
 Analysis is based on the 2000 Highway Capacity Manual Methodology (HCS 2000 +).

Along the Eleventh Avenue corridor, there are two intersections with congested movements in the weekday AM peak hour. The westbound movement at the intersection of Eleventh Avenue and W. 55th Street operates at minimally acceptable LOS D, but with a v/c ratio of 0.90. At Eleventh Avenue and W. 57th Street the eastbound through-right movement operates at LOS F, with 86.9 seconds of delay, and a v/c ratio of 1.05 and the eastbound left movement operates at LOS F, with 80.5 seconds of delay, and a v/c ratio of 0.97. The westbound through-right movement operates at LOS E, with 73.5 seconds of delay and a v/c ratio of 0.99.

During the weekday midday peak hour, there are four intersections with congested movements, all on eastbound or westbound cross-street approaches. At the intersection of Eleventh Avenue and W. 52nd Street, the eastbound movement operates at LOS E, with 72.3 seconds of delay and v/c ratio of 0.98. At the intersection of Eleventh Avenue and W. 53rd Street, the westbound movement operates at LOS E, 69.2 seconds of delay and a v/c ratio of 0.94. The westbound movement at Eleventh Avenue and W. 55th Street is congested, operating at LOS F, with 91.9 seconds of delay and a v/c ratio of 1.05. At the intersection of Eleventh Avenue and W. 57th Street, the westbound left movement operates at LOS E, with 63.0 seconds of delay and a v/c ratio of 0.92, and the westbound through-right movement operates at LOS E, with 65.6 seconds of delay and a v/c ratio of 0.96 seconds of delay.

During the weekday PM peak hour, there is one intersection with congested movements. At Eleventh Avenue and W. 57th Street, the eastbound through-right movement operates at LOS E, with 60.6 seconds of delay and a v/c ratio of 0.91 and the westbound through-right movement operates at LOS F with 86.8 seconds of delay and a v/c ratio of 1.05.

During the Saturday midday peak hour, there are three intersections with congested movements. At Eleventh Avenue and W. 53rd Street, the westbound left-right movement operates at LOS F, with 90.1 seconds of delay, and a v/c ratio of 1.02. At Eleventh Avenue and W. 55th Street, the westbound movement operates at LOS E, with 80.0 seconds of delay, and a v/c ratio of 1.05. At Eleventh Avenue and W. 57th Street, the westbound through-right movement operates at LOS E, with 61.3 seconds of delay, and a v/c ratio of 0.94.

Twelfth Avenue

During the weekday AM peak hour, there are four intersections with congested movements in the Twelfth Avenue corridor. The southbound left turn movement at Twelfth Avenue and W. 54th Street operates at LOS E, with 59.4 seconds of delay. However it operates with a v/c ratio of 0.51 which reflects the limited green time provided to this movement's protected phase during the signal cycle. Also at this intersection, the westbound right movement operates at LOS E, with 60.0 seconds of delay, but with a v/c ratio of 0.48. Conversely, the southbound through movement on the main roadway operates at a minimally acceptable LOS D, but with a v/c ratio of 1.05 reflecting heavy volumes. At Twelfth Avenue and W. 52nd Street, the southbound left turn movement operates at LOS F, with 131.1 seconds of delay and a v/c ratio of 1.05 and the southbound through movement operates at LOS C but with a v/c ratio of 1.01. Also at this intersection the northbound through-right movement also operates at LOS C but with a v/c ratio of 0.93. At Twelfth Avenue and W. 55th Street, the westbound right movement operates at LOS E, with 56.6 seconds of delay but with a v/c ratio of 0.39, the westbound left turn movement operates at LOS F, with 119.9 seconds of delay and

a v/c ratio of 1.05 the northbound left turn movement also operates at LOS F, with a 169.1 seconds of delay, and a v/c ratio of 1.05, and the southbound through movement operates at minimally acceptable LOS D but with a v/c ratio of 1.05.

During the weekday midday peak hour, there are three intersections with congested movements. At Twelfth Avenue and W. 52nd Street, the southbound left turn operates at LOS F, with 132.9 seconds of delay and a v/c ratio of 1.05, and the northbound through-right movement operates at LOS E, with 58.7 seconds of delay and a v/c ratio of 1.05. At Twelfth Avenue and W. 56th Street, the southbound left turn operates at LOS E, with 77.6 seconds of delay, with a 0.97 v/c ratio. At Twelfth Avenue and W. 55th Street, the northbound left operates at LOS F, with 141.8 seconds of delay and with a 1.05 v/c ratio.

During the weekday PM peak hour, four of the five analyzed study area intersections in this corridor has two or more congested movements. At Twelfth Avenue and W. 52nd Street, the southbound left turn operates at LOS F, with 142.2 seconds of delay, and a v/c ratio of 1.05, and the northbound through-right movement operates at minimally acceptable LOS D, but with a v/c ratio of 1.05. At Twelfth Avenue and W. 54th Street, the westbound right turn movement operates at LOS E, with 67.4 seconds of delay, but with a v/c ratio of 0.62, the northbound through-right movement operates at LOS A but with a v/c ratio of 0.93, and the southbound left operates at LOS E, with 57.6 seconds of delay but with a 0.42 v/c ratio. At Twelfth Avenue and W. 55th Street, the westbound left turn movement operates at LOS E, with 61.7 seconds of delay, but with a v/c ratio of 0.60, the westbound right movement operates at LOS E, with 61.4 seconds of delay, but with a v/c ratio of 0.55, and the northbound left movement operates at LOS F with 104.7 seconds of delay and a v/c ratio of 0.72. At Twelfth Avenue and W. 56th Street, the southbound left turn movement operates at LOS E, with 70.5 seconds of delay, and a 0.89 v/c ratio, and the northbound through movement operates at LOS B, but with a v/c ratio of 0.95.

During the Saturday midday peak hour, there are two intersections with congested movements. At Twelfth Avenue and W. 52nd Street, the southbound left turn operates at LOS F with 138.4 seconds of delay, and the v/c ratio is 1.05 and the northbound through-right movement operates at LOS C but with a v/c ratio of 0.90. At Twelfth Avenue and W. 55th Street, the northbound left turn operates at LOS F, with 141.3 seconds and with a v/c ratio of 1.02 and the westbound left turn movement operates at LOS F, with 87.1 seconds of delay, and a v/c ratio of 0.99.

Parking

The proposed project would have a 225-space accessory garage on the project site. However, the project's forecasted peak parking demand is expected to exceed the accessory supply. Therefore off-street public parking facilities within approximately a quarter-mile of the site were assessed for their capacities and approximate utilization during the weekday AM, weekday Midday, weekday PM, overnight, and Saturday Midday peak periods, based on field surveys in October and November 2007 with later confirmation surveys in September 2008. Figure 13-6 shows the locations of these facilities and Table 13-2 shows their capacity and estimated utilization levels for 2008 Existing conditions.

The *CEQR Technical Manual* states that a quarter-mile walk is generally considered the maximum distance from primary off-site parking facilities to the project site, although if a quarter-mile area should prove insufficient to accommodate the peak parking demand consideration should be given to extending a parking study area to a half-mile radius of the project site.

Table 13-2 shows that there are 15 off-street public parking facilities with a total of 2,844 spaces within a quarter-mile of the project site. During the overnight and weekend periods, one of these facilities is closed; as a result during those periods there are 14 public off-street parking facilities with a capacity of 2,766 spaces. Overall, utilization of these facilities was found to be approximately 90 percent, 76 percent, 80 percent, 41 percent, and 45 percent, in the weekday AM, weekday midday, weekday PM, overnight, and Saturday midday periods, respectively. As shown in the table, utilization peaks in the morning and remains moderately high during the day, before declining late at night and on weekends.

Curbside parking regulations in the vicinity of the site typically restrict parking on the avenues in the AM and/ or PM peak periods while the cross-streets have a wide variety of regulations ranging from alternate side parking to bus staging regulations. These include the south side of W. 54th Street east of Eleventh Avenue, the NYCT M31 bus ends its route on this street and lays over adjacent to the project site. Based on field observations, utilization of on-street parking supply in the study area generally is high throughout the day. Prior to the initiation of the ongoing excavation of the project site, parking regulations in the vicinity of the project site were a mix of 1-hour and 2-hour metered parking along Tenth and Eleventh Avenues with some peak period no parking regulations, and no parking 8 AM to 6 PM, Monday through Saturday, along cross-streets. On-site parking regulations within a quarter-mile radius of the project site are presented in Figure 13-7.

On-street parking is presently not permitted along the curbs bordering the project site due to ongoing excavation on the project site. Prior to this construction there were approximately 7, 21, and 12 legal auto parking spaces adjacent to the project site on Eleventh Avenue, W. 53rd Street, and W. 54th Street, respectively. However, it should be noted that private buses were often observed parking along W. 53rd and W. 54th streets and thereby reducing the functional capacity.

C. FUTURE WITHOUT THE PROPOSED PROJECT

Between 2008 and 2011, it is expected that the transportation demands in the study area will increase due to development projects in the area as well as background growth. In order to forecast those future demands without the proposed project (the No Build condition), major development projects (along with any required mitigation) listed in Chapter 2, "Land Use, Zoning and Public Policy", were considered in addition to an annual background growth rate of 0.5 percent per year (2008 to 2011) applied to Existing conditions. This background growth rate, recommended in the *CEQR Technical Manual*, for projects in Manhattan, is applied to account for smaller projects and general increases in travel demand not attributable to specific development projects identified in Chapter 2. The project site is assumed to remain unoccupied. The analysis also incorporates traffic operations improvements associated with the Piers 92-94 Redevelopment Project, as outlined in the *Manhattan Piers 92 and 94 Redevelopment Environmental Assessment Statement* (CEQR No. 09SBS002M, February 2009).

Table 13-2, 2008 Existing Off-street Public Parking Inventory and Utilization

Map #	Name & Address	License No.	License Capacity	Utilization Rate			Demand			Available Spaces					
				AM	MD	PM	LATE	SAT	AM	MD	PM	LATE	SAT		
1	MTP Operating Corp.(1) 514-540 W. 49th St.	1013511	125	60%	50%	40%	40%	20%	75	63	50	50	62	75	100
2	Primary Parking LLC 721-735 10th Av.	780839	181	75%	90%	80%	50%	40%	136	163	145	91	45	18	109
3	Rex Parking Corp. 532 W. 53rd St.	429832	78	80%	80%	50%	closed	closed	62	62	39	closed	16	16	closed
4	Worthy Pakring 841 10th Ave. (W. 55th St.)	1148650	86	90%	90%	75%	50%	50%	77	77	65	43	9	9	43
5	411 W. 55th Corp. 411 W. 55th St.	427688	188	80%	85%	70%	60%	50%	150	160	132	113	38	28	56
6	Apex Parking, LLC 440 W. 57th St.	368300	378	85%	85%	85%	60%	60%	321	321	321	227	57	57	151
7	57 & 11 Parking Corp. (GMC) 622 W. 57th St.	429031	1,000	100%	60%	100%	35%	50%	1,000	600	1,000	350	0	400	500
8	Effective Parking LLC 435 W. 57th St.	368157	55	75%	80%	70%	40%	20%	41	44	39	22	14	11	33
9	Kinney Systems 838-852 11th Av. & 543-5 W. 57th St.	1137953	84	85%	80%	75%	35%	30%	71	67	63	29	13	17	55
10	56 - 57 Holding Corp. 408 W. 57th St.	1113944	80	80%	100%	75%	50%	20%	64	80	60	40	16	0	64
11	K Park Group LLC 680 12th Av.	1186413	170	100%	90%	60%	10%	10%	170	153	102	17	0	17	153
12	50-51 Operating Corp. 622-630 W. 51st St.	1189161	181	100%	85%	50%	10%	50%	181	154	91	18	0	27	90
13	815 Tenth Parking LLC 815 10th Av. (W. 54th St.)	1179523	48	100%	100%	85%	60%	50%	48	48	41	29	0	0	7
14	Hudson View Parking LLC 747 10th Av. (W. 51st St.)	769937	107	85%	85%	70%	50%	50%	91	91	75	54	16	16	32
15	Clinton 53 Parking LLC 515 W. 52nd St.	1263170	83	85%	85%	70%	50%	40%	71	71	58	42	12	12	41
TOTAL		2,844	2,844	90%	76%	80%	41%	45%	2,558	2,154	2,281	1,125	286	690	1,641

Notes on time periods - AM: 8 to 9 AM; MD: 12 noon to 1 PM; PM 5 to 6 PM; LATE: overnight; SAT: peak Saturday demand.

Source: PHA surveys October and November 2007, and October 2008; also AKRF surveys June 2007, April and May 2008

(1) MTP Operating Corp. garage has a licensed capacity of 240, however this garage only operates with approximately 125 spaces. (see 534 W. 49th St. EAS, 2007 (CEQR #07DCP043M))

In addition to the effects of major developments listed in Chapter 2, the analysis also considered the effects on study area traffic flows of traffic generated by development and traffic mitigation associated with the W. 61st Street rezoning which was adopted by the City in 2007. (This development is located outside the land use study area but would have effects on traffic conditions in the traffic study area.)

Vehicular Traffic

Traffic forecasts were made for each of the four peak hours analyzed, and Figures 13-8 through 13-11 show the anticipated weekday AM, midday, PM, and Saturday midday peak hour traffic volumes in the study area for the 2011 future without the proposed project. Capacity analyses were then prepared for each intersection. Table 13-3 shows the result of these analyses. The table shows that under 2011 No-Build conditions, 13 of the 16 intersections will experience congestion in one or more of the peak hours, as compared to 9 under existing 2008 conditions. There will be 9, 7, 9, and 5 intersections experiencing congestion on one or more approaches in the weekday AM, midday, PM, and Saturday midday peak hours, respectively. By comparison, during these peak hours there are 6, 7, 5, and 6 intersections with congested movements under existing conditions. While under existing conditions there are 4, 3, 2, and 5 intersections with a movement having a v/c ratio of more than 1.0 in the weekday AM, midday, PM, and Saturday midday peak hours, respectively, under 2011 No-Build conditions there will be 3, 4, 3, and 4 such intersections in the respective peak hours.

Among the intersections that will experience congestion or further deterioration of already congested conditions, there are several of particular concern given the expected distribution of project generated demand. At Eleventh Avenue and W. 51st Street in the AM peak hour, the southbound movement will deteriorate from LOS C, with a v/c ratio of 0.84 under existing conditions to a v/c ratio of 0.90 under No-Build while remaining at LOS C. At Tenth Avenue and W. 52nd Street in the weekday AM peak hour, the eastbound movement will deteriorate from LOS D and a v/c ratio of 0.86 under existing conditions to LOS D with 53.1 seconds of delay, with a v/c ratio of 0.93 on the through movement (the eastbound left movement will remain at acceptable operating conditions).

At Tenth Avenue and W. 53rd Street in the PM peak hour, the westbound movement will deteriorate from LOS D, with a v/c ratio of 0.81, to LOS E with a v/c ratio of 0.96. At Tenth Avenue and W. 55th Street, the westbound through-right movement will become congested in two peak hours and further deteriorate in a third. In the AM peak it will deteriorate from LOS D, with a v/c ratio of 0.88 to LOS E with a v/c ratio of 0.94, in the PM peak hour it will deteriorate from LOS D with a v/c ratio of 0.86 to LOS E with a v/c ratio of 0.93, and in the Saturday midday peak hour it will deteriorate from LOS E with a v/c ratio of 1.05 to LOS F with a v/c ratio of 1.06.

At Twelfth Avenue and W. 57th Street in the PM peak hour, the northbound through movement on the main roadway will become congested, deteriorating from LOS B with a v/c ratio of 0.89 to a v/c ratio of 0.93 while remaining at LOS B.

Signalized Intersection	Lane Group	2008 Existing AM Peak Hour			2011 NoBuild AM Peak Hour			2008 Existing MD Peak Hour			2011 NoBuild MD Peak Hour		
		V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS
10th Avenue (NB) @ West 52nd Street (EB)	EB-L				0.46	27.1	C						
	EB-T				0.93	53.1	D *						
	EB-LT	0.86	42.8	D				0.66	31.5	C	0.89	46.2	D
	NB-TR	0.60	9.8	A	0.63	10.2	B	0.71	11.5	B	0.76	13.2	B
10th Avenue (NB) @ West 53rd Street (WB)	WB-TR	0.75	37.5	D	0.82	42.8	D	0.65	32.4	C	0.74	36.7	D
	NB-LT	0.59	9.7	A	0.66	10.5	B	0.69	11.1	B	0.75	12.2	B
10th Avenue (NB) @ West 54th Street (EB)	EB-LT	0.71	34.6	C	0.85	44.1	D	0.48	27.1	C	0.58	29.6	C
	NB-TR	0.59	9.7	A	0.69	10.9	B	0.70	11.3	B	0.77	12.6	B
10th Avenue (NB) @ West 55th Street (WB)	WB-TR	0.88	48.8	D	0.94	56.5	E *	0.73	35.6	D	0.80	39.8	D
	NB-LT	0.58	9.6	A	0.65	11.0	B	0.66	10.7	B	0.71	11.4	B
10th Avenue (NB) @ West 57th Street (E-W)	EB-LT	0.73	26.8	C	0.82	31.0	C	0.56	24.3	C	0.66	27.0	C
	WB-TR	0.55	21.5	C	0.61	22.2	C	0.80	30.9	C	0.85	34.5	C
	NB-LTR	0.68	16.7	B	0.75	18.8	B						
	NB-LT							0.56	12.9	B	0.59	13.3	B
	NB-R							0.38	16.1	B	0.43	16.9	B
11th Avenue (N-S) @ West 51st Street (WB)	WB-L	0.21	19.3	B	0.21	19.3	B	0.39	32.5	C	0.39	32.6	C
	WB-TR	0.27	19.9	B	0.28	20.0	C	0.65	39.7	D	0.68	40.8	D
	NB-L	0.16	14.7	B	0.19	15.9	B	0.08	6.6	A	0.08	6.7	A
	NB-T	0.47	15.8	B	0.52	16.6	B	0.15	6.5	A	0.18	6.7	A
	SB-TR	0.84	21.3	C	0.90	25.7	C *	0.56	10.3	B	0.60	10.8	B
11th Avenue (N-S) @ West 52nd Street (EB)	EB-LT				0.82	34.7	C				0.99	71.7	E *
	EB-R				0.09	17.1	B				0.19	26.1	C
	EB-LTR	0.64	26.8	C				0.98	72.3	E *			
	NB-TR	0.51	16.5	B	0.58	18.3	B	0.21	6.8	A	0.25	8.4	A
	SB-L	0.45	17.1	B	0.65	28.4	C	0.13	6.8	A	0.18	8.6	A
11th Avenue (N-S) @ West 53rd Street (WB)	WB-LR	0.59	29.5	C	0.72	34.3	C	0.94	69.2	E *	1.06	100.2	F *
	NB-T	0.46	13.5	B	0.51	14.1	B	0.21	6.9	A	0.23	7.0	A
	SB-T	0.70	13.2	B	0.74	14.3	B	0.45	8.8	A	0.47	9.1	A
11th Avenue (N-S) @ West 54th Street (EB)	EB-LTR	0.66	31.7	C	0.79	38.8	D	0.57	36.6	D	0.69	41.6	D
	NB-L	0.40	17.7	B	0.46	20.4	C	0.13	7.0	A	0.14	7.2	A
	NB-TR	0.52	14.4	B	0.57	15.3	B	0.27	7.3	A	0.30	7.5	A
	SB-L	0.31	11.0	B	0.36	12.6	B	0.14	6.9	A	0.16	7.2	A
	SB-T	0.62	11.5	B	0.66	12.2	B						
	SB-R	0.04	9.6	A	0.04	9.6	A						
	SB-TR							0.45	8.9	A	0.48	9.2	A
11th Avenue (N-S) @ West 55th Street (WB)	WB-LT				0.95	59.0	E *						
	WB-R				0.11	20.6	C						
	WB-LTR	0.90	49.9	D *				1.05	91.9	F *	1.15	123.1	F *
	NB-L	0.73	34.7	C	0.77	39.9	D	0.23	8.2	A	0.24	8.9	A
	NB-T	0.40	12.7	B	0.45	13.4	B	0.20	6.8	A	0.24	7.4	A
	SB-TR	0.45	9.2	A	0.48	9.5	A						
	SB-R							0.37	8.1	A	0.41	8.8	A
11th Avenue (N-S) @ West 57th Street (E-W)	EB-L	0.97	80.5	F *	0.85	54.0	D	0.51	25.6	C	0.41	19.7	B
	EB-TR	1.05	86.9	F *	0.56	28.5	C	0.72	39.5	D	0.41	26.6	C
	WB-L	0.83	49.0	D	0.66	28.9	C	0.92	63.0	E *	0.83	44.4	D
	WB-TR	0.99	73.5	E *	0.68	32.4	C	0.96	65.6	E *	0.60	30.0	C
	NB-L	0.09	15.5	B	0.19	17.7	B	0.15	16.2	B	0.26	19.1	B
	NB-TR	0.57	20.5	C	0.63	21.9	C	0.38	17.7	B	0.43	19.0	B
	SB-L	0.64	29.7	C	0.75	40.0	D	0.29	18.4	B	0.37	20.9	C
	SB-TR	0.70	20.3	C	0.74	21.5	C	0.48	19.1	B	0.55	20.8	C
12th Avenue (N-S) @ West 52nd Street (EB)	EB-LTR	--	--	--	0.99	94.2	F	--	--	--	0.65	45.8	D
	NB-TR	0.93	34.9	C *	0.98	41.5	D *	1.05	58.7	E *	1.09	73.0	E *
	SB-L	1.05	131.1	F *	0.87	95.6	F *	1.05	132.9	F *	0.82	84.2	F *
	SB-T	1.01	21.4	C *	0.98	13.0	B *	0.66	12.8	B	0.62	12.2	B
12th Avenue (N-S) @ West 54th Street (E-W)	WB-R	0.48	60.0	E *	0.50	60.8	E *	0.26	39.1	D	0.27	39.1	D
	NB-TR	0.80	15.1	B	0.92	21.6	C *	0.82	17.0	B	0.92	21.8	C *
	SB-L	0.51	59.4	E *	0.52	59.7	E *	0.37	40.8	D	0.38	41.0	D
	SB-T	1.05	37.2	D *	1.07	46.2	D *	0.63	12.3	B	0.65	12.7	B
	(Service Rd) SB-T	0.54	3.7	A	0.14	1.5	A	0.30	9.0	A	0.06	7.0	A
12th Avenue (N-S) @ West 55th Street (WB)	WB-L	1.05	119.9	F *	0.89	86.4	F *	0.62	48.1	D	0.53	44.8	D
	WB-LR				0.75	77.6	E *				0.64	51.0	D
	WB-R	0.39	56.6	E *	0.36	60.1	E *	0.59	46.7	D	0.57	50.3	D
	WB(1)					80.6	F					48.4	D
	NB-L	1.05	169.1	F *	1.09	169.9	F *	1.05	141.8	F *	0.99	118.4	F *
	NB-T	0.69	12.2	B	0.74	12.3	B	0.68	13.8	B	0.72	14.6	B
	SB-T	1.05	40.6	D *	1.07	47.6	D *	0.78	24.4	C	0.83	27.4	C
	(Service Rd) NB-T	0.37	8.5	A	0.50	9.5	A	0.31	9.5	A	0.40	10.6	B
	(Service Rd) SB-T	0.32	12.7	B	0.36	13.2	B	0.28	15.8	B	0.32	17.3	B
12th Avenue (N-S) @ West 56th Street (EB)	NB-T	0.98	52.9	D *	1.02	61.9	E *	0.69	11.3	B	0.72	12.0	B
	SB-L	0.82	34.4	C	0.91	43.4	D *	0.97	77.6	E *	1.04	96.9	F *
	(Service Rd) NB-TR	0.50	30.9	C	0.65	33.8	C	0.21	6.6	A	0.26	7.0	A
12th Avenue (N-S) @ West 57th Street (E-W)	NB-T Main	0.69	26.9	C	0.72	27.9	C	0.75	16.4	B	0.79	17.4	B
	NB-T Service	0.41	22.1	C	0.58	26.1	C	0.20	9.3	A	0.27	9.9	A
	WB-R	0.25	30.3	C	0.30	31.2	C	0.43	37.2	D	0.53	39.0	D
unsignalized (Service Rd) NB-R	0.77	21.4	C	0.86	28.8	D	0.54	15.9	C	0.63	18.3	C	

This table has updated since the DEIS

NOTES:

EB-Eastbound, WB-Westbound, NB-Northbound, SB-Southbound
L-Left, T-Through, R-Right, DFL-Analysis considers a Defacto Left Lane on this approach.
V/C Ratio - Volume to Capacity Ratio, SEC/VEH - Seconds per vehicle
LOS - Level of service

* -Denotes Congested Location
(1) -Total approach delay (provided due to changes in lane configuration)
Analysis is based on the 2000 Highway Capacity Manual Methodology (HCS 2000 + Version 5.3).

Table 13-3b, 2011 No-Build Traffic Conditions

Signalized Intersection	Lane Group	2008 Existing PM Peak Hour			2011 NoBuild PM Peak Hour			2008 Existing SMD Peak Hour			2011 NoBuild SMD Peak Hour		
		V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS
10th Avenue (NB) @ West 52nd Street (EB)	EB-LT NB-TR	0.62	30.2	C	0.88	45.5	D	0.53	27.6	C	0.76	36.0	D
		0.50	8.6	A	0.52	8.8	A	0.68	10.9	B	0.70	11.2	B
10th Avenue (NB) @ West 53rd Street (WB)	WB-TR NB-LT	0.81	42.0	D	0.96	62.4	E *	0.67	33.0	C	0.82	41.8	D
		0.47	8.4	A	0.51	8.8	A	0.64	10.4	B	0.69	11.1	B
10th Avenue (NB) @ West 54th Street (EB)	EB-LT NB-TR	0.47	26.9	C	0.56	29.0	C	0.27	23.4	C	0.34	24.5	C
		0.49	8.6	A	0.54	9.0	A	0.66	10.6	B	0.71	11.4	B
10th Avenue (NB) @ West 55th Street (WB)	WB-TR NB-LT	0.86	45.4	D	0.93	55.9	E *	1.05	79.6	E *	1.06	80.4	F *
		0.49	8.5	A	0.51	8.8	A	0.62	10.1	B	0.66	11.3	B
10th Avenue (NB) @ West 57th Street (E-W)	EB-LT WB-TR NB-LTR NB-LT NB-R	0.43	21.7	C	0.49	21.3	C	0.44	22.2	C	0.52	23.8	C
		0.64	25.6	C	0.67	24.8	C	0.68	26.7	C	0.73	28.1	C
		0.56	12.6	B	0.60	14.6	B	0.53	12.5	B	0.54	12.7	B
		0.24	13.9	B	0.30	15.8	B	0.28	14.3	B	0.32	14.9	B
11th Avenue (N-S) @ West 51st Street (WB)	WB-L WB-TR NB-L NB-T SB-TR	0.36	31.9	C	0.37	32.0	C	0.42	33.3	C	0.43	33.5	C
		0.76	45.4	D	0.78	47.6	D	0.69	41.5	D	0.70	42.3	D
		0.08	3.3	A	0.09	3.5	A	0.07	6.4	A	0.07	6.5	A
		0.08	2.8	A	0.11	2.9	A	0.11	6.2	A	0.12	6.3	A
		0.54	10.0	A	0.59	10.7	B	0.52	9.7	A	0.55	10.1	B
11th Avenue (N-S) @ West 52nd Street (EB)	EB-LT EB-R EB-LTR NB-TR SB-L SB-T				0.75	40.3	D				0.75	42.9	D
					0.14	25.4	C				0.28	30.1	C
		0.70	40.4	D				0.71	40.8	D			
		0.13	3.0	A	0.17	4.4	A	0.17	6.6	A	0.19	6.7	A
		0.18	7.2	A	0.25	9.3	A	0.13	6.8	A	0.18	7.2	A
11th Avenue (N-S) @ West 53rd Street (WB)	WB-LR NB-T SB-T	0.83	53.5	D	0.98	78.1	E *	1.02	90.1	F *	1.17	138.3	F *
		0.12	2.9	A	0.15	3.0	A	0.15	6.5	A	0.16	6.5	A
		0.50	9.4	A	0.54	9.9	A	0.44	8.8	A	0.47	9.0	A
11th Avenue (N-S) @ West 54th Street (EB)	EB-LTR NB-L NB-TR SB-L SB-T SB-R SB-TR	0.52	34.9	C	0.64	39.0	D	0.30	29.9	C	0.41	31.9	C
		0.37	7.1	A	0.41	8.3	A	0.34	10.3	B	0.37	10.9	B
		0.16	3.1	A	0.19	3.2	A	0.22	6.9	A	0.24	7.0	A
		0.13	6.7	A	0.15	6.9	A	0.07	6.2	A	0.07	6.3	A
		0.51	9.5	A	0.55	10.0	B	0.46	9.0	A	0.48	9.2	A
11th Avenue (N-S) @ West 55th Street (WB)	WB-LTR NB-L NB-T SB-TR SB-T SB-R	0.57	32.5	C	0.63	33.9	C	1.05	80.0	E *	1.06	83.1	F *
		0.15	3.8	A	0.15	3.9	A	0.19	7.7	A	0.20	8.2	A
		0.11	2.9	A	0.15	3.0	A	0.17	6.6	A	0.20	7.2	A
		0.41	8.4	A	0.45	8.8	A	0.33	7.6	A	0.35	8.2	A
		0.14	6.6	A	0.19	7.0	A	0.16	6.7	A	0.19	7.4	A
11th Avenue (N-S) @ West 57th Street (E-W)	EB-L EB-TR WB-L WB-TR NB-L NB-TR SB-L SB-TR	0.58	30.4	C	0.46	22.2	C	0.37	21.4	C	0.30	18.1	B
		0.91	60.6	E *	0.48	28.0	C	0.62	34.5	C	0.35	25.8	C
		0.62	26.6	C	0.56	23.2	C	0.89	54.1	D	0.86	48.0	D
		1.05	86.8	F *	0.64	30.8	C	0.94	61.3	E *	0.55	29.0	C
		0.22	15.2	B	0.34	18.8	B	0.28	18.6	B	0.32	19.6	B
		0.33	14.5	B	0.38	15.0	B	0.37	17.6	B	0.39	17.9	B
		0.44	21.5	C	0.54	24.5	C	0.27	17.9	B	0.31	18.6	B
		0.55	20.2	C	0.64	22.1	C	0.47	19.0	B	0.50	19.4	B
12th Avenue (N-S) @ West 52nd Street (EB)	EB-LTR NB-TR SB-L SB-T	--	--	--	0.86	77.0	E	--	--	--	0.55	43.0	D
		1.05	46.9	D *	1.09	62.4	E *	0.90	29.4	C *	0.93	31.7	C *
		1.05	142.2	F *	0.78	88.5	F *	1.05	138.4	F *	0.80	86.6	F *
		0.74	12.0	B	0.71	11.2	B	0.79	15.8	B	0.76	15.0	B
12th Avenue (N-S) @ West 54th Street (E-W)	WB-R NB-TR SB-L SB-T (Service Rd) SB-T	0.62	67.4	E *	0.63	68.2	E *	0.48	44.7	D	0.49	45.0	D
		0.93	8.4	A *	1.01	21.1	C *	0.69	13.4	B	0.76	14.9	B
		0.42	57.6	E *	0.43	57.8	E *	0.20	37.4	D	0.21	37.6	D
		0.72	12.4	B	0.75	13.1	B	0.77	15.1	B	0.79	15.7	B
		0.28	7.3	A	0.04	5.5	A	0.27	8.7	A	0.03	6.9	A
12th Avenue (N-S) @ West 55th Street (WB)	WB-L WB-LR WB-R WB(1) NB-L NB-T SB-T (Service Rd) (Service Rd) NB-T SB-T	0.60	61.7	E *	0.63	63.4	E *	0.99	87.1	F *	0.74	53.1	D
					0.60	66.8	E				0.80	61.2	E *
		0.55	61.4	E *	0.47	62.8	E *	0.72	52.7	D	0.68	54.7	D
						64.4	E					56.4	E
		0.72	104.7	F *	0.76	100.7	F *	1.02	141.3	F *	1.01	130.2	F *
		0.84	5.1	A	0.87	6.0	A	0.63	12.8	B	0.66	13.2	B
		0.85	24.8	C	0.89	29.3	C	0.88	28.6	C	0.93	33.6	C *
		0.32	8.0	A	0.40	2.7	A	0.23	8.8	A	0.33	9.8	A
0.15	11.7	B	0.18	13.2	B	0.24	15.3	B	0.28	16.8	B		
12th Avenue (N-S) @ West 56th Street (EB)	NB-T SB-L (Service Rd) NB-TR	0.95	14.1	B *	0.99	20.3	C *	0.65	10.8	B	0.68	11.2	B
		0.89	70.5	E *	0.95	80.4	F *	0.61	47.4	D	0.64	48.2	D
		0.24	3.4	A	0.29	3.7	A	0.14	6.1	A	0.18	6.4	A
12th Avenue (N-S) @ West 57th Street (E-W)	NB-T Main NB-T Service WB-R unsignalized (Service Rd) NB-R	0.89	10.1	B	0.93	11.8	B *	0.71	15.3	B	0.74	15.9	B
		0.14	3.1	A	0.21	3.4	A	0.13	8.6	A	0.15	8.8	A
		0.53	50.6	D	0.64	53.4	D	0.49	38.1	D	0.54	39.0	D
		0.59	17.0	C	0.66	19.5	C	0.50	15.1	C	0.59	17.2	C

This table has updated since the DEIS

NOTES:

- EB-Eastbound, WB-Westbound, NB-Northbound, SB-Southbound
- L-Left, T-Through, R-Right, DFL-Analysis considers a Defacto Left Lane on this approach .
- V/C Ratio - Volume to Capacity Ratio, SEC/VEH - Seconds per vehicle
- LOS - Level of service
- * - Denotes Congested Location
- (1) -Total approach delay (provided due to changes in lane configuration)

Parking

Changes in Parking Supply

In the future without the proposed action by 2011, there would be some changes to the supply of off-street public parking facilities. Two existing public parking facilities are expected to be replaced by No-Build developments. The 125-space MTP Operating Corp. garage at 514-540 W. 49th Street (no. 1 in Table 13-2) will be replaced by a new residential development (refer to Chapter 2, "Land Use, Zoning, and Public Policy," Table 2-4, No-Build development no. 11). This No-Build development will include 31 accessory spaces as well as 57 public parking spaces. As a result there would be a net decrease of 68 public parking spaces on that site. In addition, the 78-space Rex Parking Corp. public parking lot located across the street from the project site at 532 W. 53rd Street would be replaced by a new residential development (No-Build development no. 19 in Table 2-4) and is not expected to include any public parking spaces. In addition, an 81-space public parking facility at 455 W. 53rd Street, at which there formerly was a public parking garage until approximately 2007, is expected to open by 2010. It is assumed for analysis purposes that this would be a 24-hour, 7 day a week facility as a portion of the spaces will be reserved for monthly parkers.

With these changes in public parking supply, in the future without the proposed action in 2011 the total number of public parking spaces in the study area will decrease from 2,844 to 2,779.

Several of the expected No-Build developments will include accessory parking spaces. These spaces are not included in the No-Build parking inventory as public parking may not be permitted at these facilities and furthermore many of these facilities are expected to be at full utilization as they are not expected to accommodate the peak parking demand generated by the developments to which they are accessory.

Changes in Parking Demand

Demand for public parking is expected to increase in the study area. There are several new No-Build developments which are expected to result in new parking demand that either will provide no on-site parking or will provide on-site parking which is not sufficient to accommodate expected peak parking demand. In addition, due to general trends, existing parking demand is expected to increase as reflected by applying a background growth rate of 0.5 percent per year to existing demand levels. These increased demands for public parking in the future without the proposed action are reflected in Table 13-4.

Parking Utilization

With the changes to public parking supply and demand, utilization of study area public parking is expected to increase in the future without the proposed action. As shown in Table 13-4, utilization is expected to increase in the analyzed peak periods, rising from 90 percent to 104 percent in the weekday AM, from 76 percent to 89 percent in the weekday midday, from 80 percent to 96 percent in the weekday PM, from 41 percent to 54 percent in the overnight, and from 45 percent to 55 percent in the Saturday midday. As noted, demand will be highest in the AM peak period, with demand exceeding supply by approximately 123 spaces, while in the other periods analyzed the

number of available spaces will range from 113 in the weekday PM period to 1,265 in the overnight period.

Table 13-4, 2011 No-Build Public Off-Street Parking Conditions

		2008 Existing Conditions	Change	2011 No-Build Conditions
A M	Capacity	2,844	<u>-65</u>	<u>2,779</u>
	Public Parking Demand	2,558	344	2,902
	Available Spaces	286	-	<u>-123</u>
	Utilization	90%	-	<u>104%</u>
M D	Capacity	2,844	<u>-65</u>	<u>2,779</u>
	Public Parking Demand	2,154	313	2,467
	Available Spaces	690	-	<u>312</u>
	Utilization	76%	-	<u>89%</u>
P M	Capacity	2,844	<u>-65</u>	<u>2,779</u>
	Public Parking Demand	2,281	385	2,666
	Available Spaces	563	-	<u>113</u>
	Utilization	80%	-	<u>96%</u>
L A T E	Capacity	2,766	<u>13</u>	<u>2,779</u>
	Public Parking Demand	1,125	389	1,514
	Available Spaces	1641	-	<u>1,265</u>
	Utilization	41%	-	<u>54%</u>
S A T M D	Capacity	2,766	<u>13</u>	<u>2,779</u>
	Public Parking Demand	1,232	295	1,527
	Available Spaces	1,534	-	<u>1,252</u>
	Utilization	45%	-	<u>55%</u>

D. FUTURE WITH THE PROPOSED ACTION

The proposed project includes several components that would generate travel demand, including 900 DUs, 8,800 gsf of local retail, 20,000 gsf of public health club space, 330,000 gsf of automobile sales, preparation, and repairs space, and 36,000 gsf of NYPD Mounted Unit facility, including stable and related space. In addition, the development would have up to 225 accessory parking spaces to serve site-generated parking demand. As shown on the proposed project's site plan (Figure

1-5, in Chapter 1, “Project Description,” the project would have several curb cuts along W. 53rd Street and W. 54th Street for ramps and loading docks. These would include a driveway for the accessory garage on W. 53rd Street, a driveway/loading area for the NYPD stable also on W. 53rd Street, driveways for the auto dealership on W. 53rd and W. 54th Streets, and a commercial loading dock on W. 53rd Street. There would be no curb cuts on Eleventh Avenue. For pedestrian access, there would be residential lobby entrances accessible from both W. 53rd and W. 54th Street and access points for the commercial uses spread across the site’s three frontages.

Table 13-5 shows the transportation planning assumptions used to estimate the weekday and Saturday demand for each of the project components. The table shows the overall daily generation rates, hourly peaking patterns, mode choice and vehicle occupancy. The planning assumptions in Table 13-5 are based on accepted travel demand criteria, many used for other West Side developments, as well as census (journey-to-work and reverse journey-to-work) and empirical data collected for this project (e.g., NYPD Stable).

Table 13-6 shows the peak hour person-trip and vehicle-trip forecasts for each component of the proposed project for the four analyzed peak hours. As the project site is assumed to remain vacant under No-Build conditions for analysis purposes, there is no credit for removing previous uses or uses that could be developed as-of-right in future without the proposed action. As shown in the table, the proposed project would generate an estimated 221, 174 220, and 182 vehicle trips (in and out combined) in the weekday AM, weekday midday, weekday PM, and Saturday midday peak hours, respectively. Peak hour transit and pedestrian trips are discussed in Chapter 14, “Transit and Pedestrians.” As the above travel demand demonstrates, the proposed project would have its heaviest demand in the weekday PM peak hour due to the heavier residential and health club demand in that period.

Project-generated vehicle trips would consist of those made by auto, taxi and truck. Origin and destination patterns for project-generated vehicular trips were developed based on local traffic patterns and the location of major employment centers. Based on their origins or destinations, project-generated vehicle trips were then assigned to study area portals and to study area intersections based on logical routes of travel. Auto trips were assigned to either the project site, or for vehicles which could not be accommodated on-site, to nearby off-street public parking garages expected to have available capacity. This includes some facilities located outside the traffic study area as the number of public parking facilities and availability of space close to the site are limited. Taxi trips were assigned to one of the site’s three block faces.

Vehicular Traffic

Figures 13-12 through 13-15 show the incremental vehicular traffic (autos, taxis and trucks) generated by the proposed project during the weekday AM, weekday midday, weekday PM, and Saturday midday peak hours. Figures 13-16 through 13-19 show the Build condition traffic in the study area during these peak hours, which is a combination of the incremental project traffic and the traffic volumes in the future without the project. Peak hour traffic volumes would experience increases along the primary access and egress routes for the project site.

**TABLE 13-5
TRANSPORTATION PLANNING ASSUMPTIONS**

Land Use:	Uses Generated by the Proposed Action									
	Residential		Health Club		Retail		Auto Dealership		NYPD Mounted Unit	
Size/Units:	900 DUs		20,000 gsf		8,800 gsf		330,000 gsf		36,000 gsf	
Trip Generation:	(1)		(2)		(1)		(3)		(4)	
	WKDY	8.075	44.7	205.0	2.63	7.44				
	SAT	8.075	29.5	205.0	2.63	7.44				
	per DU		per 1,000 sf							
Temporal Distribution:	(1)		(2)		(1)		(3)		(4)	
WKDY AM	9.1%		4.8%		3.1%		12.0%		15.0%	
WKDY MD	4.7%		5.6%		19.0%		12.0%		3.0%	
WKDY PM	10.7%		13.2%		9.6%		9.0%		16.0%	
SAT MD	7.0%		9.8%		9.5%		12.0%		2.0%	
Modal Splits:	(5)		(6)		(7)		(3)		(4)	
	<u>AM/MD/PM</u>		<u>AM/MD/PM</u>		<u>AM/MD/PM</u>		<u>AM/MD/PM</u>		<u>AM/PM</u>	
Auto	9.0%		35.0%		2.0%		100.0%		38.0%	
Taxi	6.0%		3.0%		3.0%		0.0%		0.0%	
Subway	31.0%		41.0%		6.0%		0.0%		0.0%	
Bus	20.0%		12.0%		6.0%		0.0%		0.0%	
Walk	34.0%		9.0%		83.0%		0.0%		5.0%	
Other	0.0%		0.0%		0.0%		0.0%		57.0%	
	100.0%		100.0%		100.0%		100.0%		100.0%	
In/Out Splits:	(1)		(2)		(7)		(3)		(4)	
	<u>In</u>	<u>Out</u>	<u>In</u>	<u>Out</u>	<u>In</u>	<u>Out</u>	<u>In</u>	<u>Out</u>	<u>In</u>	<u>Out</u>
WKDY AM	15%	85%	41%	59%	50%	50%	67%	33%	80%	20%
WKDY MD	50%	50%	54%	46%	50%	50%	50%	50%	35%	65%
WKDY PM	70%	30%	75%	25%	50%	50%	15%	85%	5%	95%
SAT MD	50%	50%	54%	46%	50%	50%	50%	50%	20%	80%
Vehicle Occupancy:	(5),(2)		(2)		(7)		(3)		(4)	
Auto	1.26		1.40		1.6		1.3		1.0	
Taxi	1.40		1.40		1.2		1.5		1.0	
Truck Trip Generation:	(8)		(2)		(7)		(3)		(4)	
WKDY	0.064		0.19		0.35		0.15		0.15	
SAT	0.004		0.01		0.018		0.15		0.15	
	per DU		per 1,000 sf							
	(8)		(2)		(7)		(3)		(4)	
WKDY AM	6.0%		6.0%		7.7%		9.6%		6.0%	
WKDY MD	11.0%		11.0%		11.0%		11.0%		11.0%	
WKDY PM	1.0%		1.0%		1.0%		1.0%		1.0%	
SAT MD	7.9%		7.6%		11.0%		11.0%		11.0%	
	(8)		(2)		(7)		(3)		(4)	
	<u>In</u>	<u>Out</u>	<u>In</u>	<u>Out</u>	<u>In</u>	<u>Out</u>	<u>In</u>	<u>Out</u>	<u>In</u>	<u>Out</u>
AM/MD/PM	50%	50%	50%	50%	50%	50%	50%	50%	50%	50%

Sources:

- (1) Pushkarev & Zupan, *Urban Space for Pedestrians* (1975).
- (2) Coliseum Redevelopment FEIS (1997)
- (3) W. 57th Street Rezoning FEIS (2001)
- (4) Daily trip rate, temporal distribution, and directional split are derived from driveway count conducted by PHA at existing NYPD Stable facility on Hudson River Pier 76. Other trips walking or by horse. The calculated number of vehicle trips in Table 13-6 match the vehicle count data at the existing facility.
- (5) 2000 Census for NY County tract 135, Journey to Work data (adjusted to exclude "worked at home")
- (6) 2000 Census for NY County tract 135, Reverse Journey to Work data (adjusted to exclude "worked at home")
- (7) Hudson Yards FGEIS (2004)
- (8) Clinton Green Mixed Use Development EAS (2004)

Note: Gross floor area numbers are approximate.

**TABLE 13-6
TRANSPORTATION PLANNING CALCULATIONS**

Land Use:	<i>Uses Generated by the Proposed Action</i>										Subtotal, Build Scenario		
	Residential		Health Club		Retail		Auto Dealership		NYPD Mounted Unit				
Size/Units:	900 DUs		20,000 gsf		8,800 gsf		330,000 gsf		18,000 gsf				
Peak Hour Trips:													
WKDAY AM	661		43		56		104		40		905		
WKDY MD	342		50		343		104		8		847		
WKDY PM	778		118		173		78		43		1,190		
SAT MD	509		58		171		104		5		847		
Person Trips:													
	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	Total
W AM Auto	9	51	6	9	1	1	70	34	12	3	98	97	195
Taxi	6	34	1	1	1	1	0	0	0	0	7	35	43
Subway	31	174	7	10	2	2	0	0	0	0	40	186	226
Bus	20	112	2	3	2	2	0	0	0	0	24	117	141
Walk	34	191	2	2	23	23	0	0	2	0	60	217	277
Other	0	0	0	0	0	0	0	0	18	5	18	5	23
Total	99	562	18	25	28	28	70	34	32	8	247	658	905
	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	Total
W MD Auto	15	15	9	8	3	3	52	52	1	2	81	81	162
Taxi	10	10	1	1	5	5	0	0	0	0	16	16	32
Subway	53	53	11	9	10	10	0	0	0	0	74	73	147
Bus	34	34	3	3	10	10	0	0	0	0	48	47	95
Walk	58	58	2	2	142	142	0	0	0	0	203	203	406
Other	0	0	0	0	0	0	0	0	2	3	2	3	5
Total	171	171	27	23	171	171	52	52	3	5	424	422	847
	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	Total
W PM Auto	49	21	31	10	2	2	12	66	1	15	94	115	209
Taxi	33	14	3	1	3	3	0	0	0	0	38	17	55
Subway	169	72	36	12	5	5	0	0	0	0	210	90	300
Bus	109	47	11	4	5	5	0	0	0	0	125	55	180
Walk	185	79	8	3	72	72	0	0	0	2	265	156	421
Other	0	0	0	0	0	0	0	0	1	23	1	23	24
Total	544	233	89	30	87	87	12	66	2	41	733	456	1,190
	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	Total
S MD Auto	23	23	11	9	2	2	52	52	0	2	88	88	176
Taxi	15	15	1	1	3	3	0	0	0	0	19	19	37
Subway	79	79	13	11	5	5	0	0	0	0	97	95	192
Bus	51	51	4	3	5	5	0	0	0	0	60	59	119
Walk	86	86	3	2	71	71	0	0	0	0	160	160	321
Other	0	0	0	0	0	0	0	0	1	2	1	2	3
Total	254	254	31	27	86	86	52	52	1	4	424	423	847
Vehicle Trips :													
	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	Total
W AM Auto (Total)	7	40	4	6	0	0	54	26	12	3	78	76	154
Taxi	4	24	0	1	1	1	0	0	0	0	5	25	31
Taxi (Bal.)											28	28	56
Truck	2	2	0	0	0	0	2	2	0	0	4	4	8
TOTAL											112	109	221
	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	Total
W MD Auto (Total)	12	12	7	6	2	2	40	40	1	2	62	62	124
Taxi	7	7	1	0	4	4	0	0	0	0	12	12	24
Taxi (Bal.)											18	18	36
Truck	4	4	0	0	0	0	3	3	0	0	7	7	14
TOTAL											87	87	174
	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	Total
W PM Auto (Total)	39	17	22	7	1	1	9	51	1	15	72	92	164
Taxi	23	10	2	1	2	2	0	0	0	0	27	13	40
Taxi (Bal.)											27	27	54
Truck	1	1	0	0	0	0	0	0	0	0	1	1	2
TOTAL											100	120	220
	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	Total
S MD Auto (Total)	18	18	8	7	1	1	40	40	0	2	68	68	135
Taxi	11	11	1	1	2	2	0	0	0	0	14	14	27
Taxi (Bal.)											20	20	40
Truck	0	0	0	0	0	0	3	3	0	0	3	3	6
TOTAL											91	91	182

Capacity and level of service analyses were performed for the study area intersections using the future Build peak hour traffic volumes. Table 13-7 compares the 2011 No-Build and Build operating conditions for these intersections.

Based on the thresholds established for signalized intersections in the *CEQR Technical Manual*, if a No-Build LOS of A, B, or C deteriorates to an unacceptable LOS D, E, or F under Build conditions, then a significant impact is deemed to have occurred. The *CEQR Technical Manual* further states that for a No-Build LOS A, B, or C that operates at LOS D under Build conditions, mitigation to mid-LOS D is required. Therefore, any such Build LOS change with a delay of 45 seconds (mid-LOS D) or less, is not considered an impact for the purposes of this analysis. For a No-Build LOS D, an increase of Build delay by 5 or more seconds is considered a significant impact. For a No-Build LOS E, the threshold is a 4-second increase in Build delay, and for a No-Build LOS F, a 3-second increase in Build delay is considered significant. However, if a No-Build LOS F condition has a delay in excess of 120 seconds, an increase in Build delay of more than 1 second is considered significant, unless the proposed action would generate fewer than five vehicles through that lane group in the peak hour.

Table 13-7 identifies, with an asterisk and shading (*) the impacted intersections in the four analyzed peak hours, based on the above criteria. As shown in the table, there would be 4, 3, 3, and 2 intersections with one or more impacted movements in the weekday AM, weekday midday, weekday PM, and Saturday midday peak hours, respectively. The following provides a discussion of the key impacted locations in the study area.

Tenth Avenue Corridor:

There are three intersections in this corridor which would have impacted locations in this corridor, all on cross-street movements.

The westbound movement at W. 53rd Street would be impacted in the weekday AM and PM peak hours. In the AM peak hour it would deteriorate by 5.5 seconds of delay, from 42.8 seconds (LOS D) to 48.3 seconds (LOS D). In the PM peak hour it would deteriorate by 8.1 seconds of delay, from 62.4 seconds (LOS E) to 70.5 seconds (LOS E). The eastbound movement at W. 54th Street would be impacted in the weekday AM. It would deteriorate by 7.5 seconds of delay, from 44.1 seconds (LOS D) to 51.6 seconds (LOS D).

The eastbound movement at W. 52nd Street would be impacted in the weekday midday and PM peak hours. In the midday it would deteriorate by 7.4 seconds of delay from 46.2 (LOS D) seconds to 53.6 seconds (LOS D). In the PM it would deteriorate by 10.3 seconds from 45.5 seconds (LOS D) to 54.8 (LOS D).

Eleventh Avenue Corridor:

There are three intersections in this corridor which would have impacted locations in this corridor, one on a northbound left turn and the others on cross-street movements.

Table 13-7a, 2011 Build Traffic Conditions

Signalized Intersection	Lane Group	2011 No-Build AM Peak Hour			2011 Build AM Peak Hour			2011 No-Build MD Peak Hour			2011 Build MD Peak Hour								
		V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS						
10th Avenue (NB) @ West 52nd Street (EB)	EB-L	0.46	27.1	C	0.50	28.2	C	0.89	46.2	D	0.94	53.6	D						
	EB-T	0.93	53.1	D	0.94	56.3	E												
	EB-LR	0.63	10.2	B	0.64	10.2	B							0.76	13.2	B	0.77	13.3	B
	NB-TR																		
10th Avenue (NB) @ West 53rd Street (WB)	WB-TR	0.82	42.8	D	0.87	48.3	D	0.74	36.7	D	0.79	39.8	D						
	NB-LT	0.66	10.5	B	0.68	10.8	B	0.75	12.2	B	0.77	12.5	B						
10th Avenue (NB) @ West 54th Street (EB)	EB-LT	0.85	44.1	D	0.91	51.6	D	0.58	29.6	C	0.63	31.4	C						
	NB-TR	0.69	10.9	B	0.69	10.9	B	0.77	12.6	B	0.77	12.6	B						
10th Avenue (NB) @ West 55th Street (WB)	WB-TR	0.94	56.5	E	0.94	56.5	E	0.80	39.8	D	0.80	39.9	D						
	NB-LT	0.65	11.0	B	0.67	11.3	B	0.71	11.4	B	0.73	11.7	B						
10th Avenue (NB) @ West 57th Street (E-W)	EB-LT	0.82	31.0	C	0.83	31.4	C	0.66	27.0	C	0.67	27.2	C						
	WB-TR	0.61	22.2	C	0.62	22.4	C	0.85	34.5	C	0.86	34.9	C						
	NB-LTR	0.75	18.8	B	0.76	19.2	B	0.59	13.3	B	0.60	13.4	B						
	NB-LT																		
	NB-R	0.43	16.9	B	0.44	17.2	B												
SB-TR	0.21	19.3	B	0.21	19.3	B	0.39	32.6	C	0.39	32.6	C							
11th Avenue (N-S) @ West 51st Street (WB)	WB-TR	0.28	20.0	C	0.28	20.1	C	0.68	40.8	D	0.68	41.1	D						
	NB-L	0.19	15.9	B	0.21	16.8	B	0.08	6.7	A	0.09	6.8	A						
	NB-T	0.52	16.6	B	0.52	16.7	B	0.18	6.7	A	0.18	6.7	A						
	SB-TR	0.90	25.7	C	0.94	30.2	C	0.60	10.8	B	0.62	11.3	B						
	EB-LR	0.82	34.7	C	0.83	35.9	D	0.99	71.7	E	1.01	77.2	E						
11th Avenue (N-S) @ West 52nd Street (EB)	EB-R	0.09	17.1	B	0.09	17.1	B	0.19	26.1	C	0.19	26.1	C						
	NB-TR	0.58	18.3	B	0.59	18.4	B	0.25	8.4	A	0.25	8.4	A						
	SB-L	0.65	28.4	C	0.73	34.8	C	0.18	8.6	A	0.22	9.0	A						
	SB-T	0.87	24.3	C	0.91	27.3	C	0.58	12.0	B	0.60	12.4	B						
	WB-LR	0.72	34.3	C	0.87	46.7	D	1.06	100.2	F	1.25	170.4	F						
11th Avenue (N-S) @ West 53rd Street (WB)	NB-T	0.51	14.1	B	0.51	14.2	B	0.23	7.0	A	0.24	7.0	A						
	SB-T	0.74	14.3	B	0.75	14.5	B	0.47	9.1	A	0.48	9.2	A						
	EB-LTR	0.79	38.8	D	0.83	42.2	D	0.69	41.6	D	0.72	43.4	D						
	NB-L	0.46	20.4	C	0.52	23.1	C	0.14	7.2	A	0.16	7.5	A						
	NB-TR	0.57	15.3	B	0.60	15.8	B	0.30	7.5	A	0.31	7.6	A						
11th Avenue (N-S) @ West 54th Street (EB)	SB-L	0.36	12.6	B	0.43	14.5	B	0.16	7.2	A	0.19	7.5	A						
	SB-T	0.66	12.2	B	0.66	12.3	B	0.48	9.2	A	0.48	9.2	A						
	SB-R	0.04	9.6	A	0.04	9.6	A												
	WB-LT	0.95	59.0	E	0.95	59.0	E												
	WB-R	0.11	20.6	C	0.11	20.6	C												
WB-LTR	0.77	39.9	D	0.81	45.4	D													
11th Avenue (N-S) @ West 55th Street (WB)	NB-L	0.45	13.4	B	0.46	13.5	B	1.15	123.1	F	1.15	124.0	F						
	SB-TR	0.48	9.5	A	0.49	9.6	A	0.24	8.9	A	0.26	9.2	A						
	SB-T	0.41	8.8	A	0.41	8.8	A	0.24	7.4	A	0.24	7.5	A						
	SB-R																		
	EB-L	0.85	54.0	D	0.85	54.0	D	0.41	19.7	B	0.41	19.7	B						
EB-TR	0.56	28.5	C	0.56	28.5	C	0.41	26.6	C	0.41	26.6	C							
11th Avenue (N-S) @ West 57th Street (E-W)	WB-L	0.66	28.9	C	0.69	30.8	C	0.83	44.4	D	0.85	47.4	D						
	WB-TR	0.68	32.4	C	0.68	32.4	C	0.60	30.0	C	0.60	30.0	C						
	NB-L	0.19	17.7	B	0.19	17.8	B	0.26	19.1	B	0.26	19.2	B						
	NB-TR	0.63	21.9	C	0.64	22.1	C	0.43	19.0	B	0.44	19.1	B						
	SB-L	0.75	40.0	D	0.76	41.5	D	0.37	20.9	C	0.38	21.1	C						
	SB-TR	0.74	21.5	C	0.75	21.8	C	0.55	20.8	C	0.55	20.9	C						
	EB-LTR	0.99	94.2	F	0.99	94.2	F	0.65	45.8	D	0.65	45.8	D						
	NB-TR	0.98	41.5	D	0.99	43.2	D	1.09	73.0	E	1.09	75.4	E						
	SB-L	0.87	95.6	F	0.88	98.0	F	0.82	84.2	F	0.85	87.1	F						
	SB-T	0.98	13.0	B	0.98	13.0	B	0.62	12.2	B	0.62	12.2	B						
12th Avenue (N-S) @ West 54th Street (E-W)	WB-R	0.50	60.8	E	0.53	62.3	E	0.27	39.1	D	0.28	39.5	D						
	NB-TR	0.92	21.6	C	0.93	22.1	C	0.92	21.8	C	0.92	22.1	C						
	SB-L	0.52	59.7	E	0.56	61.2	E	0.38	41.0	D	0.40	41.3	D						
	SB-T	1.07	46.2	D	1.07	46.5	D	0.65	12.7	B	0.65	12.7	B						
	(Service Rd) SB-T	0.14	1.5	A	0.14	1.5	A	0.06	7.0	A	0.06	7.0	A						
12th Avenue (N-S) @ West 55th Street (WB)	WB-L	0.89	86.4	F	0.89	86.4	F	0.53	44.8	D	0.53	44.8	D						
	WB-LR	0.75	77.6	E	0.77	78.8	E	0.64	51.0	D	0.64	51.4	D						
	WB-R	0.36	60.1	E	0.37	60.6	E	0.57	50.3	D	0.58	50.7	D						
	WB(1)	80.6	F	81.0	F	48.4	D	48.6	D										
	NB-L	1.09	169.9	F	1.09	169.9	F	0.99	118.4	F	0.99	118.4	F						
	NB-T	0.74	12.3	B	0.74	12.3	B	0.72	14.6	B	0.72	14.7	B						
	SB-T	1.07	47.6	D	1.07	48.8	D	0.83	27.4	C	0.83	27.5	C						
	NB-T	0.50	9.5	A	0.50	9.5	A	0.40	10.6	B	0.40	10.6	B						
	(Service Rd) SB-T	0.36	13.2	B	0.36	13.2	B	0.32	17.3	B	0.32	17.3	B						
	(Service Rd) SB-T	0.36	13.2	B	0.36	13.2	B	0.32	17.3	B	0.32	17.3	B						
12th Avenue (N-S) @ West 56th Street (EB)	NB-T	1.02	61.9	E	1.02	63.2	E	0.72	12.0	B	0.72	12.1	B						
	SB-L	0.91	43.4	D	0.91	43.4	D	1.04	96.9	F	1.04	97.4	F						
	(Service Rd) NB-TR	0.65	33.8	C	0.65	33.8	C	0.26	7.0	A	0.26	7.0	A						
12th Avenue (N-S) @ West 57th Street (E-W)	NB-T Main	0.72	27.9	C	0.73	28.0	C	0.79	17.4	B	0.79	17.4	B						
	NB-T Service	0.58	26.1	C	0.58	26.1	C	0.27	9.9	A	0.27	9.9	A						
	WB-R	0.30	31.2	C	0.30	31.2	C	0.53	39.0	D	0.53	39.1	D						
unsignalized (Service Rd)	NB-R	0.86	28.8	D	0.86	28.8	D	0.63	18.3	C	0.63	18.3	C						

This table has updated since the DEIS

NOTES:
 EB-Eastbound, WB-Westbound, NB-Northbound, SB-Southbound
 L-Left, T-Through, R-Right, DLT-Analysis considers a Defacto Left Lane on this approach .
 V/C Ratio - Volume to Capacity Ratio, SEC/VEH - Seconds per vehicle
 LOS - Level of service
 * -Denotes Impacted Location
 (1) -Total approach delay (provided due to changes in lane configuration)
 Analysis is based on the 2000 Highway Capacity Manual Methodology (HCS 2000 +).

Table 13-7b, 2011 Build Traffic Conditions

Signalized Intersection	Lane Group	2011 No-Build PM Peak Hour			2011 Build PM Peak Hour			2011 No-Build SMD Peak Hour			2011 Build SMD Peak Hour		
		V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS	V/C Ratio	Delay (sec/veh)	LOS
10th Avenue (NB) @ West 52nd Street (EB)	EB-LT	0.88	45.5	D	0.94	54.8	D	0.76	36.0	D	0.81	39.3	D
	NB-TR	0.52	8.8	A	0.52	8.8	A	0.70	11.2	B	0.71	11.3	B
10th Avenue (NB) @ West 53rd Street (WB)	WB-TR	0.96	62.4	E	0.99	70.5	E	0.82	41.8	D	0.86	46.0	D
	NB-LT	0.51	8.8	A	0.52	8.9	A	0.69	11.1	B	0.71	11.4	B
10th Avenue (NB) @ West 54th Street (EB)	EB-LT	0.56	29.0	C	0.63	31.2	C	0.34	24.5	C	0.40	25.4	C
	NB-TR	0.54	9.0	A	0.54	9.0	A	0.71	11.4	B	0.71	11.4	B
10th Avenue (NB) @ West 55th Street (WB)	WB-TR	0.93	55.9	E	0.94	57.0	E	1.06	80.4	F	1.06	80.4	F
	NB-LT	0.51	8.8	A	0.53	8.9	A	0.66	11.3	B	0.68	11.6	B
10th Avenue (NB) @ West 57th Street (E-W)	EB-LT	0.49	21.3	C	0.49	21.3	C	0.52	23.8	C	0.53	23.8	C
	WB-LTR	0.67	24.8	C	0.67	24.9	C	0.73	28.1	C	0.73	28.3	C
	NB-LTR	0.60	14.6	B	0.61	14.8	B	0.54	12.7	B	0.55	12.8	B
	NB-R	0.30	15.8	B	0.31	16.0	B	0.32	14.9	B	0.33	15.0	B
11th Avenue (N-S) @ West 51st Street (WB)	WB-L	0.37	32.0	C	0.37	32.0	C	0.43	33.5	C	0.43	33.5	C
	WB-TR	0.78	47.6	D	0.79	48.0	D	0.70	42.3	D	0.70	42.5	D
	NB-L	0.09	3.5	A	0.09	3.6	A	0.07	6.5	A	0.08	6.6	A
	NB-T	0.11	2.9	A	0.11	2.9	A	0.12	6.3	A	0.13	6.3	A
	SB-TR	0.59	10.7	B	0.62	11.3	B	0.55	10.1	B	0.58	10.5	B
11th Avenue (N-S) @ West 52nd Street (EB)	EB-LT	0.75	40.3	D	0.80	43.2	D	0.75	42.9	D	0.78	45.2	D
	EB-R	0.14	25.4	C	0.14	25.4	C	0.28	30.1	C	0.28	30.1	C
	NB-TR	0.17	4.4	A	0.18	4.4	A	0.19	6.7	A	0.19	6.8	A
	SB-L	0.25	9.3	A	0.28	9.6	A	0.18	7.2	A	0.20	7.5	A
	SB-T	0.58	12.0	B	0.61	12.5	B	0.49	9.4	A	0.52	9.6	A
11th Avenue (N-S) @ West 53rd Street (WB)	WB-LR	0.98	78.1	E	1.24	166.9	F	1.17	138.3	F	1.37	217.6	F
	NB-T	0.15	3.0	A	0.15	3.0	A	0.16	6.5	A	0.16	6.6	A
	SB-T	0.54	9.9	A	0.54	10.0	A	0.47	9.0	A	0.47	9.1	A
11th Avenue (N-S) @ West 54th Street (EB)	EB-LTR	0.64	39.0	D	0.65	39.5	D	0.41	31.9	C	0.44	32.7	C
	NB-L	0.41	8.3	A	0.46	9.6	A	0.37	10.9	B	0.40	11.6	B
	NB-TR	0.19	3.2	A	0.21	3.3	A	0.24	7.0	A	0.25	7.2	A
	SB-L	0.15	6.9	A	0.16	7.1	A	0.07	6.3	A	0.09	6.4	A
	SB-TR	0.55	10.0	B	0.55	10.1	B	0.48	9.2	A	0.49	9.3	A
11th Avenue (N-S) @ West 55th Street (WB)	WB-LTR	0.63	33.9	C	0.63	33.9	C	1.06	83.1	F	1.06	83.5	F
	NB-L	0.15	3.9	A	0.17	4.2	A	0.20	8.2	A	0.21	8.4	A
	NB-T	0.15	3.0	A	0.15	3.1	A	0.20	7.2	A	0.20	7.2	A
	SB-T	0.45	8.8	A	0.46	8.9	A	0.35	8.2	A	0.36	8.3	A
	SB-R	0.19	7.0	A	0.19	7.0	A	0.19	7.4	A	0.19	7.4	A
11th Avenue (N-S) @ West 57th Street (E-W)	EB-L	0.46	22.2	C	0.46	22.2	C	0.30	18.1	B	0.30	18.1	B
	EB-TR	0.48	28.0	C	0.48	28.0	C	0.35	25.8	C	0.35	25.8	C
	WB-L	0.56	23.2	C	0.58	27.0	C	0.86	48.0	D	0.88	50.8	D
	WB-TR	0.64	30.8	C	0.64	30.8	C	0.55	29.0	C	0.55	29.0	C
	NB-L	0.34	18.8	B	0.35	19.2	B	0.32	19.6	B	0.32	19.7	B
	NB-TR	0.38	15.0	B	0.39	15.2	B	0.39	17.9	B	0.40	18.0	B
	SB-L	0.54	24.5	C	0.55	24.9	C	0.31	18.6	B	0.31	18.7	B
	SB-TR	0.64	22.1	C	0.65	22.3	C	0.50	19.4	B	0.51	19.5	B
	SB-T	0.64	22.1	C	0.65	22.3	C	0.50	19.4	B	0.51	19.5	B
12th Avenue (N-S) @ West 52nd Street (EB)	EB-LTR	0.86	77.0	E	0.86	77.0	E	0.55	43.0	D	0.55	43.1	D
	NB-TR	1.09	62.4	E	1.10	65.0	E	0.93	31.7	C	0.94	32.5	C
	SB-L	0.78	88.5	F	0.80	91.1	F	0.80	86.6	F	0.84	90.9	F
	SB-T	0.71	11.2	B	0.71	11.3	B	0.76	15.0	B	0.76	15.0	B
	SB-T	0.71	11.2	B	0.71	11.3	B	0.76	15.0	B	0.76	15.0	B
12th Avenue (N-S) @ West 54th Street (E-W)	WB-R	0.63	68.2	E	0.68	71.4	E	0.49	45.0	D	0.51	45.7	D
	NB-TR	1.01	21.1	C	1.01	21.4	C	0.76	14.9	B	0.76	15.0	B
	SB-L	0.43	57.8	E	0.45	58.3	E	0.21	37.6	D	0.23	37.9	D
	SB-T	0.75	13.1	B	0.75	13.1	B	0.79	15.7	B	0.79	15.7	B
	(Service Rd) SB-T	0.04	5.5	A	0.04	5.5	A	0.03	6.9	A	0.03	6.9	A
	WB-L	0.63	63.4	E	0.63	63.4	E	0.74	53.1	D	0.74	53.1	D
	WB-LR	0.60	66.8	E	0.62	67.6	E	0.80	61.2	E	0.81	62.1	E
	WB-R	0.47	62.8	E	0.49	63.6	E	0.68	54.7	D	0.69	55.4	E
	WB(1)	0.64	64.4	E	0.64	64.8	E	0.56	56.4	E	0.56	56.9	E
NB-L	0.76	100.7	F	0.76	100.7	F	1.01	130.2	F	1.01	130.2	F	
NB-T	0.87	6.0	A	0.88	6.1	A	0.66	13.2	B	0.66	13.3	B	
SB-T	0.89	29.3	C	0.90	29.6	C	0.93	33.6	C	0.93	34.0	C	
(Service Rd) NB-T	0.40	2.7	A	0.40	2.7	A	0.33	9.8	A	0.33	9.8	A	
(Service Rd) SB-T	0.18	13.2	B	0.18	13.2	B	0.28	16.8	B	0.28	16.8	B	
12th Avenue (N-S) @ West 56th Street (EB)	NB-T	0.99	20.3	C	1.00	21.3	C	0.68	11.2	B	0.68	11.2	B
	SB-L	0.95	80.4	F	0.95	80.4	F	0.64	48.2	D	0.64	48.2	D
(Service Rd) NB-TR	0.29	3.7	A	0.29	3.7	A	0.18	6.4	A	0.18	6.4	A	
12th Avenue (N-S) @ West 57th Street (E-W)	NB-T Main	0.93	11.8	B	0.93	12.0	B	0.74	15.9	B	0.74	16.0	B
	NB-T Service	0.21	3.4	A	0.21	3.4	A	0.15	8.8	A	0.15	8.8	A
	WB-R	0.64	53.4	D	0.64	53.4	D	0.54	39.0	D	0.54	39.1	D
unsignalized (Service Rd) NB-R	0.66	19.5	C	0.66	19.5	C	0.59	17.2	C	0.59	17.2	C	

This table has updated since the DEIS

NOTES:
 EB-Eastbound, WB-Westbound, NB-Northbound, SB-Southbound
 L-Left, T-Through, R-Right, D/L-Analysis considers a Defacto Left Lane on this approach .
 V/C Ratio - Volume to Capacity Ratio, SEC/VEH - Seconds per vehicle
 LOS - Level of service
 * - Denotes Impacted Location
 Analysis is based on the 2000 Highway Capacity Manual Methodology (HCS 2000 +).

At W. 52nd Street, the eastbound movement at this intersection would be impacted in the weekday midday peak hour. It would deteriorate by 6.5 seconds of delay from 71.7 seconds (LOS E) to 77.2 seconds (LOS E).

At W. 53rd Street, the westbound movement would be impacted in all four peak hours. In the weekday AM peak hour it would deteriorate by 12.4 seconds of delay, from 34.3 seconds (LOS C) to 46.7 seconds (LOS D). In the weekday midday peak hour it would deteriorate by 70.2 seconds of delay, from 100.2 seconds (LOS F) to 170.4 seconds (LOS F). In the weekday PM peak hour, it would deteriorate by 88.8 seconds of delay, from 78.1 seconds (LOS E) to 166.9 seconds (LOS F) and in the Saturday midday peak hour it would deteriorate by 89.3 seconds of delay, from 138.3 seconds (LOS F) to 217.6 seconds (LOS F).

At W. 55th Street, the northbound left movement would be impacted in the AM peak hour. It would deteriorate by 5.5 seconds of delay, from 39.9 seconds (LOS D) to 45.4 seconds (LOS D).

Twelfth Avenue Corridor:

There would be one impacted intersections in the Twelfth Avenue corridor.

At West 52nd Street, the southbound left would be impacted in the Saturday midday peak hour. It would deteriorate by 4.3 seconds of delay from 86.6 seconds (LOS F) to 90.9 seconds (LOS F).

Overall, 7 of the 16 study area intersections would be impacted in one or more of the analyzed peak hours. Table 13-8 provides a summary of these impacted locations.

Mitigation measures for these impacts are presented in Chapter 19, "Mitigation."

Table 13-8, Summary of Impacted Intersections

IMPACTED INTERSECTION (1)	PEAK PERIOD: IMPACTED MOVEMENT			
	WKDY AM	WKDY MD	WKDY PM	SAT MD
10th Ave. & W. 52nd St.	==	EB-LT	EB-LT	--
10th Ave. & W. 53rd St.	<u>WB-TR</u>	--	WB-TR	==
10th Ave. & W. 54th St.	EB-LT	--	--	--
11th Ave. & W. 52nd St.	==	EB-LT	==	==
11th Ave. & W. 53rd St.	<u>WB-LR</u>	<u>WB-LR</u>	<u>WB-LR</u>	<u>WB-LR</u>
<u>11th Ave. & W. 55th St.</u>	<u>NB-L</u>	==	==	==
<u>12th Ave. & W. 52nd St.</u>	--	--	--	<u>SB-L</u>

(1) The following intersections would not be impacted in any of the analyzed peak hours: 10th Ave. & W. 55th St.; 10th Ave. & W. 57th St.; 11th Ave. & W. 51st St.; 11th Ave. & W. 54th St.; 11th Ave. & W. 57th St.; 12th Ave. & W. 54th St.; 12th Ave. & W. 55th St.; 12th Ave. & W. 56th St.; 12th Ave. & W. 57th St.

Traffic Safety

The annual number of pedestrians and bicyclists injured or killed in motor vehicle accidents from 2005 through 2007 at study area intersections is shown in Table 13-9. (The accident data do not distinguish injuries from fatalities.) Accidents resulting in injuries or fatalities to pedestrians or bicyclists often involve turning vehicles, with failure to yield the right-of-way to pedestrians in crosswalks frequently cited as a causal factor. The New York City Department of Transportation (NYCDOT) considers any intersection at which five or more pedestrians or cyclists are killed or injured per year as a high accident location. As shown in Table 1, three intersections experienced one or more years with 5 or more pedestrians or bicyclists killed or injured during the 2005 to 2007 study period.

Table 13-9, Annual Pedestrian and Bicycle Injuries/Fatalities at Study Area Intersections, 2005-2007

Intersection		Bicyclists Killed/Injured			Pedestrians Killed/Injured			Total, Pedestrians & Bicyclists Killed/Injured		
		2005	2006	2007	2005	2006	2007	2005	2006	2007
10th Ave. at	W. 52nd St.	0	0	1	0	1	0	0	1	1
	W. 53rd St.	1	0	1	1	0	0	2	0	1
	W. 54th St.	0	0	1	0	0	1	0	0	2
	W. 55th St.	0	0	0	1	4	2	1	4	2
	W. 56th St.	0	0	1	1	3	0	1	3	1
	W. 57th St.	2	2	0	9	3	6	11	5	6
11th Ave. at	W. 51st St.	0	0	0	1	0	3	1	0	3
	W. 52nd St.	1	0	0	1	0	0	2	0	0
	W. 53rd St.	1	0	1	0	0	0	1	0	1
	W. 54th St.	0	2	0	2	0	3	2	2	3
	W. 55th St.	0	1	0	0	0	1	0	1	1
	W. 56th St.	0	2	0	2	0	0	2	2	0
	W. 57th St.	0	2	1	5	0	0	5	2	1
12th Ave. at	W. 52nd St.	0	0	0	1	0	1	1	0	1
	W. 54th St.	0	2	4	1	0	2	1	2	6
	W. 55th St.	0	2	0	0	0	1	0	2	1
	W. 56th St.	0	0	0	3	0	0	3	0	0
	W. 57th St.	0	0	1	0	2	1	0	2	2

Source: NYCDOT data

These high accident location intersections include:

- * Tenth Avenue at W. 57th Street -- there were 2 bicyclists and 9 pedestrians injured or killed in 2005; 2 bicyclists and 3 pedestrians injured or killed in 2006; and 6 pedestrians injured or killed in 2007.
- * Eleventh Avenue at W. 57th Street -- there were 5 pedestrians injured or killed in 2005.
- * Twelfth Avenue at W. 54th Street -- there were 4 bicyclists and 2 pedestrians injured or killed in 2007.

According to the *CEQR Technical Manual*, pedestrian safety is especially of concern at sensitive land use locations, such as hospitals, schools, parks, nursing homes, and elderly housing, where there would be substantial child or elderly activities. The intersection of W. 54th Street and Twelfth Avenue is adjacent to De Witt Clinton Park and Hudson River Park and therefore may attract child and/or elderly populations. In addition, the intersection of W. 57th Street and Tenth Avenue is approximately one block from St. Luke's Roosevelt Hospital and therefore may be traversed by a higher than average number of children, elderly, or mobility impaired individuals.

The *Manual* further states that the key issue to be resolved in safety analyses is the extent to which vehicular and pedestrian exposure to accidents may reasonably be expected to increase with the proposed action in place. The proposed action will generate new vehicular, pedestrian, and bicycle trips through these intersections. However, as these intersections are not immediately adjacent to the site or parking or transit facilities that would be used by action-generated vehicle trips, the proposed action would not reasonably be expected to significantly increase the number of accidents at these locations.

Measures to improve pedestrian/bicyclist conditions at these intersections are as follows:

* *Tenth Avenue at W. 57th Street*

The intersection of Tenth Avenue and W. 57th Street was analyzed in detail for potential causal factors. Figure 13-20 shows the collision diagram for the 20 of the 22 pedestrian/bicycle accidents over the 2005 to July 2008 period. It is evident from the figure that three-quarters of the pedestrian/bicycle accidents at the intersection are along the western crosswalk. One half (10) of all the accidents are related to left-turning vehicles from northbound Tenth Avenue. This left-turning accident pattern is not totally atypical in Manhattan, however, the additional accidents at this crosswalk on the eastbound through movement indicates that some remedial action is warranted at this crosswalk which already has high visibility markings.

A review was made of the time and weather conditions of the accidents, however there were no discernible patterns. The following two countermeasures would help reduce accidents at this location:

- * Improved illumination on the crosswalk itself would enhance visibility after dark; and

* A leading pedestrian interval (LPI) of 7 seconds would introduce pedestrians into the crosswalk before the vehicles, also enhancing pedestrian priority and visibility. This could also include “Yield to Pedestrians” and “Wait for Green” signs.

These recommended countermeasures would be under the jurisdiction of NYCDOT to advance to implementation. During the post-FEIS design phase, the applicant will assist NYCDOT in providing a follow-up study and developing these and any additional countermeasures at this intersection. As demonstrated in Figures 13-12 to 13-19 (showing Build Increment and Build traffic volumes for the analyzed peak hours) the proposed action itself would increase traffic volumes by less than 1 percent at this intersection and as a result would not alter the number of accidents and would not result in a significant adverse impact.

* *Eleventh Avenue at W. 57th Street*

According to the NYCDOT data, at this intersection the number of traffic accidents has decreased, as compared to previously reported accident data, due to improvements implemented by NYCDOT.

* *Twelfth Avenue at W. 54th Street*

As discussed in the *Manhattan Piers 92 and 94 Redevelopment EAS*, under No-Build conditions at the Twelfth Avenue and W. 54th intersection, the Hudson River Park shared bicycle/pedestrian greenway would no longer traverse and thereby be exposed to traffic flows along the southbound service road. The greenway would be expanded maintained along the west side of the service road, only conflicting with traffic making a southbound right turn into the redeveloped Piers 92-94 trade show facility. There would no longer be any conflicts with high-speed service road through traffic headed up the ramp to the passenger ship terminal or taxis arriving at that site. Also, as part of the Piers 92-94 project (a No-Build development), a speed table would be constructed at the entrance to the piers to further enforce the greenway priority over the right-turning traffic. It is expected that most presently occurring conflicts would be reduced thereby improving traffic safety.

Parking

Parking Supply Changes

The proposed project would provide up to 225 accessory parking spaces for use by building residents, employees, and visitors. This represents the maximum number of accessory parking spaces permitted as-of-right under the proposed zoning. Also, the proposed automobile dealership would provide space for vehicle servicing and storage and therefore would accommodate vehicles traveling to the site for servicing. In addition, parking demand generated by the proposed NYPD Stable facility would be accommodated within that facility.

The proposed project would not provide any public parking spaces.

As noted in the existing conditions section, on-street parking space is limited in the vicinity of the project site and utilization is typically very high throughout the day. As discussed in Chapter 19, “Mitigation,” traffic mitigation for the proposed project includes daylighting of parking regulations at two approaches on two intersections during certain peak hours, at locations where “No Parking” would be changed to “No Standing.” This mitigation would not affect the supply of on-street

parking. However, with the creation of new curb cuts for the proposed development, the number of on-street parking spaces in the area would be reduced moderately.

Parking Demand Changes

Total parking demand generated by the proposed project's various components would exceed the 225-space accessory parking supply. Table 13-10 shows the expected parking demand and accumulation for a typical weekday, but excludes NYPD Stable parking demand (accommodated in the stable) and auto dealership service-related trips (which would be accommodated within the dealership's service areas). Therefore, the table shows the parking demand that would need to be accommodated either by the on-site accessory garage or by off-street public parking facilities in the surrounding area.

As shown in the table, parking demand generated by the proposed project would exceed the supply provided by the 225-space accessory garage, with total demand at 232, 253, 302, and 263, during the weekday AM, weekday midday, weekday PM, and overnight periods, respectively. In addition, a parking demand forecast for the Saturday midday period, based on the accumulation patterns used in Table 13-10 and the travel demand assumptions in Table 13-5, also found that parking demand would exceed the on-site capacity. Specifically, it is expected that the project's parking demand would be approximately 236 spaces during the Saturday midday period. The weekend overnight demand likely would be similar to the weekday overnight demand.

As a result, excess parking demand would have to be accommodated off-site. As on-street parking utilization is currently very high, to be conservative, the analysis assumes that all parking demand generated by the proposed project which cannot be accommodated on-site would have to be accommodated by the off-street public parking facilities in the surrounding area. Accordingly, an analysis was conducted to determine if the off-street public parking facilities within a quarter-mile radius of the project site could accommodate the public parking demand generated by the proposed project.

Table 13-11 shows the overall effect on the off-street public parking study area under the proposed project and compares it to the No-Build conditions. As shown in the table, with the proposed project utilization rates would increase. In the weekday AM peak period, which would experience a shortfall under No-Build conditions, the shortfall would increase by an additional 35 vehicles, a moderate increase in the shortfall from 123 to spaces to 158 spaces, an increase from 104 percent to 106 percent of capacity. In the other peak hours, a shortfall in supply would not occur. In the PM peak period, which is near capacity under No-Build conditions, the proposed action would increase demand by 76 vehicles, resulting in demand at a level close to capacity with only 37 available spaces. As a result, demand would increase from 96 percent to 99 percent of capacity. Utilization would increase from 89 percent to 90 percent in the weekday midday peak period, from 54 percent to 56 percent in the overnight period, and from 55 percent to 56 percent in the Saturday midday peak period.

Table 13-10, Parking Accumulation Calculations: Total Accessory and Off-site Public Parking Demand

	Residential (1)			Health Club (2)			Retail (Market) (3)			Auto Dealer (4)			Total Parking Demand (5)		
	In	Out	accum	In	Out	accum	In	Out	accum	In	Out	accum	In	Out	accum
12-1 AM	1	1	263	0	0	0	0	0	0	0	0	0	1	1	263
1-2	1	1	263	0	0	0	0	0	0	0	0	0	1	1	263
2-3	1	1	263	0	0	0	0	0	0	0	0	0	1	1	263
3-4	1	1	263	0	0	0	0	0	0	0	0	0	1	1	263
4-5	1	1	263	0	0	0	0	0	0	0	0	0	1	1	263
5-6	2	5	260	0	0	0	0	0	0	0	0	0	2	5	260
6-7	4	16	248	0	0	0	0	0	0	0	0	0	4	16	248
7-8	5	16	237	15	3	12	0	0	0	13	4	9	33	23	258
8-9	7	40	204	7	9	10	0	0	0	18	9	18	32	58	232
9-10	9	14	199	9	3	16	1	0	1	14	6	26	33	23	242
10-11	9	16	192	6	3	19	1	0	2	8	3	31	24	22	244
11-12	10	14	188	12	3	28	1	1	2	7	4	34	30	22	252
12-1 PM	12	12	188	10	9	29	2	2	2	13	13	34	37	36	253
1-2	13	13	188	6	6	29	1	1	2	7	7	34	27	27	253
2-3	14	13	189	6	6	29	1	1	2	9	7	36	30	27	256
3-4	20	12	197	6	6	29	1	1	2	7	4	39	34	23	267
4-5	25	17	205	9	6	32	1	1	2	8	14	33	43	38	272
5-6	39	17	227	33	11	54	1	1	2	3	17	19	76	46	302
6-7	28	14	241	21	15	60	1	1	2	3	15	7	53	45	310
7-8	27	14	254	12	24	48	0	1	1	1	5	3	40	44	306
8-9	20	12	262	9	30	27	0	0	1	0	0	3	29	42	293
9-10	3	5	260	6	21	12	1	0	2	0	0	3	10	26	277
10-11	3	3	260	1	12	1	0	2	0	0	0	3	4	17	264
11-12	4	1	263	0	1	0	0	0	0	0	0	3	4	2	266
24 hr total	259	259	518	168	168	336	12	12	24	111	108	219	550	547	1,097

Notes:

- (1) 2000 Census data from Census Tract 135 used for calculation of maximum residential vehicle demand. Accumulation pattern based on ABC West End Ave. Properties FEIS.
- (2) Accumulation pattern based on Coliseum Redevelopment FEIS
- (3) Accumulation pattern based on PHA Survey of Manhattan College Pathmark
- (4) 2/3 of auto dealer trips are service trips (vehicles go directly into auto dealer facility, 1/3 of auto dealer trips are sales & employee trips; assumed to use accessory garage (based on interview with an auto dealer manager). Accumulation pattern based on W. 57th St. Rezoning FEIS.
- (5) All NYPD Mounted Unit parking demand accommodated in the Stable facility. Not reflected in Total In, Out, & Accumulation

Table 13-11, 2011 Build Public Off-Street Parking Conditions

		2011 No-Build Conditions	Change	2011 Build Conditions
A M	Capacity	<u>2,779</u>	0	<u>2,779</u>
	Public Parking Demand	2,902	35	2,937
	Available Spaces	<u>-123</u>	-	<u>-158</u>
	Utilization	104%	-	106%
M D	Capacity	<u>2,779</u>	0	<u>2,779</u>
	Public Parking Demand	<u>2,467</u>	46	2,513
	Available Spaces	<u>312</u>	-	<u>266</u>
	Utilization	<u>89%</u>	-	<u>90%</u>
P M	Capacity	<u>2,779</u>	0	<u>2,779</u>
	Public Parking Demand	2,666	76	2,742
	Available Spaces	<u>113</u>	-	<u>37</u>
	Utilization	<u>96%</u>	-	<u>99%</u>
L A T E	Capacity	<u>2,779</u>	0	<u>2,779</u>
	Public Parking Demand	1,514	38	1,552
	Available Spaces	<u>1,265</u>	-	<u>1,227</u>
	Utilization	<u>54%</u>	-	<u>56%</u>
S A T M D	Capacity	<u>2,779</u>	0	<u>2,779</u>
	Public Parking Demand	1,527	37	1,564
	Available Spaces	<u>1,252</u>	-	<u>1,215</u>
	Utilization	<u>55%</u>	-	<u>56%</u>

In summary, the proposed project's parking demand would be partly accommodated on-site and partly accommodated by public parking facilities. Utilization of off-street public parking facilities would increase as a result of the proposed project, with a shortfall in capacity in the weekday AM and PM peak periods. The shortfall in public parking spaces expected under No-Build conditions in the weekday AM peak period would increase slightly under Build conditions. The small availability of spaces under No-Build conditions in the weekday PM peak period would become a small shortfall under Build conditions. According to the *CEQR Technical Manual*, for proposed actions within the Manhattan Central Business District (defined as the area south of 61st Street), the inability of the proposed action or the surrounding area to accommodate projected future parking demands would be generally considered a parking shortfall, but is not deemed to be a significant impact. The unsatisfied demand for parking spaces in the AM and PM peak hours would result in

vehicles parking outside of the quarter-mile study area and motorists walking greater distances to their destinations. As parking shortfalls do not constitute significant adverse impacts for *CEQR* purposes, mitigation is not required.

E. CONCLUSION

The effects of the proposed project on area traffic and parking conditions were analyzed during the weekday AM, weekday midday, weekday PM, and Saturday midday peak periods. Overnight conditions for parking were also considered. Although the site could be developed as-of-right under the existing zoning and is currently undergoing as-of-right foundation work, the analysis conservatively assumes that in the future without the proposed action the project site would remain vacant. This will serve as the baseline for comparing the effects of the future without and with the proposed action. The traffic analysis found that the proposed project would generate 221, 174, 220, and 182 vehicles per hour (vph), in the weekday AM, weekday midday, weekday PM, and Saturday midday peak hours respectively. This increased travel demand would result in significant adverse traffic impacts at 4, 3, 3, and 2 intersections during the weekday AM, weekday midday, weekday PM, and Saturday midday peak hours, respectively. Chapter 19, "Mitigation" describes mitigation measures to address the traffic impacts. The parking analysis found that the proposed project would generate peak parking demand in excess of the accessory parking spaces that would be provided on-site. An assessment found that there would be sufficient off-street public parking spaces available within a quarter-mile radius of the project site to accommodate the proposed project's public parking demand in the weekday midday, weekday PM, overnight, and Saturday midday peak periods. In the weekday AM peak period there would be a shortfall with a 2 percentage point increase in utilization. As per *CEQR Technical Manual* guidelines, this parking shortfall would not be considered a significant adverse impact and no mitigation is required.